
Python calculation for heat pump ProDomo13-R410A

Parametric Heat Pump calculation

Dani Carbonell

dani.carbonell@solarenergy.ch

2019/03/12 at: 16:18:55 h

Table 1: Fitted coefficients for the heat pump.

Coefficient	Description	[kW]
PQ_1	1 st condenser polynomial coefficient	1.4868e+01
PQ_2	2 st condenser polynomial coefficient	1.2747e+02
PQ_3	3 st condenser polynomial coefficient	-1.3745e+01
PQ_4	4 st condenser polynomial coefficient	-2.1650e+02
PQ_5	5 st condenser polynomial coefficient	3.9254e+02
PQ_6	6 st condenser polynomial coefficient	-7.9875e+00
$PCOP_1$	1 st COP polynomial coefficient	1.2411e+01
$PCOP_2$	2 st COP polynomial coefficient	6.1891e+01
$PCOP_3$	3 st COP polynomial coefficient	-8.3490e+01
$PCOP_4$	4 st COP polynomial coefficient	-2.3331e+02
$PCOP_5$	5 st COP polynomial coefficient	1.0307e+02
$PCOP_6$	6 st COP polynomial coefficient	1.7703e+02
\dot{m}_{cond}	3000.00 [kg/h]	
\dot{m}_{evap}	2800.00 [kg/h]	
COP_{nom} (B0W35)	4.68	
$Q_{c,nom}$ (B0W35)	12.48 kW	
COP_{nom} (B2W35)	4.92	
$Q_{c,nom}$ (B2W35)	13.17 kW	
COP_{nom} (B10W35)	6.00	
$Q_{c,nom}$ (B10W35)	16.29 kW	

Table 2: Predicting results of the heat pump.

$T_{evap,in}$ °C	$T_{evap,out}$ °C	$T_{cond,in}$ °C	$T_{cond,out}$ °C	COP [-]	Q_{cond} [kW]	Q_{evap} [kW]	W_{comp} [kW]	\dot{m}_{cond} kg/h	\dot{m}_{evap} kg/h	ΔT_{evap} K	ΔT_{cond} K
-7.00	-9.76	26.99	30.00	4.57	10.50	8.20	2.30	3000	2800	2.8	3.0
-7.00	-9.47	35.82	38.75	3.50	10.25	7.32	2.93	3000	2800	2.5	2.9
-7.00	-9.16	44.64	47.50	2.79	9.98	6.40	3.58	3000	2800	2.2	2.9
-7.00	-8.92	53.48	56.25	2.43	9.67	5.70	3.97	3000	2800	1.9	2.8
-7.00	-8.85	62.33	65.00	2.44	9.33	5.50	3.83	3000	2800	1.9	2.7
-4.00	-7.06	26.74	30.00	4.93	11.39	9.08	2.31	3000	2800	3.1	3.3
-4.00	-6.74	35.58	38.75	3.78	11.07	8.14	2.93	3000	2800	2.7	3.2
-4.00	-6.40	44.42	47.50	2.98	10.74	7.14	3.60	3000	2800	2.4	3.1
-4.00	-6.12	53.28	56.25	2.54	10.37	6.29	4.08	3000	2800	2.1	3.0
-4.00	-5.99	62.15	65.00	2.46	9.96	5.92	4.04	3000	2800	2.0	2.9
-1.00	-4.38	26.46	30.00	5.31	12.36	10.04	2.33	3000	2800	3.4	3.5
-1.00	-4.05	35.32	38.75	4.07	11.98	9.04	2.94	3000	2800	3.0	3.4
-1.00	-3.68	44.18	47.50	3.20	11.58	7.96	3.62	3000	2800	2.7	3.3
-1.00	-3.35	53.06	56.25	2.68	11.15	6.99	4.16	3000	2800	2.4	3.2
-1.00	-3.17	61.94	65.00	2.52	10.68	6.43	4.24	3000	2800	2.2	3.1
2.00	-1.73	26.16	30.00	5.72	13.42	11.07	2.35	3000	2800	3.7	3.8
2.00	-1.38	35.03	38.75	4.40	12.98	10.03	2.95	3000	2800	3.4	3.7
2.00	-0.99	43.92	47.50	3.44	12.51	8.88	3.64	3000	2800	3.0	3.6
2.00	-0.62	52.81	56.25	2.84	12.02	7.79	4.24	3000	2800	2.6	3.4
2.00	-0.38	61.71	65.00	2.59	11.48	7.06	4.43	3000	2800	2.4	3.3
5.00	0.89	25.83	30.00	6.15	14.56	12.19	2.37	3000	2800	4.1	4.2
5.00	1.26	34.73	38.75	4.75	14.05	11.09	2.96	3000	2800	3.7	4.0
5.00	1.67	43.63	47.50	3.71	13.53	9.88	3.65	3000	2800	3.3	3.9
5.00	2.08	52.53	56.25	3.02	12.97	8.68	4.29	3000	2800	2.9	3.7
5.00	2.38	61.46	65.00	2.70	12.37	7.78	4.59	3000	2800	2.6	3.5
8.00	3.49	25.48	30.00	6.61	15.78	13.39	2.39	3000	2800	4.5	4.5
8.00	3.88	34.39	38.75	5.12	15.21	12.24	2.97	3000	2800	4.1	4.4
8.00	4.31	43.31	47.50	4.00	14.62	10.96	3.66	3000	2800	3.7	4.2
8.00	4.74	52.24	56.25	3.23	14.01	9.67	4.33	3000	2800	3.3	4.0
8.00	5.10	61.18	65.00	2.82	13.35	8.62	4.73	3000	2800	2.9	3.8
11.00	6.06	25.11	30.00	7.09	17.08	14.67	2.41	3000	2800	4.9	4.9
11.00	6.46	34.04	38.75	5.52	16.45	13.47	2.98	3000	2800	4.5	4.7
11.00	6.91	42.98	47.50	4.31	15.80	12.13	3.66	3000	2800	4.1	4.5
11.00	7.38	51.92	56.25	3.46	15.12	10.76	4.36	3000	2800	3.6	4.3
11.00	7.78	60.87	65.00	2.97	14.41	9.56	4.84	3000	2800	3.2	4.1
14.00	8.60	24.71	30.00	7.59	18.46	16.03	2.43	3000	2800	5.4	5.3
14.00	9.02	33.66	38.75	5.94	17.76	14.78	2.99	3000	2800	5.0	5.1
14.00	9.49	42.62	47.50	4.65	17.05	13.39	3.67	3000	2800	4.5	4.9
14.00	9.98	51.58	56.25	3.72	16.32	11.94	4.38	3000	2800	4.0	4.7
14.00	10.43	60.55	65.00	3.15	15.55	10.61	4.94	3000	2800	3.6	4.5
17.00	11.12	24.30	30.00	8.13	19.92	17.46	2.45	3000	2800	5.9	5.7
17.00	11.55	33.26	38.75	6.39	19.16	16.16	3.00	3000	2800	5.4	5.5
17.00	12.04	42.23	47.50	5.02	18.39	14.72	3.67	3000	2800	5.0	5.3
17.00	12.55	51.21	56.25	4.00	17.60	13.20	4.39	3000	2800	4.4	5.0
17.00	13.04	60.20	65.00	3.35	16.77	11.76	5.01	3000	2800	4.0	4.8
20.00	13.61	23.86	30.00	8.68	21.45	18.98	2.47	3000	2800	6.4	6.1
20.00	14.06	32.84	38.75	6.86	20.63	17.63	3.01	3000	2800	5.9	5.9
20.00	14.56	41.83	47.50	5.41	19.80	16.14	3.66	3000	2800	5.4	5.7
20.00	15.10	50.82	56.25	4.31	18.95	14.55	4.40	3000	2800	4.9	5.4
20.00	15.62	59.83	65.00	3.57	18.06	13.01	5.05	3000	2800	4.4	5.2




Figure 1: COP Results for the heat pump at the selected points




Figure 2: Q_c Results for the heat pump at the selected points