

RobotLog2RQM

v. 1.4.0

Tran Duy Ngoan

24.07.2024

Contents

1	Introduction	1
2	Description	2
2.1	Get Robot Framework XML result	2
2.2	Tool features	2
2.2.1	Usage	3
2.2.2	Basic import feature	3
2.2.3	Verify the given arguments	4
2.2.4	Import multiple *.xml result files	4
2.2.5	Create missing Test Case on RQM	4
2.2.6	Update existing Test Case on RQM	5
2.2.7	Test suite feature	5
2.2.8	Project with Configuration Management (CM)	5
2.3	Robot Framework Test Case Information on RQM:	6
3	CRQM.py	8
3.1	Function: get_xml_tree	8
3.2	Class: CRQMClient	8
3.2.1	Method: login	9
3.2.2	Method: verifyProjectName	9
3.2.3	Method: disconnect	9
3.2.4	Method: config	9
3.2.5	Method: userURL	10
3.2.6	Method: integrationURL	10
3.2.7	Method: webIDfromResponse	11
3.2.8	Method: webIDfromGeneratedID	11
3.2.9	Method: getResourceByID	11
3.2.10	Method: getAllByResource	12
3.2.11	Method: getAllBuildRecords	12
3.2.12	Method: getAllConfigurations	12
3.2.13	Method: getAllTeamAreas	12
3.2.14	Method: addTeamAreaNode	13
3.2.15	Method: createTestcaseTemplate	13
3.2.16	Method: createTCERTemplate	14
3.2.17	Method: createExecutionResultTemplate	15
3.2.18	Method: createBuildRecordTemplate	16
3.2.19	Method: createConfigurationTemplate	16

3.2.20	Method: createTSERTemplate	17
3.2.21	Method: createTestsuiteResultTemplate	17
3.2.22	Method: createTestsuiteTemplate	18
3.2.23	Method: createResource	19
3.2.24	Method: createBuildRecord	19
3.2.25	Method: createConfiguration	20
3.2.26	Method: updateResourceByID	20
3.2.27	Method: linkListTestcase2Testplan	21
3.2.28	Method: linkListTestcase2Testsuite	21
3.2.29	Method: addTestsuite2Testplan	22
4	robotlog2rqm.py	23
4.1	Function: get_from_tags	23
4.2	Function: convert_to_datetime	23
4.3	Function: process_suite_metadata	24
4.4	Function: process_metadata	24
4.5	Function: process_suite	24
4.6	Function: process_test	25
4.7	Function: RobotLog2RQM	25
4.8	Class: Logger	26
4.8.1	Method: config	26
4.8.2	Method: log	26
4.8.3	Method: log_warning	27
4.8.4	Method: log_error	27
5	Appendix	28
6	History	29

Chapter 1

Introduction

RobotLog2RQM facilitates the import of Robot Framework result file(s) in ***.xml** format into IBM® Rational® Quality Manager (RQM) resources.

It introduces the **CRQM Class**, offering the capability to interact with various RQM resources, including test plans, test cases, builds, and more, through the [RqmAPI](#) to:

- retrieve RQM resources: obtain resources by a given ID or retrieve all available entities of a specified resource type.
- update RQM resources: modify existing resources by providing the relevant ID.
- create new RQM resources: generate new resources using predefined templates located in the [RQM.templates](#) folder.

So that **RobotLog2RQM** tool can:

- create all required resources (*Test Case Execution Record*, *Test Case Execution Result*, ...) for new test cases on RQM.
- link all test cases to provided test plan.
- add new test results for existing test cases on RQM.
- update existing test cases on RQM.

Chapter 2

Description

2.1 Get Robot Framework XML result

In order to manage test cases and their results Rational Quality Manager (RQM), certain traceable information, such as version, test case ID, component, etc., is required.

This enables the **RobotLog2RQM** tool to associate the imported test results with specific elements (Test Case) or link them to other entities (Build Record, Test Environment) in RQM.

These information should be provided in **Metadata** (for the whole testsuite/execution info: version, build, ...) and **[Tags]** information (for specific test case info: component, test case ID, requirement ID, ...) of Robot Framework test case. Then when executing Robot Framework test case(s), the generated Robot Framework result file (default is *output.xml*) will contain all of them and ready for importing.

Sample Robot Framework test case with the necessary information for importing to RQM:

```

*** Settings ***
Metadata  project      ROBFW          # Test Environment on RQM for linking
Metadata  version_sw   SW_VERSION_0.1 # Build Record on RQM for linking
Metadata  machine      ${COMPUTERNAME} # Hostname attribute in RQM Test Case Result
Metadata  component    Import_Tools    # Component attribute in RQM Test Case
Metadata  team-area    Internet Team RQM # team-area (case-sensitive) on RQM for linking

*** Test Cases ***
Testcase 01
  [Documentation] This test is traceable with provided tcid
  [Tags] TCID-1001 FID-112 FID-111 robotfile=https://github.com/test-fullautomation
  Log      This is Testcase 01

Testcase 02
  [Documentation] This new test case will be created if -createmissing argument
  ... is provided when importing
  [Tags] FID-113 robotfile=https://github.com/test-fullautomation
  Log      This is Testcase 02

```

Listing 2.1: Sample Robot Framework test case

Hint



In case you are using RobotFramework AIO, above highlighted **Metadata** definitions are not required because they have been handled by **RobotFramework.TestsuitesManagement** library within **Suite Setup**.

2.2 Tool features

After getting the Robot Framework **.xml* result file(s), you can use the **RobotLog2RQM** tool to import them into RQM.

Its usage and features are described as following sections.

2.2.1 Usage

Use below command to get tools's usage:

```
RobotLog2DB -h
```

The tool's usage should be showed as below:

```
usage: RobotLog2RQM (RobotXMLResult to RQM importer) [-h] [-v] [--testsuite TESTSUITE] ↵
  ↵ [--recursive] [--createmissing] [--updatetestcase] [--dryrun] [--stream STREAM] ↵
  ↵ [--baseline BASELINE]
                                     resultxmlfile host project user ↵
  ↵ password testplan

RobotLog2RQM imports XML result files (default: output.xml) generated by the Robot ↵
  ↵ Framework into an IBM Rational Quality Manager.

positional arguments:
  resultxmlfile          absolute or relative path to the xml result file or directory of ↵
  ↵ result files to be imported.
  host                   RQM host url.
  project                project on RQM.
  user                   user for RQM login.
  password               password for RQM login.
  testplan               testplan ID for this execution.

optional arguments:
  -h, --help             show this help message and exit
  -v, --version          Version of the RobotLog2RQM importer.
  --testsuite TESTSUITE testsuite ID for this execution. If 'new', then create a new testsuite for this execution.
  --recursive            if set, then the path is searched recursively for log files to ↵
  ↵ be imported.
  --createmissing        if set, then all testcases without tcid are created when importing.
  --updatetestcase      if set, then testcase information on RQM will be updated bases ↵
  ↵ on robot testfile.
  --dryrun              if set, then verify all input arguments (includes RQM ↵
  ↵ authentication) and show what would be done.
  --stream STREAM       project stream. Note, requires Configuration Management (CM) to ↵
  ↵ be enabled for the project area.
  --baseline BASELINE   project baseline. Note, requires Configuration Management (CM), ↵
  ↵ or Baselines Only to be enabled for the project area.
```

As above instruction, **RobotLog2RQM** tool requires 5 positional arguments consists of:

- The Robot Framework result file/folder `resultxmlfile`
- The RQM authentication `host` , `project` , `user` , `password`
- The RQM `testplan` ID which will contains all importing test results

2.2.2 Basic import feature

Use the below command for the simple import the `output.xml` file to RQM project **ROBFW-AIO** which is hosted at <https://sample-rqm-host.com>

```
RobotLog2RQM output.xml https://sample-rqm-host.com ROBFW-AIO test_user test_pw 720
```

When command is executed, the tool will process with following steps:

- Login the RQM server with the provided credential, then verify the existences of given `project` , `testplan` on RQM
- Create RQM **Build Record** and **Test Environment** (if already provided in Robot Framework test case and not existing on RQM)

- Create new RQM **Test Case Execution Record - TCER** (if it is not existing) bases on test case ID (defined `TCID-xxx` in `[Tags]` of Robot Framework Test Cases) and `testplan` ID
- Create new RQM **Test Case Execution Result** which contents the detail and result state of Robot Framework test case
- Link all test case(s) to provided `testplan`

2.2.3 Verify the given arguments

In case you just want to verify whether the given `*.xml` file/folder and the RQM authentication in arguments are corrected or not, the optional argument `--dryrun` will help to do it.

In the dryrun mode, **RobotLog2RQM** will not create any resources on RQM, it just verify:

- The given Robot Framework result file/folder is valid or not
- The given RQM authentication is correct or not
- The given RQM project and testplan are existing or not

2.2.4 Import multiple *.xml result files

RobotLog2RQM accepts the first argument `resultxmlfile` can be a single file or the folder that contains multiple Robot Framework result files.

When the folder is used, **RobotLog2RQM** will only search for `*.xml` file under given directory and exclude any file within subdirectories as default.

In case you have result file(s) under the subdirectory of given folder and want these result files will also be imported, the optional argument `--recursive` should be used when executing **RobotLog2RQM** command.

When `--recursive` argument is set, **RobotLog2RQM** will walk through the given directory and its subdirectories to discover and collect all available `*.xml` for importing.

For example: your result folder has a structure as below:

```
logFolder
|_____ result_1.xml
|_____ result_2.xml
|_____ subFolder_1
|         |_____ result_sub_1.xml
|         |_____ subSubFolder
|         |         |_____ result_sub_sub_1.xml
|_____ subFolder_2
|         |_____ result_sub_2.xml
```

- Without `--recursive` : only `result_1.xml` and `result_2.xml` are found for importing.
- With `--recursive` : all `result_1.xml`, `result_2.xml`, `result_sub_1.xml`, `result_sub_2.xml` and `result_sub_sub_1.xml` will be imported.

2.2.5 Create missing Test Case on RQM

By default, **RobotLog2RQM** tool will not touch (create, update) any RQM Test Case.

If the `TCID-xxx` information is missing in `[Tags]` section of Robot Framework Test Case, an error message will be raised for that specific importing Test Case, and the tool will proceed with the next Test Cases accordingly

```
ERROR: There is no 'tcid' information for importing test 'Testcase 01'.
```

So that, in order to import those missing `TCID-xxx` Test Cases, the optional arguments `--createmissing` should be provided in the **RobotLog2RQM** arguments.

When `--createmissing` is used, **RobotLog2RQM** will help to create RQM Test Cases bases on the defined information in Robot Framework Test Cases. It obtains the new Test Case ID and uses it for linking to related RQM resources **TCER**, **Test Case Execution Result** as basic feature.

The new IDs for the created Test Cases are also displayed in the execution log. You can copy these IDs and update the `TCID-xxx` information in Robot Framework Test Cases for the next execution. This information will then be available in the generated `*.xml` result file for importing.

Please refer [Robot Framework Test Case Information on RQM](#) section for details on how the defined information in Robot Framework Test Cases is reflected in RQM.

2.2.6 Update existing Test Case on RQM

In case the Test Case is existing on RQM, but you want to update its attribute(s) such as **Component**, **Description**, ... the optional argument `--updatetestcase` should be used.

RobotLog2RQM will update RQM Test Case resource bases on the defined information in Robot Framework Test Case before creating its result.

Please refer [Robot Framework Test Case Information on RQM](#) section for details on how the defined information in Robot Framework Test Cases is reflected in RQM.

2.2.7 Test suite feature

In addition to managing the imported test results by testplan, the **RobotLog2RQM** tool also supports the use of testsuite with the optional argument `--testsuite TESTSUITE`.

This argument provides two main features:

- **Importing to an existing testsuite:** If you specify the ID of an existing testsuite using the `--testsuite TESTSUITE` argument, the tool will import the test results directly into that testsuite.

Example: testsuite with id `1234` is already existing

```
RobotLog2RQM output.xml https://sample-rqm-host.com ROBFW-AIO test_user test_pw 720 ↔
↔ --testsuite 1234
```

- **Creating a new testsuite and then importing:** If you set the value to `new` using the `--testsuite new` argument, the tool will create a new testsuite and then import the test results into this newly created testsuite.

Example:

```
RobotLog2RQM output.xml https://sample-rqm-host.com ROBFW-AIO test_user test_pw 720 ↔
↔ --testsuite new
```

When using the `--testsuite` argument, the tool will follow these additional steps besides the basic steps which is described in above [Basic import feature](#) section.

- Verify the existence of given `testsuite`. Or create the new **Test Suite** if `new` value is used.
- Create a **Test Suite Execution Record** for given (or newly created) `testsuite`.
- Create a **Test Suite Result** which contains all **Test Case Execution Result**.
- Link all test cases to the given (or newly created) `testsuite`.
- Add that `testsuite` to the given `testplan`.

2.2.8 Project with Configuration Management (CM)

When Configuration Management (CM) is enabled for the project area, it is necessary to specify the project stream or baseline when executing import tool to interact with the proper stream/baseline resources.

Otherwise, the tool will not be able to correctly associate the imported test results.

Configuration Management (CM) is only enabled by Project Administrator as below figure:

The screenshot shows the IBM Engineering Test Management (qtm) Administration - Engineering Test Management (/qtm) interface. The page title is "Administration - Engineering Test Management (/qtm)". The main content area is titled "Configuration Management" and includes a question: "Use configurations to create and work with multiple versions of artifacts and manage reuse. What do you want to do with configurations?". There are three radio button options: "Nothing", "Enable only baselines", and "Enable full configuration management (to do multi-stream development, use components, and reuse versioned artifacts)". The third option is selected. Below the options, there is a text block explaining that with configuration management, you can create multiple development streams and baselines in a project area. It also includes an "Important:" section with bullet points: "After you enable configuration management, you cannot disable it. Before you continue, ensure that you have a backup.", "If you integrate with other non-ELM tools, such as through linking or synchronizing data, you must understand how they link to your ELM applications. In other tools, versions of artifacts might not exist in multiple streams or baselines, so enabling configuration management might cause unexpected behavior.", and "To decide whether to enable this capability, see Considerations before enabling configuration management." There is also a link to "Reporting on data in configurations." and a note about OSLC linking requirements. At the bottom right, there is a blue button labeled "Enable Configuration Management".

The following arguments are used to provide this information:

- `--stream STREAM` : specifies the project `STREAM` .
A project stream represents a branch of work within a project area. When CM is enabled, it is crucial to provide this option to correctly associate the imported test results with the appropriate stream.
Example:

```
RobotLog2RQM output.xml https://sample-rqm-host.com ROBFW-AIO test_user test_pw ↵
↵ 720 --stream "Develop_stream"
```

- `--baseline BASELINE` : specifies the project `BASELINE` .
A baseline captures the state of project artifacts at a particular point in time. When CM or Baselines Only is enabled, this option is required to ensure that the test results are linked to the correct baseline.
Example:

```
RobotLog2RQM output.xml https://sample-rqm-host.com ROBFW-AIO test_user test_pw ↵
↵ 720 --baseline "Baseline_v1"
```

Note



Only one option (`--stream` or `--baseline`) should be used at a time.
If both options are provided, the `--stream` option will take precedence.

2.3 Robot Framework Test Case Information on RQM:

For more detail about the mapping between the defined information from Robot Framework Test Case to Robot Framework result (*output.xml*) file and their reflections on RQM WebApp, please refer below mapping table:

RQM data		Robot Framework	
Resource	Attribute/ Field	Testsuite/Testcase	Output.xml
Build Record	Title	<code>Metadata version_sw Build</code>	<code>//suite/metadata/item[@name="version_sw"]</code>
Test Environment	Title	<code>Metadata project Environment</code>	<code>//suite/metadata/item[@name="project"]</code>
Test Case	ID	<code>[Tags] tcid-xxx</code>	<code>//suite/test/tags/tag[@text="tcid-xxx"]</code>
	Name	tesname	<code>//suite/test/@name</code>
	Team Area	<code>Metadata team-area Team_Area</code>	<code>//suite/metadata/item[@name="team-area"]</code>
	Description	test doc - <code>[Documentation]</code>	<code>//suite/test/doc/@text</code>
	Owner	provided <code>user</code> in cli	
	Component/ Categories	<code>Metadata component Component</code>	<code>//suite/metadata/item[@name="component"]</code>
	Requirement ID	<code>[Tags] fid-yyy</code>	<code>//suite/test/tags/tag[@text="fid-yyy"]</code>
	Robot File	<code>[Tags] robotfile-zzz</code>	<code>//suite/test/tags/tag[@text="robotfile-zzz"]</code>
Test Case Execution Record (TCER)	Owner	provided <code>user</code> in cli	
	Team Area	<code>Metadata team-area Team_Area</code>	<code>//suite/metadata/item[@name="team-area"]</code>
	Test Plan	Interaction URL to provided <code>testplan</code> in cli	
	Test Case	Interaction URL to provided test case ID: provided tcid in <code>[Tags]: tcid-xxx</code> or generated tcid when using <code>-createmissing</code>	<code>//suite/test/tags/tag[@text="tcid-xxx"]</code>
	Test Environment	<code>Metadata project Environment</code>	<code>//suite/metadata/item[@name="project"]</code>
Test Result	Owner	provided <code>user</code> in cli	
	Tested By	provided <code>user</code> in cli - userid must be used	
	Team Area	<code>Metadata team-area Team_Area</code>	<code>//suite/metadata/item[@name="team-area"]</code>
	Actual Result	Test case result (PASSED , FAILED , UNKNOWN)	<code>//suite/test/status/@status</code>
	Host Name	<code>Metadata machine ↔ ↔ % {COMPUTERNAME}</code>	<code>//suite/metadata/item[@name="machine"]</code>
	Test Plan	Interaction URL to provided <code>testplan</code> in cli	
	Test Case	Interaction URL to provided test case ID: provided tcid in <code>[Tags]: tcid-xxx</code> or generated tcid when using <code>-createmissing</code>	<code>//suite/test/tags/tag[@text="tcid-xxx"]</code>
	Test Case Execution Record	Interaction URL to TCER ID	
	Build	<code>Metadata version_sw Build</code>	<code>//suite/metadata/item[@name="version_sw"]</code>
	Start Time	Test case start time	<code>//suite/test/status/@starttime</code>
	End Time	Test case end time	<code>//suite/test/status/@endtime</code>
	Total Run Time	Calculated from start and end time	
Result Details	Test case message log	<code>//suite/test/status/@text</code>	

Table 2.1: RQM data & Robot Framework

Chapter 3

CRQM.py

3.1 Function: get_xml_tree

Parse xml object from file.

Arguments:

- `file_name`
/ *Condition*: required / *Type*: str /
Path to file or file-like object.
- `bdt_validation`
/ *Condition*: optional / *Type*: bool /
If True, validate against a DTD referenced by the document.

Returns:

- `oTree`
/ *Type*: lxml.etree.ElementTree object /
The xml etree object.

3.2 Class: CRQMClient

Imported by:

```
from RobotLog2RQM.CRQM import CRQMClient
```

CRQMClient class uses RQM REST APIs to get, create and update resources (testplan, testcase, test result, ...) on RQM - Rational Quality Manager

Resource type mapping:

- `buildrecord`: Build Record
- `configuration`: Test Environment
- `testplan`: Test Plan
- `testsuite`: Test Suite
- `suiteexecutionrecord`: Test Suite Execution Record (TSER)
- `testsuitelog`: Test Suite Log
- `testcase`: Test Case
- `executionworkitem`: Test Execution Record (TCER)
- `executionresult`: Execution Result

3.2.1 Method: login

Log in RQM by provided user & password.

Arguments:

(no arguments)

Returns:

- bSuccess
/ Type: bool /
Indicates if the computation of the method login was successful or not.

3.2.2 Method: verifyProjectName

Verify the project name by searching it in project-areas XML response.

Arguments:

(no arguments)

Returns:

- bSuccess
/ Type: bool /
Indicates if the computation of the method verifyProjectName was successful or not.

3.2.3 Method: disconnect

Disconnect from RQM.

Arguments:

(no arguments)

Returns:

(no returns)

3.2.4 Method: config

Configure RQMClient with testplan ID, build, configuration, createmissing, ...

- Verify the existence of provided testplan ID.
- Verify the existences of provided build and configuration names before creating new ones.

Arguments:

- plan_id
/ Condition: required / Type: str /
Testplan ID of RQM project for importing result(s).
- build_name
/ Condition: optional / Type: str / Default: None /
The Build Record for linking result(s). Set it to None if not be used, the empty name " " will lead to error.
- config_name
/ Condition: optional / Type: str / Default: None /
The Test Environment for linking result(s). Set it to None if not be used, the empty name " " may lead to error.
- createmissing
/ Condition: optional / Type: bool / Default: False /
If True, the testcase without tcid information will be created on RQM.

- `update testcase`
/ *Condition*: optional / *Type*: bool / *Default*: False /
If True, the information of testcase on RQM will be updated bases on robot testfile.
- `suite_id` (optional)
/ *Condition*: optional / *Type*: str / *Default*: None /
Testsuite ID of RQM project for importing result(s).

Returns:*(no returns)***3.2.5 Method: userURL**

Return interaction URL of provided userID

Arguments:

- `userID`
/ *Condition*: required / *Type*: str /
The user ID.

Returns:

- `userURL`
/ *Type*: str /
The interaction URL of provided userID.

3.2.6 Method: integrationURLReturn interaction URL of provided resource and ID. The provided ID can be `internalID` (contains only digits) or `externalID`.**Arguments:**

- `resourceType`
/ *Condition*: required / *Type*: str /
The RQM resource type (e.g: "testplan", "testcase", ...).
- `id`
/ *Condition*: optional / *Type*: str / *Default*: None /
The ID of given resource.
 - If given: the specified url to resource ID is returned.
 - If None: the url to resource type (to get all entity) is returned.
- `forceinternalID`
/ *Condition*: optional / *Type*: bool / *Default*: False /
If True, force to return the url of resource as internal ID.

Returns:

- `integrationURL`
/ *Type*: str /
The interaction URL of provided resource and ID.

3.2.7 Method: webIDfromResponse

Get internal ID (number) from response of POST method.

Note: Only executionresult has response text. Other resources has only response header.

Arguments:

- response
/ *Condition*: required / *Type*: str /
The xml response from POST method for parsing ID information.
- tagID
/ *Condition*: optional / *Type*: str / *Default*: 'rqm:resultId' /
Tag name which contains ID information.

Returns:

- resultId
/ *Type*: str /
The internal ID (as number).

3.2.8 Method: webIDfromGeneratedID

Return web ID (ns2:webId) from generate ID by get resource data from RQM.

Note:

- This method is only used for generated testcase, executionworkitem and executionresult.
- buildrecord and configuration does not have ns2:webId in response data.

Arguments:

- resourceType
/ *Condition*: required / *Type*: str /
The RQM resource type.
- generateID
/ *Condition*: required / *Type*: str /
The Slug ID which is returned in Content-Location from POST response.

Returns:

- webID
/ *Type*: str /
The web ID (as number).

3.2.9 Method: getResourceByID

Return data of provided resource and ID by GET method

Arguments:

- resourceType
/ *Condition*: required / *Type*: str /
The RQM resource type.

- `id`
/ *Condition*: required / *Type*: str /
ID of resource.

Returns:

- `res`
/ *Type*: Response object /
Response data of GET request.

3.2.10 Method: getAllByResource

Return all entries (in all pages) of provided resource by GET method.

Arguments:

- `resourceType`
/ *Condition*: required / *Type*: str /
The RQM resource type.

Returns:

- `dReturn`
/ *Type*: dict /
A dictionary which contains response status, message and data.
Example:

```
{
  'success' : False,
  'message' : '',
  'data'    : {}
}
```

3.2.11 Method: getAllBuildRecords

Get all available build records of project on RQM and store them into `dBuildVersion` property.

Arguments:

(no arguments)

Returns:

(no returns)

3.2.12 Method: getAllConfigurations

Get all available configurations of project on RQM and store them into `dConfiguration` property.

Arguments:

(no arguments)

Returns:

(no returns)

3.2.13 Method: getAllTeamAreas

Get all available team-areas of project on RQM and store them into `dTeamAreas` property.

Example:

```
{
  'teamA' : '{host}/qm/process/project-areas/{project-id}/team-areas/{teamA-id}',
  'teamB' : '{host}/qm/process/project-areas/{project-id}/team-areas/{teamB-id}'
}
```

Arguments:*(no arguments)***Returns:***(no returns)***3.2.14 Method: addTeamAreaNode**

Append team-area node which contains URL to given team-area into xml template.

Note: team-area information is case-casesensitive

Arguments:

- root
/ *Condition:* required / *Type:* Element object /
The xml root object.
- sTeam
/ *Condition:* required / *Type:* str /
Team name to be added.

Returns:

- root
/ *Type:* str /
The xml root object with addition team-area node.

3.2.15 Method: createTestcaseTemplate

Return testcase template from provided information.

Arguments:

- testcaseName
/ *Condition:* required / *Type:* str /
Testcase name.
- sDescription
/ *Condition:* optional / *Type:* str / *Default:* " /
Testcase description.
- sComponent
/ *Condition:* optional / *Type:* str / *Default:* " /
Component which testcase is belong to.
- sFID
/ *Condition:* optional / *Type:* str / *Default:* " /
Function ID (requirement ID) for linking.
- sTeam
/ *Condition:* optional / *Type:* str / *Default:* " /
Team name for linking.

- `sRobotFile`
/ *Condition*: optional / *Type*: str / *Default*: " /
Link to robot file on source control.
- `sTestType`
/ *Condition*: optional / *Type*: str / *Default*: " /
Test type information.
- `sASIL`
/ *Condition*: optional / *Type*: str / *Default*: " /
ASIL information.
- `sOwnerID`
/ *Condition*: optional / *Type*: str / *Default*: " /
User ID of testcase owner.
- `sTCtemplate`
/ *Condition*: optional / *Type*: str / *Default*: None /
Existing testcase template as xml string.
If not provided, template file under RQM_templates is used as default.

Returns:

- `sTCxml`
/ *Type*: str /
The xml testcase template as string.

3.2.16 Method: createTCERTemplate

Return testcase execution record template from provided information.

Arguments:

- `testcaseID`
/ *Condition*: required / *Type*: str /
Testcase ID for linking.
- `testcaseName`
/ *Condition*: required / *Type*: str /
Testcase name.
- `testplanID`
/ *Condition*: required / *Type*: str /
Testplan ID for linking.
- `confID`
/ *Condition*: optional / *Type*: str / *Default*: " /
Configuration - Test Environment for linking.
- `sTeam`
/ *Condition*: optional / *Type*: str / *Default*: " /
Team name for linking.
- `sOwnerID`
/ *Condition*: optional / *Type*: str / *Default*: " /
User ID of testcase owner.

Returns:

- sTCERxml
/ *Type*: str /
The xml testcase execution record template as string.

3.2.17 Method: createExecutionResultTemplate

Return testcase execution result template from provided information.

Arguments:

- testcaseID
/ *Condition*: required / *Type*: str /
Testcase ID for linking.
- testcaseName
/ *Condition*: required / *Type*: str /
Testcase name.
- testplanID
/ *Condition*: required / *Type*: str /
Testplan ID for linking.
- TCERID
/ *Condition*: required / *Type*: str /
Testcase execution record (TCER) ID for linking.
- resultState
/ *Condition*: required / *Type*: str /
Testcase result status.
- startTime
/ *Condition*: required / *Type*: str /
Testcase start time.
- endTime
/ *Condition*: optional / *Type*: str / *Default*: " /
Testcase end time.
- duration
/ *Condition*: optional / *Type*: str / *Default*: " /
Testcase duration.
- testPC
/ *Condition*: optional / *Type*: str / *Default*: " /
Test PC which executed testcase.
- testBy
/ *Condition*: optional / *Type*: str / *Default*: " /
User ID who executed testcase.
- lastlog
/ *Condition*: optional / *Type*: str / *Default*: " /
Traceback information (for Failed testcase).

- buildrecordID
/ *Condition*: optional / *Type*: str / *Default*: " /
Build Record ID for linking.
- sTeam
/ *Condition*: optional / *Type*: str / *Default*: " /
Team name for linking.
- sOwnerID
/ *Condition*: optional / *Type*: str / *Default*: " /
User ID of testcase owner.

Returns:

- sTCResultxml
/ *Type*: str /
The xml testcase result template as string.

3.2.18 Method: createBuildRecordTemplate

Return build record template from provided build name.

Arguments:

- buildName
/ *Condition*: required / *Type*: str /
Build Record name.

Returns:

- sBuildxml
/ *Type*: str /
The xml build template as string.

3.2.19 Method: createConfigurationTemplate

Return configuration - Test Environment template from provided configuration name.

Arguments:

- buildName
/ *Condition*: required / *Type*: str /
Configuration - Test Environment name.

Returns:

- sEnvironmentxml
/ *Type*: str /
The xml test environment template as string.

3.2.20 Method: createTSERTemplate

Return testsuite execution record (TSER) template from provided configuration name.

Arguments:

- testsuiteID
/ *Condition*: required / *Type*: str /
Testsuite ID.
- testsuiteName
/ *Condition*: required / *Type*: str /
Testsuite name.
- testplanID
/ *Condition*: required / *Type*: str /
Testplan ID for linking.
- confID
/ *Condition*: optional / *Type*: str / *Default*: " /
Configuration - Test Environment ID for linking.
- sOwnerID
/ *Condition*: optional / *Type*: str / *Default*: " /
User ID of testsuite owner.

Returns:

- sTSxml
/ *Type*: str /
The xml testsuite template as string.

3.2.21 Method: createTestsuiteResultTemplate

Return testsuite execution result template from provided configuration name.

Arguments:

- testsuiteID
/ *Condition*: required / *Type*: str /
Testsuite ID.
- testsuiteName
/ *Condition*: required / *Type*: str /
Testsuite name.
- TSERID
/ *Condition*: required / *Type*: str /
Testsuite execution record (TSER) ID for linking.
- lTCER
/ *Condition*: required / *Type*: str /
List of testcase execution records (TCER) for linking.
- lTCResults
/ *Condition*: required / *Type*: str /
List of testcase results for linking.

- `startTime`
/ *Condition*: optional / *Type*: str / *Default*: " /
Testsuite start time.
- `endTime`
/ *Condition*: optional / *Type*: str / *Default*: " /
Testsuite end time.
- `duration`
/ *Condition*: optional / *Type*: str / *Default*: " /
Testsuite duration.
- `sOwnerID`
/ *Condition*: optional / *Type*: str / *Default*: " /
User ID of testsuite owner.

Returns:

- `sTSResultxml`
/ *Type*: str /
The xml testsuite result template as string.

3.2.22 Method: createTestsuiteTemplate

Return testcase template from provided information.

Arguments:

- `testsuiteName`
/ *Condition*: required / *Type*: str /
Testsuite name.
- `sDescription`
/ *Condition*: optional / *Type*: str / *Default*: " /
Testsuite description.
- `sOwnerID`
/ *Condition*: optional / *Type*: str / *Default*: " /
User ID of testsuite owner.
- `sSTemplate`
/ *Condition*: optional / *Type*: str / *Default*: None /
Existing testsuite template as xml string.
If not provided, template file under RQM_templates is used as default.

Returns:

- `sTSxml`
/ *Type*: str /
The xml testsuite template as string.

3.2.23 Method: createResource

Create new resource with provided data from template by POST method.

Arguments:

- resourceType
/ Condition: required / Type: str /
Resource type.
- content
/ Condition: required / Type: str /
The xml template as string.

Returns:

- returnObj
/ Type: dict /
A dictionary reponse which contains status, ID, status_code and error message.
Example:

```
{
  'success' : False,
  'id': None,
  'message': '',
  'status_code': ''
}
```

3.2.24 Method: createBuildRecord

Create new build record.

Arguments:

- sBuildSWVersion
/ Condition: required / Type: str /
Build version - Build Record name.
- forceCreate
/ Condition: optional / Type: bool / Default: False /
If True, force to create new build record without existing verification.

Returns:

- returnObj
/ Type: dict /
A dictionary reponse which contains status, ID, status_code and error message.
Example:

```
{
  'success' : False,
  'id': None,
  'message': '',
  'status_code': ''
}
```

3.2.25 Method: createConfiguration

Create new configuration - test environment.

Arguments:

- `sConfigurationName`
/ *Condition*: required / *Type*: str /
Configuration - Test Environment name.
- `forceCreate`
/ *Condition*: optional / *Type*: str / *Default*: False /
If True, force to create new Test Environment without existing verification.

Returns:

- `returnObj`
/ *Type*: dict /
A dictionary reponse which contains status, ID, status_code and error message.
Example:

```
{
  'success' : False,
  'id': None,
  'message': '',
  'status_code': ''
}
```

3.2.26 Method: updateResourceByID

Update data of provided resource and ID by PUT method.

Arguments:

- `resourceType`
/ *Condition*: required / *Type*: str /
Resource type.
- `id`
/ *Condition*: required / *Type*: str /
Resource id.
- `content`
/ *Condition*: required / *Type*: str /
The xml template as string.

Returns:

- `res`
/ *Type*: Response object /
Response object from PUT request.

3.2.27 Method: linkListTestcase2Testplan

Link list of test cases to provided testplan ID.

Arguments:

- testplanID
/ *Condition*: required / *Type*: str /
Testplan ID to link given testcase(s).
- lTestcases
/ *Condition*: optional / *Type*: list / *Default*: None /
List of testcase(s) to be linked with given testplan.
If not provide, lTestcaseIDs property will be used as list of testcase.

Returns:

- returnObj
/ *Type*: dict /
Response dictionary which contains status and error message.
Example:

```
{
  'success' : False,
  'message' : ''
}
```

3.2.28 Method: linkListTestcase2Testsuite

Link list of test cases to provided testsuite ID

Arguments:

- testsuiteID
/ *Condition*: required / *Type*: str /
Testsuite ID to link given testcase(s).
- lTestcases
/ *Condition*: optional / *Type*: list / *Default*: None /
List of testcase(s) to be linked with given testplan.
If not provide, lTestcaseIDs property will be used as list of testcase.

Returns:

- returnObj
/ *Type*: dict /
Response dictionary which contains status and error message.
Example:

```
{
  'success' : False,
  'message' : ''
}
```

3.2.29 Method: addTestsuite2Testplan

Add testsuite ID to provided testplan ID

Arguments:

- testplanID
/ *Condition*: required / *Type*: str /
Testplan ID to link given testsuite ID.
- testsuiteID
/ *Condition*: optional / *Type*: str / *Default*: None /
Testsuite to be linked with given testplan.
If not provide, testsuite['id'] value will be used as id of testsuite.

Returns:

- returnObj
/ *Type*: dict /
Response dictionary which contains status and error message.

Example:

```
{  
  'success' : False,  
  'message' : ''  
}
```

Chapter 4

robotlog2rqm.py

4.1 Function: get_from_tags

Extract testcase information from tags.

Example: TCID-xxxx, FID-xxxx, ...

Arguments:

- `lTags`
/ *Condition:* required / *Type:* list /
List of tag information.
- `reInfo`
/ *Condition:* required / *Type:* str /
Regex to get the expected info (ID) from tag info.

Returns:

- `lInfo`
/ *Type:* list /
List of expected information (ID)

4.2 Function: convert_to_datetime

Convert time string to datetime.

Arguments:

- `time`
/ *Condition:* required / *Type:* str /
String of time.

Returns:

- `dt`
/ *Type:* datetime object /
Datetime object.

4.3 Function: process_suite_metadata

Try to find metadata information from all suite levels.

Metadata at top suite level has a highest priority.

Arguments:

- `suite`
/ *Condition*: required / *Type*: TestSuite object /
Robot suite object.
- `default_metadata`
/ *Condition*: optional / *Type*: dict / *Default*: DEFAULT_METADATA /
Initial Metadata information for updating.

Returns:

- `dMetadata`
/ *Type*: dict /
Dictionary of Metadata information.

4.4 Function: process_metadata

Extract metadata from suite result bases on DEFAULT_METADATA.

Arguments:

- `metadata`
/ *Condition*: required / *Type*: dict /
Robot metadata object.
- `default_metadata`
/ *Condition*: optional / *Type*: dict / *Default*: DEFAULT_METADATA /
Initial Metadata information for updating.

Returns:

- `dMetadata`
/ *Type*: dict /
Dictionary of Metadata information.

4.5 Function: process_suite

Process robot suite for importing to RQM.

Arguments:

- `RQMClient`
/ *Condition*: required / *Type*: RQMClient object/
RQMClient object.
- `suite`
/ *Condition*: required / *Type*: TestSuite object/
Robot suite object.

- `log_indent`
/ *Condition*: optional / *Type*: int / *Default*: 0 /
Indent for logging message.

Returns:*(no returns)*

4.6 Function: process_test

Process robot test for importing to RQM.

Arguments:

- `RQMClient`
/ *Condition*: required / *Type*: RQMClient object/
RQMClient object.
- `test`
/ *Condition*: required / *Type*: TestCase object/
Robot test object.
- `log_indent`
/ *Condition*: optional / *Type*: int / *Default*: 0 /
Indent for logging message.

Returns:*(no returns)*

4.7 Function: RobotLog2RQM

Import robot results from output.xml to RQM - IBM Rational Quality Manager.

Flow to import Robot results to RQM:

1. Process provided arguments from command line
2. Login Rational Quality Management (RQM)
3. Parse Robot results
4. Import results into RQM
5. Link all executed testcases to provided testplan/testsuite ID

Arguments:`* args`

/ *Condition*: required / *Type*: ArgumentParser object /
Argument parser object which contains:

- `resultxmlfile` : path to the xml result file or directory of result files to be imported.
- `host` : RQM host url.
- `project` : RQM project name.
- `user` : user for RQM login.
- `password` : user password for RQM login.
- `testplan` : RQM testplan ID.
- `testsuite` : testsuite ID for this execution. If 'new', then create a new testsuite for this execution.

- `recursive` : if True, then the path is searched recursively for log files to be imported.
- `createmissing` : if True, then all testcases without `tcid` are created when importing.
- `updatetestcase` : if True, then testcases information on RQM will be updated bases on robot testfile.
- `dryrun` : if True, then verify all input arguments (includes RQM authentication) and show what would be done.
- `stream` : project stream. Note, requires Configuration Management (CM) to be enabled for the project area.
- `baseline` : project baseline. Note, requires Configuration Management (CM), or Baselines Only to be enabled for the project area.

Returns:*(no returns)*

4.8 Class: Logger

Imported by:

```
from RobotLog2RQM.robotlog2rqm import Logger
```

Logger class for logging message.

4.8.1 Method: config

Configure Logger class.

Arguments:

- `output_console`
/ *Condition*: optional / *Type*: bool / *Default*: True /
Write message to console output.
- `output_logfile`
/ *Condition*: optional / *Type*: str / *Default*: None /
Path to log file output.
- `dryrun`
/ *Condition*: optional / *Type*: bool / *Default*: True /
If set, a prefix as 'dryrun' is added for all messages.

Returns:*(no returns)*

4.8.2 Method: log

Write log message to console/file output.

Arguments:

- `msg`
/ *Condition*: optional / *Type*: str / *Default*: " /
Message which is written to output.
- `color`
/ *Condition*: optional / *Type*: str / *Default*: None /
Color style for the message.

- indent
/ *Condition*: optional / *Type*: int / *Default*: 0 /
Offset indent.

Returns:

(no returns)

4.8.3 Method: log_warning

Write warning message to console/file output.

Arguments:

- msg
/ *Condition*: required / *Type*: str /
Warning message which is written to output.
- indent
/ *Condition*: optional / *Type*: int / *Default*: 0 /
Offset indent.

Returns:

(no returns)

4.8.4 Method: log_error

Write error message to console/file output.

- msg
/ *Condition*: required / *Type*: str /
Error message which is written to output.
- fatal_error
/ *Condition*: optional / *Type*: bool / *Default*: False /
If set, tool will terminate after logging error message.
- indent
/ *Condition*: optional / *Type*: int / *Default*: 0 /
Offset indent.

Returns:

(no returns)

Chapter 5

Appendix

About this package:

Table 5.1: Package setup

Setup parameter	Value
Name	RobotLog2RQM
Version	1.4.0
Date	24.07.2024
Description	Imports robot result(s) to IBM Rational Quality Manager (RQM)
Package URL	robotframework-robotlog2rqm
Author	Tran Duy Ngoan
Email	Ngoan.TranDuy@vn.bosch.com
Language	Programming Language :: Python :: 3
License	License :: OSI Approved :: Apache Software License
OS	Operating System :: OS Independent
Python required	>=3.0
Development status	Development Status :: 4 - Beta
Intended audience	Intended Audience :: Developers
Topic	Topic :: Software Development

Chapter 6

History

0.1.0	07/2022
<i>Initial version</i>	
1.1.1	01.08.2022
<i>Rework repository's document bases on GenPackageDoc</i>	
1.1.2	25.08.2022
<ul style="list-style-type: none"> - Correct indent of sourcode's docstring. - Update new style for history. 	
1.1.3	13.10.2022
<ul style="list-style-type: none"> - Fix findings and enhance README and document files - Change argument name 'outputfile' to 'resultxmlfile' 	
1.1.4	10.11.2022
<i>Rename package to RobotLog2RQM</i>	
1.2.0	09.01.2023
<ul style="list-style-type: none"> - Rework optional arguments and improve logging messages - Update README and document for publishing pypi 	
1.2.1	14.06.2023
<i>Update README: fix links issue and update installation section</i>	
1.2.2	06.03.2024
<i>Fix findings in documentation</i>	
1.2.3	14.03.2024
<i>Add support for basic authentication as an alternative to SSO system</i>	
1.2.4	11.06.2024
<i>Fix issue when test result has SKIP status</i>	
1.3.0	19.06.2024
<i>Add new feature of test suite with new optional argument <code>-testsuite TEST-SUITE</code></i>	
1.3.1	03.07.2024
<i>Add link to Test Environment for TSER when using testsuite feature</i>	
1.4.0	24.07.2024
<i>Add support project with enabled Configuration Management (multiple streams, baselines)</i>	

RobotLog2RQM.pdf

Created at 05.08.2024 - 11:59:19

by GenPackageDoc v. 0.41.1
