

Tables of ADES Tags and Structures

July 13, 2018

1 Table of ADES Elements

XML elements are the things which appear as XML tags, such as <permID> value </permID>. The ones in this table are all top-level elements, which means they can be the root of their own XML document and thus validated against XSD individually. The last element in the table, “ades,” is intended to be used as the root element for every XML document used for interchange. All elements are written in camelCase with the first character not capitalized.

Elements and their Descriptions

ADES observation sub-elements		
Name	Type	Description
permID	PermIDType	IAU permanent designation, i.e., IAU number
provID	ProvIDType	MPC provisional designation (unpacked form) for unnumbered object
artSat	StringType	Name of an artificial satellite
trkSub	TrkSubType	Observer-assigned tracklet identifier, unique within submission batch.
obsID	ObsIDType	Globally Unique Observation ID assigned by MPC
trkID	TrkIDType	Globally Unique alphanumeric tracklet ID assigned by MPC
mode	ModeType	Mode of optical and offset observations.
stn	StationType	Observatory code from MPC list.
trx	StationType	Station code of transmitting antenna.
rcv	StationType	Station code of receiving antenna.
sys	SysType	Coordinate system for station coordinates and covariance.

to be cont'd on next page

(continued)

ctr	xsd:integer	Origin of the reference system. Use public SPICE codes, e.g., 399 is the geocenter, 10 is the Sun center. Note; sys=WGS84 implies ctr=399
pos1	xsd:decimal	Position of observer, first value.
pos2	xsd:decimal	Position second value per sys
pos3	xsd:decimal	Position third value per sys
posCov11	xsd:decimal	11 covariance per sys
posCov12	xsd:decimal	12 covariance per sys
posCov13	xsd:decimal	13 covariance per sys
posCov22	xsd:decimal	22 covariance per sys
posCov23	xsd:decimal	23 covariance per sys
posCov33	xsd:decimal	33 covariance per sys
prog	ProgType	Program code as assigned by the MPC.
obsTime	TimeType	UTC time of the observation in ISO 8601 format, i.e., <i>yyyy-mm-ddThh:mm:ss.ssZ</i> .
ra	RAType	J2000.0 Astrometric equatorial right ascension in decimal degrees.
dec	DeclinationType	J2000.0 Astrometric equatorial declination in decimal degrees. Positive DEC values may optionally include a + sign
raStar	RAType	J2000.0 RA in decimal degrees of the occulted star
decStar	DeclinationType	J2000.0 DEC in decimal degrees of the occulted star
obsCenter	ObsCenterType	Center of offset observation may be planet or other body with PermID or ProvID

to be cont'd on next page

(continued)

deltaRA	xsd:decimal	Measured $\Delta(\text{RA} \cos \text{DEC})$ in arcseconds. For offset measurements of a satellite with respect to its primary, or for occultation observations with respect to the star in rectangular coordinates, J2000.0 frame.
deltaDec	xsd:decimal	Measured ΔDEC in arcseconds. For offset measurements of a satellite with respect to its primary, or for occultation observations with respect to the star in rectangular coordinates, J2000.0 frame
dist	PosDecimalType	Measured distance in arcseconds. For offset measurements of a satellite with respect to its primary, or for occultation observations with respect to the star in polar coordinates.
pa	RAType	Measured position angle in degrees. For offset measurements of a satellite with respect to its primary, or for occultation observations with respect to the star in polar coordinates.
rmsTime	PosDecimalType	Random component of the obsTime 1σ uncertainty in seconds as estimated by the observer.

to be cont'd on next page

(continued)

rmsRA	PosDecimalType	Random component of the RA cos DEC 1σ uncertainty in arcseconds as estimated by the observer as part of the image processing and astrometric reduction.
rmsDec	PosDecimalType	Random component of the DEC 1σ uncertainty in arcseconds as estimated by the observer as part of the image processing and astrometric reduction.
rmsDist	PosDecimalType	Random component of the distance 1σ uncertainty in arcseconds as estimated by the observer as part of the image processing and astrometric reduction.
rmsPA	PosDecimalType	Random component of the polar angle 1σ uncertainty in degrees as estimated by the observer as part of the image processing and astrometric reduction.
rmsCorr	CorrDecimalType	Correlation between RA and DEC or dist and PA that may result from the astrometric reduction. This is derived from the RA-DEC or dist-PA covariance matrix, where the off-diagonal term is $\text{rmsCorr} * \text{rmsRA} * \text{rmsDec}$ or $\text{rmsCorr} * \text{rmsDist} * \text{rmsPA}$.
delay	PosDecimalType	Observed radar delay value in seconds.
rmsDelay	PosDecimalType	Measurement 1σ uncertainty in μs for radar delay

to be cont'd on next page

(continued)

doppler	xsd:decimal	observed radar doppler value in Hz
rmsDoppler	PosDecimalType	Measurement 1σ uncertainty in Hz for radar doppler
astCat	CatType	Star catalog used for the astrometric reduction or for the occulted star in the case of occultation observations.)
mag	xsd:decimal	Apparent Magnitude in specified band
rmsMag	PosDecimalType	Apparent magnitude 1σ uncertainty in magnitudes.
band	BandType	Filter designation for photometry.
photCat	CatType	Star catalog used for photometry measurements.
photAp	PosDecimalType	Photometric aperture radius in arcseconds.
nucMag	LogicalType	Nuclear magnitude flag for comets. 0 for total magnitude (i.e., for most archival comet observations and all asteroid observations), 1 for nuclear magnitude. Primarily used for archival data as photAp should be used to communicate this information in the new standard
logSNR	xsd:decimal	\log_{10} of the signal-to-noise ratio of the source in the image integrated on the entire aperture used for the astrometric centroid.

to be cont'd on next page

(continued)

seeing	PosDecimalType	Size of seeing disc in arcseconds, measured at Full Width Half Maximum (FWHM) of target point spread function (PSF).
exp	PosDecimalType	Exposure time in s. Total exposure time in the case of stacked image detections
rmsFit	PosDecimalType	RMS of fit of astrometric comparison stars in arcseconds.
nStars	xsd:positiveInteger	Number of stars in astrometric fit.
com	LogicalType	Flag to indicate that the observation is reduced to the center of mass. 0 implies a measurement to the peak power position, which is usually interpreted as the leading edge of the target, with the reflection point being modeled one object radius prior to the center of mass.
frq	PosDecimalType	Carrier reference frequency in MHz
ref	RefType	Standard reference field used for citations.
disc	DiscType	Discovery flag; '*' marks a new discovery record; '+' marks the first measurement of a previously observed object; otherwise not present

to be cont'd on next page

(continued)

subFmt	SubFmtType	Format in which the observation was originally submitted to the MPC, e.g., M92 for MPC1992 format or A17 for the current standard standard. Filled by the MPC according to a list provided and maintained by the MPC.
subFrm	SubFrmType	Reference frame for the original submission of reported angular measurements.
precTime	TimePrecType	Precision in millionths of a day of the reported observation time for archived MPC1992 data records
precRA	RaDecPrecType	Precision in seconds of the reported RA for archived MPC1992 data records.
precDec	RaDecPrecType	Precision in arcseconds of the reported DEC for archived MPC1992 data records.
uncTime	PosDecimalType	Estimated time uncertainty in seconds. Unlike the preceding RMS fields, which indicate random errors, this field indicates a presumed level of systematic clock error. NB: This field is generally only to be used to communicate exceptions and problems with clock calibration and is not intended to be used in routine submissions where clock errors are not a significant source of astrometric error.

to be cont'd on next page

(continued)

notes	NotesType	A set of one-character note flags to communicate observing circumstances.
remarks	RemarkType	Comment field provided by the observer. This field can be used to report additional information that is not reportable in the notes field, but that may be of relevance for interpretation of the observations.
deprecated	DeprecatedType	Marks deprecated observation.
localUse	LocalUseType	For user-defined fields in observations

observations residual sub-elements		
Name	Type	Description
orbProd	StringType	Orbit producer. Can be institution, individual, or even email address, e.g. ‘MPC’
orbID	StringType	Local reference for orbit, e.g., ‘JPL 7’ or ‘MPO 12345’.
resRA	xsd:decimal	Residuals in RA cos DEC in arcseconds
resDec	xsd:decimal	Residuals in DEC in arcseconds
selAst	SelResType	Inclusion/rejection flag for astrometry
sigRA	PosDecimalType	Adopted RA cos DEC 1σ uncertainty in arcseconds.
sigDec	PosDecimalType	Adopted DEC 1σ uncertainty in arcseconds.
sigCorr	CorrDecimalType	Adopted correlation between RA cos DEC and DEC.
sigTime	PosDecimalType	Adopted 1σ time uncertainty in seconds.
biasRA	xsd:decimal	Adopted RA cos DEC bias in arcseconds.

to be cont’d on next page

(continued)

biasDec	xsd:decimal	Adopted DEC bias in arcseconds.
biasTime	xsd:decimal	Adopted time bias in s.
photProd	StringType	Producer of photometric residuals. Can be institution, individual, or even email address, e.g. 'MPC'
resMag	xsd:decimal	Photometric residual in magnitudes
selPhot	SelResType	Inclusion/rejection flag for photometry
sigMag	PosDecimalType	Adopted 1σ magnitude uncertainty in magnitudes.
biasMag	xsd:decimal	Adopted photometric bias in magnitudes
photMod	PhotModType	Description of the photometric model.
resDelay	xsd:decimal	Residual of the radar measurement in μ s for delay
selDelay	SelResType	Inclusion/rejection flag for radar astrometry
sigDelay	PosDecimalType	Adopted uncertainty for the radar measurement in μ s for delay
resDoppler	xsd:decimal	Residual of the radar measurement in Hz for Doppler
selDoppler	SelResType	Inclusion/rejection flag for radar astrometry
sigDoppler	PosDecimalType	Adopted uncertainty for the radar measurement in Hz for Doppler
observation-context sub-elements		
Name	Type	Description
observatory	ObservatoryType	observatory information block
submitter	SubmitterType	Contact information block

to be cont'd on next page

(continued)

observers	NamesType	list of observer names (initials then surname)
measurers	NamesType	list of measurer names (initials then surnames)
telescope	TelescopeType	Description of telescope
software	SoftwareType	Description of software
coinvestigators	NamesType	list of coinvestigator names (initials then surname)
collaborators	NamesType	list of collaborator names (initials then surname)
fundingSource	StringType	funding source
comment	CommentType	comment for observation context
observation types		
Name	Type	Description
optical	OpticalType	optical observation
offset	OffsetType	optical offset
occultation	OccultationType	optical occultation
radar	RadarType	delay or doppler radar
observation-context, obsBlock		
Name	Type	Description
obsContext	ObsContextType	observation context information
obsData	ObsDataType	list of optical or radar observations
obsBlock	ObsBlockType	obsBlock contains an obsContext and obsData
Free-Standing Residuals		
Name	Type	Description
opticalResidual	OpticalResType	optical residual
radarResidual	RadarResType	radar residual
ADES root		
Name	Type	Description
ades	ADESType	document root

2 Table of Restricted Simple Types

Restricted simple types are a single XML value with some additional restrictions, such as requiring an decimal value to be in some range (such as 0.0 to 90.0) or requiring a string to be from an enumerated list. Some of these restrictions, such as the possible station string values, will eventually be pulled out of MPC-provided files and referenced over the web.

Simple Types with their Restrictions

Type	Description
AlphaNumericType base is StringType -pattern: [A-Za-z0-9_]*	AlphaNumericType restricts the field to only the ASCII upper- and lower-case letters, ASCII numbers and underscores
BandType base is AlphaNumericType -maxLength: 3	MPC maintains a list of bands for magnitude observations
CatType base is AlphaNumericType -maxLength: 8	MPC maintains a list of current astrometry and photometry catalogs
CorrDecimalType base is xsd:decimal -minInclusive: -1.0 -maxInclusive: 1.0	CorrDecimal in range [-1.0, 1.0]
DeclinationType base is xsd:decimal -minInclusive: -90.0 -maxInclusive: 90.0	DEC in degrees in range [-90.0, 90.0]
DeprecatedType base is xsd:string -enumeration: x	X marks the use of deprecated data
DiscType base is xsd:string -enumeration: * -enumeration: +	Used to mark the discovery record – must be ‘*’ or ‘+’ if present
SubFrmType base is StringType -pattern: ([BJ]\d{4}.0) APP\.	The submission frame, usually B1950.0 or earlier. If this field is not present, the submission frame was J2000.0

to be cont’d on next page

(continued)

Type	Description
LeapSecondsHelp base is xsd:string -pattern: 19(72 81 82 83 85 92 93 94 97)-06-30T23:59:60(\.\d+)?Z -pattern: 19(72 73 74 75 76 77 78 79 87 89 90 95 98)-12-31T23:59:60(\.\d+)?Z -pattern: 20(12 15)-06-30T23:59:60(\.\d+)?Z -pattern: 20(05 08 16)-12-31T23:59:60(\.\d+)?Z -pattern: (2[1-9]\d{2} 20[2-9]\d 201[7-9])-12-31T23:59:60(\.\d+)?Z -pattern: (2[1-9]\d{2} 20[2-9]\d 201[7-9])-06-30T23:59:60(\.\d+)?Z -pattern: [3-9]\d{3}-06-30T23:59:60(\.\d+)?Z -pattern: [3-9]\d{3}-12-31T23:59:60(\.\d+)?Z	Allowed leap seconds before 2017 are valid leap-seconds; for 2017 and later are all allowed June and December leap-second opportunities.
LogicalType base is xsd:integer -enumeration: 0 -enumeration: 1	0 for false, 1 for true to match C and FORTRAN
ModeType base is AlphaNumericType -maxLength: 3	The MPC maintains a list of mode values
ObsCenterType union of PermIDType ProvIDType PlanetNameType	May be PlanetNameType, PermIDType or ProvIDType
NotesType base is AlphaNumericType -maxLength: 6	up to six single-character notes from MPC table
ObsIDType base is AlphaNumericType -maxLength: 19	An obsID is up to nineteen alphanumeric characters

to be cont'd on next page

(continued)

Type	Description
PermIDType base is xsd:string -pattern: <code>\d+([PD]([A-Z]{1,2})?)? ((Mars Jupiter Saturn Uranus Neptune)\d{1,3} (\d+)\d{1,3})</code>	A permID (permanent ID) string may be a positive integer, a positive integer followed by P or D, a planet name followed by a positive integer, or a positive integer in parentheses followed by a positive integer. These indicate a minor planet, a comet, a natural satellite of a planet, and a natural satellite of a minor planet respectively.
PhotModType base is AlphaNumericType -maxLength: 8	Photometric model is up to eight alphanumeric characters
PlanetNameType base is xsd:string -enumeration: Mercury -enumeration: Venus -enumeration: Earth -enumeration: Moon -enumeration: Mars -enumeration: Jupiter -enumeration: Saturn -enumeration: Uranus -enumeration: Neptune	List of planet names, including Earth's Moon
PosDecimalType base is xsd:decimal -minExclusive: 0.0	PositiveDecimal in range (0.0, +inf)
ProgType base is AlphaNumericType -maxLength: 2	MPC maintains a list of 1 and 2 character program codes

to be cont'd on next page

(continued)

Type	Description
ProvIDType base is xsd:string -pattern: \{4\} [A-HJ-Y] [A-HJ-Z] \d* \{4\}	A provID (provisional ID) is may be a minor planet provid, which is a 4-digit year followed by a space followed by two letters followed optionally by digits; or a comet it, which is C/ or P/ or D/ or X/ or A/ (for asteroids with comet numbers, which may not have fragments) followed by a 4-digit year follwed by a space followed by one or two digits optionally followed by one or two digits optionally followed by "-[A-Z]" (for a comet fragment); or a satellite, which is S/ followed by a 4-digit year followed a space followed either (by a minor planet PermID in parentheses or the bare letter M, J, S, N, U) followed by a space followed by digits.
RaDecPrecType base is xsd:decimal -enumeration: 0.1 -enumeration: 0.6 -enumeration: 0.01 -enumeration: 0.001 -enumeration: 60 -enumeration: 6 -enumeration: 1 -enumeration: 60.0 -enumeration: 6.0 -enumeration: 1.0	RaDecPrecType is used to describe the precision of a decimal value when the orignal measurement was made in sexagesimal. The allowed values are applied to the last sexagesimal element, which may be seconds or arcseconds, and mean (for time) the value is accurate to an hour, 10 minutes, 1 minute, 6 seconds, 1 second, .1 second and so forth.
RAType base is xsd:decimal -minInclusive: 0.0 -maxExclusive: 360.0	RA in degrees limited to [0.0, 360.0)
RefType base is StringType -maxLength: 16	MPC-assigned reference, up to sixteen characters
RemarkType base is StringType -maxLength: 200	A remark is a String limited to 200 characters

to be cont'd on next page

(continued)

Type	Description
SelResType base is xsd:string -enumeration: A -enumeration: a -enumeration: D -enumeration: d	SelRes must be “A,” (automatic accept) “a,” (manual accept) “D,” (automatic delete) or “d” (manual delete)
StationType base is AlphaNumericType -minLength: 3 -maxLength: 4	A stn, rov, trx or tcv station. Values vary and are checked by MPC
StringType base is xsd:string -pattern: [^]*[^\s][^]*	String follows the ADES specification in that the pipe character is disallowed in PSV. To allow data conversion from XML, it must disallow in XML as well. Also disallow blank elements. Therefore, all elements must match this pattern
SubFmtType base is AlphaNumericType -maxLength: 4	MPC maintains a list of allowed submission formats with no extra fields, up to four alphanumeric characters
SysType base is xsd:string -enumeration: WGS84 -enumeration: ITRF -enumeration: IAU -enumeration: ICRF_AU -enumeration: ICRF_KM	Coordinate system for station coordinates. This is used by the pos[123] and poscov[123][123] elements to determine the meaning of coordinates. WGS84, ITRF and IAU are for ground-based stations, ICRF_AU and ICRF_KM are for space-based stations.
TimeHelp base is xsd:dateTime -pattern: \d{4}-\d{2}-\d{2}T\d{2}:\d{2}:\d{2}(\.\d+)?Z	Restrict dateTime to 4-digit positive years and Z for UTC
TimePrecType base is xsd:decimal -enumeration: 100000 -enumeration: 10000 -enumeration: 1000 -enumeration: 100 -enumeration: 10 -enumeration: 1	TimePrecType is used to describe the precision of a Time value when the original measurement was made in fractional days. The accuracy is in millionths of decimal day, so 10 means 1/100,000 of a day, a little better than a second. The large values are only for historic data on comets.

to be cont'd on next page

(continued)

Type	Description
TimeType union of TimeHelp LeapSecondsHelp	TimeType is an ISO8601 UTC time in the format yyyy-mm-ddThh:mm:ss(.s+)Z. The trailing Z means it is interpreted as UTC. It is not a restriction of xsd:dateTime because that does not properly validate leapseconds. It allows positive 4-digit years and validates the Gregorian calendar for all dates. Note this works because xsd or's all the restrictions and accepts any match. LeapSecondsHelp matches any leapsecond before 2017 and any potential new leapseconds from 2017.
TrkIDType base is AlphaNumericType -maxLength: 12	A trkID is up to twelve alphanumeric characters
TrkSubType base is AlphaNumericType -maxLength: 8	A trkSub is up to eight alphanumeric characters
VersionType base is xsd:string -enumeration: 2017	Version attribute for the current ADES schema must be "2017"

3 Groups

This is the documentation for the groups. Groups are a convenient way of organizing rules in complicated structures, used as components of other groups or of complex types. Unlike complex types, groups may appear inside other complex types or groups with no tag. Because groups act a bit like types, their names are all CamelCase with the first letter capitalized.

grouptype: MPCID

MPCID	permID or provID or both in that order, or artSat		
choice	sequence		
	element	permID	
	element	provID	(Optional)
	sequence		
	element	provID	
	sequence		
	element	artSat	

grouptype: OpticalID

OpticalID	An MPCID group or trkSub or both in that order. Of permID, provID, artSat or trkSub at least one must be present in an optical observation but all three might be present. Also, MPC will assign unique obsID and trkID fields for distribution		
sequence	choice		
	sequence		
	group	MPCID	
	element	trkSub	(Optional)
	sequence		
	element	trkSub	
	element	obsID	(NoSubmit)
	element	trkID	(NoSubmit)

grouptype: RadarID

RadarID	An MPCID group only; radar has no equivalent of the optical “trkSub” field. MPC will add a unique obsID field for distribution		
sequence			
	group	MPCID	
	element	trkSub	(Optional)
	element	obsID	(NoSubmit)

grouptype: RadarValue

RadarValue	A RadarValue is used for doppler or delay values and errors in a radar observation.	
choice		
sequence		
element	doppler	
element	rmsDoppler	
sequence		
element	delay	
element	rmsDelay	

groupstype: Precision

Precision	Precision is primarily for M92 and M47 formats. However, it may be used generally to describe data originally obtained with a certain sexagesimal precision instead of a decimal precision	
sequence	element	precTime
	element	precRA
	element	precDec

groupstype: Location

Location	location data for a rover station.	
sequence	element	sys
	element	ctr
	element	pos1
	element	pos2
	element	pos3
	element	posCov11 (Optional)
	element	posCov12 (Optional)
	element	posCov13 (Optional)
	element	posCov22 (Optional)
	element	posCov23 (Optional)
	element	posCov33 (Optional)

grouptype: Photometry

Photometry	The Photometry group is optional in all optical observation types (optical, offset, and occultation). The "mag" and "band" fields must be present; the rest are optional but can only occur if "mag" and "band" are present to define this as a Photometry group	
sequence	element	mag
	element	rmsMag (Optional)
	element	band
	element	photCat (Optional)
	element	photAp (Optional)
	element	nucMag (NoSubmit)

grouptype: OffsetVal

OffsetVal	OffsetVal allows either rectangular or polar coordinates for the offset measurement. The rectangular coordinates are deltaRA and deltaDec; the polar coordinates are dist and polar angle.		
<hr/>			
choice			
<hr/>			
sequence			
<hr/>			
element		deltaRA	
element		deltaDec	
element		rmsRA	(Optional)
element		rmsDec	(Optional)
element		rmsCorr	(Optional)
<hr/>			
sequence			
<hr/>			
element		dist	
element		pa	
element		rmsDist	(Optional)
element		rmsPA	(Optional)
element		rmsCorr	(Optional)
<hr/>			

grouptype: OpticalRes

OpticalRes	OpticalRes is optional for the OpticalResiduals group	
sequence		
element	resRA	
element	resDec	
element	selAst	
element	sigRA	
element	sigDec	
element	sigCorr	(Optional)
element	sigTime	(Optional)
element	biasRA	(Optional)
element	biasDec	(Optional)
element	biasTime	(Optional)

grouptype: OpticalResMag

OpticalResMag	OpticalRes is optional for the OpticalResiduals group	
sequence		
element	photProd	(Optional)
element	resMag	
element	selPhot	
element	sigMag	
element	biasMag	(Optional)
element	photMod	(Optional)

grouptype: OpticalResiduals

OpticalResiduals	The OpticalResiduals group is optional for adding residuals to optical observations, or as a separate obsResidual element tagged by obsID		
sequence			
element	orbProd		
element	orbID		
group	OpticalRes	(Optional)	
group	OpticalResMag	(Optional)	

grouptype: RadarResiduals

RadarResiduals		The RadarResiduals group is optional for adding residuals to optical observations, or as a separate obsResidual element tagged by obsID	
sequence			
element	orbProd		
element	orbID		
choice	sequence		
	element	resDelay	
	element	selDelay	
	element	sigDelay	
	sequence		
	element	resDoppler	
	element	selDoppler	
	element	sigDoppler	

4 Complex Types

This is the documentation for the complex types, which may be used directly as similarly-named elements or as components of other complex types and groups. Unlike a group, a complex type is always the only thing inside a tag. The names of complex types, like groups and simple types, are all CamelCase with the first letter capitalized.

complextype: NameType

NameType	List of one or more names of type String
sequence	
	type StringType name (Unbounded)

complextype: ObservatoryType

ObservatoryType	Observatory Identification
all	
	type StationType mpcCode
	type StringType name (Optional)

complextype: SubmitterType

SubmitterType	Submitter information. A name field (initials plus surname), an institution string
all	
	type StringType name
	type StringType institution (Optional)

complexttype: TelescopeType

TelescopeType	telescope information		
all			
type StringType	name	(Optional)	
type StringType	design		
type PosDecimalType	aperture		
type StringType	detector		
type PosDecimalType	fRatio	(Optional)	
type StringType	filter	(Optional)	
type StringType	arraySize	(Optional)	
type PosDecimalType	pixelScale	(Optional)	

complexttype: SoftwareType

SoftwareType	information about software used in processing		
all			
type StringType	astrometry	(Optional)	
type StringType	fitOrder	(Optional)	
type StringType	photometry	(Optional)	
type StringType	objectDetection	(Optional)	

complexttype: CommentType

CommentType	List of one or more lines of type String		
sequence			
type StringType	line	(Unbounded)	

complexttype: LocalUseType

LocalUseType	This element is to allow arbitrary fields for private data interchange
sequence	
any	

complextype: OpticalType

OpticalType	Optical Observation with RA and Dec		
sequence			
group	OpticalID		
element	mode		
element	stn		
group	Location	(Optional)	
element	prog	(NoSubmit)	
element	obsTime		
element	rmsTime	(Optional)	
element	ra		
element	dec		
element	rmsRA	(Optional)	
element	rmsDec	(Optional)	
element	rmsCorr	(Optional)	
element	astCat		
group	Photometry	(Optional)	
element	logSNR	(Optional)	
element	seeing	(Optional)	
element	exp	(Optional)	
element	rmsFit	(Optional)	
element	nStars	(Optional)	
element	ref	(NoSubmit)	
element	disc	(Optional)	
element	subFrm	(NoSubmit)	
element	subFmt	(NoSubmit)	
group	Precision	(NoSubmit)	
element	uncTime	(Optional)	
element	notes	(Optional)	
element	remarks	(Optional)	
group	OpticalResiduals	(NoSubmit)	
element	deprecated	(NoSubmit)	
element	localUse	(NoSubmit)	

complextype: OffsetType

OffsetType	Optical Offset Observation with RA and Dec		
sequence			
group	OpticalID		
element	mode		
element	stn		
group	Location	(Optional)	
element	prog	(NoSubmit)	
element	obsTime		
element	rmsTime	(Optional)	
element	obsCenter		
group	OffsetVal		
group	Photometry	(Optional)	
element	logSNR	(Optional)	
element	seeing	(Optional)	
element	exp	(Optional)	
element	rmsFit	(Optional)	
element	nStars	(Optional)	
element	ref	(NoSubmit)	
element	disc	(Optional)	
element	subFrm	(NoSubmit)	
element	subFmt	(NoSubmit)	
group	Precision	(NoSubmit)	
element	uncTime	(Optional)	
element	notes	(Optional)	
element	remarks	(Optional)	
group	OpticalResiduals	(NoSubmit)	
element	deprecated	(NoSubmit)	
element	localUse	(NoSubmit)	

complexttype: OccultationType

OccultationType		Optical Occultation Observation with deltaRA, deltaDec, raStar and decStar	
sequence	group	OpticalID	
	element	stn	
	group	Location	(Optional)
	element	prog	(NoSubmit)
	element	obsTime	
	element	rmsTime	(Optional)
	element	raStar	
	element	decStar	
	group	OffsetVal	
	element	astCat	
	group	Photometry	(Optional)
	element	logSNR	(Optional)
	element	seeing	(Optional)
	element	ref	(NoSubmit)
	element	disc	(Optional)
	element	subFrm	(NoSubmit)
	element	subFmt	(NoSubmit)
	group	Precision	(NoSubmit)
	element	uncTime	(Optional)
	element	notes	(Optional)
	element	remarks	(Optional)
	group	OpticalResiduals	(NoSubmit)
	element	deprecated	(NoSubmit)
	element	localUse	(NoSubmit)

complexttype: RadarType

RadarType	Radar Observation using either doppler or delay values from RadarValue	
sequence		
group	RadarID	
element	trx	
element	rcv	
element	prog	(NoSubmit)
element	obsTime	
group	RadarValue	
element	logSNR	(Optional)
element	com	(Optional)
element	frq	
element	ref	(NoSubmit)
element	remarks	(Optional)
group	RadarResiduals	(NoSubmit)
element	localUse	(NoSubmit)

complexttype: ObsContextType

ObsContextType	observation context header type	
all		
element	observatory	
element	submitter	
element	observers	
element	measurers	
element	telescope	
element	software	(Optional)
element	coinvestigators	(Optional)
element	collaborators	(Optional)
element	fundingSource	(Optional)
element	comment	(Optional)

complexttype: ObsDataType

ObsDataType	A list of all optical or all radar observations		
choice			
	element	optical	(Unbounded)
	element	offset	(Unbounded)
	element	occultation	(Unbounded)
	element	radar	(Unbounded)

complexttype: ObsBlockType

ObsBlockType	A list of all optical or all radar observations, with context		
sequence			
	element	obsContext	
	element	obsData	

complexttype: OpticalResType

OpticalResType	Optical Residual outside of the optical/occultation/offset structure		
sequence			
	group	OpticalID	
	element	obsTime	
	group	OpticalResiduals	

complexttype: RadarResType

RadarResType	Radar Residual outside of the radar structure	
sequence		
	group	RadarID
	element	obsTime
	group	RadarResiduals

complexttype: ADESType

ADESType	This is what is allowed in ades documents – any of these in any order		
attribute	version	VersionType	(requiredAttribute)
choice	(Unbounded)		
	element	optical	(NoSubmit)
	element	offset	(NoSubmit)
	element	occultation	(NoSubmit)
	element	radar	(NoSubmit)
	element	opticalResidual	(NoSubmit)
	element	radarResidual	(NoSubmit)
	element	obsBlock	