arXiv:2305.18290v3 [cs.LG] 29 Jul 2024

Direct Preference Optimization: Your Language Model is Secretly a Reward Model

Rafael Rafailov[*†] **Archit Sharma**[*†] **Eric Mitchell**[*†]

Stefano Ermon[†‡] **Christopher D. Manning**[†] **Chelsea Finn**[†]

[†]Stanford University [‡]CZ Biohub
{rafailov,architsh,eric.mitchell}@cs.stanford.edu

Abstract

While large-scale unsupervised language models (LMs) learn broad world knowledge and some reasoning skills, achieving precise control of their behavior is difficult due to the completely unsupervised nature of their training. Existing methods for gaining such steerability collect human labels of the relative quality of model generations and fine-tune the unsupervised LM to align with these preferences, often with reinforcement learning from human feedback (RLHF). However, RLHF is a complex and often unstable procedure, first fitting a reward model that reflects the human preferences, and then fine-tuning the large unsupervised LM using reinforcement learning to maximize this estimated reward without drifting too far from the original model. In this paper we introduce a new parameterization of the reward model in RLHF that enables extraction of the corresponding optimal policy in closed form, allowing us to solve the standard RLHF problem with only a simple classification loss. The resulting algorithm, which we call *Direct Preference Optimization* (DPO), is stable, performant, and computationally lightweight, eliminating the need for sampling from the LM during fine-tuning or performing significant hyperparameter tuning. Our experiments show that DPO can fine-tune LMs to align with human preferences as well as or better than existing methods. Notably, fine-tuning with DPO exceeds PPO-based RLHF in ability to control sentiment of generations, and matches or improves response quality in summarization and single-turn dialogue while being substantially simpler to implement and train.

1 Introduction

Large unsupervised language models (LMs) trained on very large datasets acquire surprising capabilities [11, 7, 42, 8]. However, these models are trained on data generated by humans with a wide variety of goals, priorities, and skillsets. Some of these goals and skillsets may not be desirable to imitate; for example, while we may want our AI coding assistant to *understand* common programming mistakes in order to correct them, nevertheless, when generating code, we would like to bias our model toward the (potentially rare) high-quality coding ability present in its training data. Similarly, we might want our language model to be *aware* of a common misconception believed by 50% of people, but we certainly do not want the model to claim this misconception to be true in 50% of queries about it! In other words, selecting the model's *desired responses and behavior* from its very wide *knowledge and abilities* is crucial to building AI systems that are safe, performant, and controllable [28]. While existing methods typically steer LMs to match human preferences using reinforcement learning (RL),

[*]Equal contribution; more junior authors listed earlier.

37th Conference on Neural Information Processing Systems (NeurIPS 2023).

where β is a parameter controlling the deviation from the base reference policy π_{ref}, namely the initial SFT model π^{SFT}. In practice, the language model policy π_θ is also initialized to π^{SFT}. The added constraint is important, as it prevents the model from deviating too far from the distribution on which the reward model is accurate, as well as maintaining the generation diversity and preventing mode-collapse to single high-reward answers. Due to the discrete nature of language generation, this objective is not differentiable and is typically optimized with reinforcement learning. The standard approach [51, 40, 1, 28] has been to construct the reward function $r(x, y) = r_\phi(x, y) - \beta(\log \pi_\theta(y \mid x) - \log \pi_{\text{ref}}(y \mid x))$, and maximize using PPO [39].

4 Direct Preference Optimization

Motivated by the challenges of applying reinforcement learning algorithms on large-scale problems such as fine-tuning language models, our goal is to derive a simple approach for policy optimization using preferences directly. Unlike prior RLHF methods, which learn a reward and then optimize it via RL, our approach leverages a particular choice of reward model parameterization that enables extraction of its optimal policy in closed form, without an RL training loop. As we will describe next in detail, our key insight is to leverage an analytical mapping from reward functions to optimal policies, which enables us to transform a loss function over reward functions into a loss function over policies. This change-of-variables approach avoids fitting an explicit, standalone reward model, while still optimizing under existing models of human preferences, such as the Bradley-Terry model. In essence, the policy network represents both the language model and the (implicit) reward.

Deriving the DPO objective. We start with the same RL objective as prior work, Eq. 3, under a general reward function r. Following prior work [31, 30, 19, 15], it is straightforward to show that the optimal solution to the KL-constrained reward maximization objective in Eq. 3 takes the form:

$$\pi_r(y \mid x) = \frac{1}{Z(x)} \pi_{\text{ref}}(y \mid x) \exp\left(\frac{1}{\beta} r(x, y)\right), \tag{4}$$

where $Z(x) = \sum_y \pi_{\text{ref}}(y \mid x) \exp\left(\frac{1}{\beta} r(x, y)\right)$ is the partition function. See Appendix A.1 for a complete derivation. Even if we use the MLE estimate r_ϕ of the ground-truth reward function r^*, it is still expensive to estimate the partition function $Z(x)$ [19, 15], which makes this representation hard to utilize in practice. However, we can rearrange Eq. 4 to express the reward function in terms of its corresponding optimal policy π_r, the reference policy π_{ref}, and the unknown partition function $Z(\cdot)$. Specifically, we first take the logarithm of both sides of Eq. 4 and then with some algebra we obtain:

$$r(x, y) = \beta \log \frac{\pi_r(y \mid x)}{\pi_{\text{ref}}(y \mid x)} + \beta \log Z(x). \tag{5}$$

We can apply this reparameterization to the ground-truth reward r^* and corresponding optimal model π^*. Fortunately, the Bradley-Terry model depends only on the difference of rewards between two completions, i.e., $p^*(y_1 \succ y_2 \mid x) = \sigma(r^*(x, y_1) - r^*(x, y_2))$. Substituting the reparameterization in Eq. 5 for $r^*(x, y)$ into the preference model Eq. 1, the partition function cancels, and we can express the human preference probability in terms of only the optimal policy π^* and reference policy π_{ref}. Thus, the optimal RLHF policy π^* under the Bradley-Terry model satisfies the preference model:

$$p^*(y_1 \succ y_2 \mid x) = \frac{1}{1 + \exp\left(\beta \log \frac{\pi^*(y_2|x)}{\pi_{\text{ref}}(y_2|x)} - \beta \log \frac{\pi^*(y_1|x)}{\pi_{\text{ref}}(y_1|x)}\right)} \tag{6}$$

The derivation is in Appendix A.2. While Eq. 6 uses the Bradley-Terry model, we can similarly derive expressions under the more general Plackett-Luce models [32, 23], shown in Appendix A.3.

Now that we have the probability of human preference data in terms of the optimal policy rather than the reward model, we can formulate a maximum likelihood objective for a parametrized policy π_θ. Analogous to the reward modeling approach (i.e. Eq. 2), our policy objective becomes:

$$\mathcal{L}_{\text{DPO}}(\pi_\theta; \pi_{\text{ref}}) = -\mathbb{E}_{(x, y_w, y_l) \sim \mathcal{D}} \left[\log \sigma \left(\beta \log \frac{\pi_\theta(y_w \mid x)}{\pi_{\text{ref}}(y_w \mid x)} - \beta \log \frac{\pi_\theta(y_l \mid x)}{\pi_{\text{ref}}(y_l \mid x)}\right)\right]. \tag{7}$$

This way, we fit an implicit reward using an alternative parameterization, whose optimal policy is simply π_θ. Moreover, since our procedure is equivalent to fitting a reparametrized Bradley-Terry

model, it enjoys certain theoretical properties, such as consistencies under suitable assumption of the preference data distribution [4]. In Section 5, we further discuss theoretical properties of DPO in relation to other works.

What does the DPO update do? For a mechanistic understanding of DPO, it is useful to analyze the gradient of the loss function $\mathcal{L}_{\text{DPO}}$. The gradient with respect to the parameters θ can be written as:

$$\nabla_\theta \mathcal{L}_{\text{DPO}}(\pi_\theta; \pi_{\text{ref}}) =$$
$$-\beta \mathbb{E}_{(x,y_w,y_l)\sim\mathcal{D}}\Bigg[\underbrace{\sigma(\hat{r}_\theta(x, y_l) - \hat{r}_\theta(x, y_w))}_{\text{higher weight when reward estimate is wrong}}\Bigg[\underbrace{\nabla_\theta \log \pi(y_w \mid x)}_{\text{increase likelihood of } y_w} - \underbrace{\nabla_\theta \log \pi(y_l \mid x)}_{\text{decrease likelihood of } y_l}\Bigg]\Bigg],$$

where $\hat{r}_\theta(x, y) = \beta \log \frac{\pi_\theta(y|x)}{\pi_{\text{ref}}(y|x)}$ is the reward implicitly defined by the language model π_θ and reference model π_{ref} (more in Section 5). Intuitively, the gradient of the loss function $\mathcal{L}_{\text{DPO}}$ increases the likelihood of the preferred completions y_w and decreases the likelihood of dispreferred completions y_l. Importantly, the examples are weighed by how much higher the implicit reward model $\hat{r}_\theta$ rates the dispreferred completions, scaled by β, i.e, how incorrectly the implicit reward model orders the completions, accounting for the strength of the KL constraint. Our experiments suggest the importance of this weighting, as a naïve version of this method without the weighting coefficient can cause the language model to degenerate (Appendix Table 3).

DPO outline. The general DPO pipeline is as follows: 1) Sample completions $y_1, y_2 \sim \pi_{\text{ref}}(\cdot \mid x)$ for every prompt x, label with human preferences to construct the offline dataset of preferences $\mathcal{D} = \{x^{(i)}, y_w^{(i)}, y_l)^{(i)}\}_{i=1}^N$ and 2) optimize the language model π_θ to minimize $\mathcal{L}_{\text{DPO}}$ for the given π_{ref} and $\mathcal{D}$ and desired β. In practice, one would like to reuse preference datasets publicly available, rather than generating samples and gathering human preferences. Since the preference datasets are sampled using π^{SFT}, we initialize $\pi_{\text{ref}} = \pi^{\text{SFT}}$ whenever available. However, when π^{SFT} is not available, we initialize π_{ref} by maximizing likelihood of preferred completions (x, y_w), that is, $\pi_{\text{ref}} = \arg\max_\pi \mathbb{E}_{x,y_w\sim\mathcal{D}}[\log \pi(y_w \mid x)]$. This procedure helps mitigate the distribution shift between the true reference distribution which is unavailable, and π_{ref} used by DPO. Further details related to the implementation and hyperparameters can be found in Appendix B.

5 Theoretical Analysis of DPO

In this section, we give further interpretation of the DPO method, provide theoretical backing, and relate advantages of DPO to issues with actor critic algorithms used for RLHF (such as PPO [39]).

5.1 Your Language Model Is Secretly a Reward Model

DPO is able to bypass both fitting an explicit reward and performing RL to learn the policy using a single maximum likelihood objective. Note the optimization objective Eq. 5 is equivalent to a Bradley-Terry model with a reward parameterization $r^*(x, y) = \beta \log \frac{\pi^*_\theta(y|x)}{\pi_{\text{ref}}(y|x)}$ and we optimize our parametric model π_θ, equivalently to the reward model optimization in Eq. 2 under the change of variables. In this section we will build the theory behind this reparameterization, show that it does not constrain the class of learned reward models, and allows for the exact recovery of the optimal policy. We begin with by defining an equivalence relation between reward functions.

Definition 1. *We say that two reward functions $r(x, y)$ and $r'(x, y)$ are equivalent iff $r(x, y) - r'(x, y) = f(x)$ for some function f.*

It is easy to see that this is indeed an equivalence relation, which partitions the set of reward functions into classes. We can state the following two lemmas:

Lemma 1. *Under the Plackett-Luce, and in particular the Bradley-Terry, preference framework, two reward functions from the same class induce the same preference distribution.*

Lemma 2. *Two reward functions from the same equivalence class induce the same optimal policy under the constrained RL problem.*

The proofs are straightforward and we defer them to Appendix A.5. The first lemma is a well-known under-specification issue with the Plackett-Luce family of models [32]. Due to this under-specification,

DPO's reward/KL tradeoff strictly dominates PPO. Second, DPO achieves a better frontier than PPO, *even when PPO can access ground truth rewards* (PPO-GT).

6.2 Can DPO scale to real preference datasets?

Next, we evaluate fine-tuning performance of DPO on summarization and single-turn dialogue. For summarization, automatic evaluation metrics such as ROUGE can be poorly correlated with human preferences [40], and prior work has found that fine-tuning LMs using PPO on human preferences to provide more effective summaries. We evaluate different methods by sampling completions on the test split of TL;DR summarization dataset, and computing the average win rate against reference completions in the test set. The completions for all methods are sampled at temperatures varying from 0.0 to 1.0, and the win rates are shown in Figure 2 (right). DPO, PPO and Preferred-FT all fine-tune the same GPT-J SFT model[4]. We find that DPO has a win rate of approximately 61% at a temperature of 0.0, exceeding the performance of PPO at 57% at its optimal sampling temperature of 0.0. DPO also achieves a higher maximum win rate compared to the best of N baseline. We note that we did not meaningfully tune DPO's β hyperparameter, so these results may underestimate DPO's potential. Moreover, we find DPO to be much more robust to the sampling temperature than PPO, the performance of which can degrade to that of the base GPT-J model at high temperatures. Preferred-FT does not improve significantly over the SFT model. We also compare DPO and PPO head-to-head in human evaluations in Section 6.4, where DPO samples at temperature 0.25 were preferred 58% times over PPO samples at temperature 0.

On single-turn dialogue, we evaluate the different methods on the subset of the test split of the Anthropic HH dataset [1] with one step of human-assistant interaction. GPT-4 evaluations use the preferred completions on the test as the reference to compute the win rate for different methods. As there is no standard SFT model for this task, we start with a pre-trained Pythia-2.8B, use Preferred-FT to train a reference model on the chosen completions such that completions are within distribution of the model, and then train using DPO. We also compare against the best of 128 Preferred-FT completions (we found the Best of N baseline plateaus at 128 completions for this task; see Appendix Figure 4) and a 2-shot prompted version of the Pythia-2.8B base model, finding DPO performs as well or better for the best-performing temperatures for each method. We also evaluate an RLHF model trained with PPO on the Anthropic HH dataset [5] from a well-known source [6], but are unable to find a prompt or sampling temperature that gives performance better than the base Pythia-2.8B model. Based on our results from TL;DR and the fact that both methods optimize the same reward function, we consider Best of 128 a rough proxy for PPO-level performance. Overall, DPO is the only computationally efficient method that improves over the preferred completions in the Anthropic HH dataset, and provides similar or better performance to the computationally demanding Best of 128 baseline. Finally, Figure 3 shows that DPO converges to its best performance relatively quickly.

6.3 Generalization to a new input distribution

To further compare the performance of PPO and DPO under distribution shifts, we evaluate the PPO and DPO policies from our Reddit TL;DR summarization experiment on a different distribution, news articles in the test split of the CNN/DailyMail dataset [26], using the best sampling temperatures from TL;DR (0 and 0.25). The results are presented in Table 1. We computed the GPT-4 win rate against the ground-truth summaries in the datasets, using the same GPT-4 (C) prompt we used for Reddit TL;DR, but replacing the words "forum post" with "news article". For this new distribution, DPO continues to outperform the PPO policy by a significant margin. This experiment provides initial evidence that DPO policies can generalize similarly well to PPO policies, even though DPO does not use the additional unlabeled Reddit TL;DR prompts that PPO uses.

	Win rate vs. ground truth	
Alg.	Temp 0	Temp 0.25
DPO	0.36	0.31
PPO	0.26	0.23

Table 1: GPT-4 win rates vs. ground truth summaries for out-of-distribution CNN/DailyMail input articles.

[4] `https://huggingface.co/CarperAI/openai_summarize_tldr_sft`

[5] `https://huggingface.co/reciprocate/ppo_hh_pythia-6B`

[6] `https://github.com/CarperAI/trlx/tree/main/examples/hh`