

- TransferBroker
- get_events_to_wait
- get_link_dst_state
- get_link_src_state
- get_list_dst_endpoints
- get_list_dst_rcsites
- get_list_src_endpoints
- get_list_src_rcsites
- get_max_throughput
- get_min_throughput
- get_num_circuits
- get_sense_uuid
- get_sense_uuid_2
- get_sense_vlan
- get_sense_vlan_2
- get_unidirectional
- set_events_to_wait
- set_link_dst_state
- set_link_src_state
- set_list_dst_endpoints
- set_list_dst_rcsites
- set_list_src_endpoints

▶ EXPAND SOURCE CODE

Classes

class TransferBroker
Class for transfer broker attributes.
Function to initialize the attributes.
▶ EXPAND SOURCE CODE
Methods
def get_events_to_wait(self)
Function to get events_to_wait attribute.
▶ EXPAND SOURCE CODE
def get_link_dst_state(self)
Function to get link_dst_state attribute.
▶ EXPAND SOURCE CODE
def get_link_src_state(self)
Function to get link_src_state attribute.
▶ EXPAND SOURCE CODE
def get_list_dst_endpoints(self)
Function to get list_dst_endpoints attribute.
▶ EXPAND SOURCE CODE
def get_list_dst_rcsites(self)
Function to get list_dst_rcsites attribute.
▶ EXPAND SOURCE CODE
def get_list_src_endpoints(self)
Function to get list_src_endpoints attribute.
▶ EXPAND SOURCE CODE
def get_list_src_rcsites(self)
Function to get list_src_rcsites attribute.
▶ EXPAND SOURCE CODE
def get_max_throughput(self)
Function to get max_throughput attribute.
▶ EXPAND SOURCE CODE
def get_min_throughput(self)
Function to get min_throughput attribute.
▶ EXPAND SOURCE CODE
def get_num_circuits(self)
Function to get num_circuits attribute.
▶ EXPAND SOURCE CODE
def get_sense_uuid(self)
Function to get sense_uuid attribute.
▶ EXPAND SOURCE CODE
def get_sense_uuid_2(self)
Function to get sense_uuid_2 attribute.
▶ EXPAND SOURCE CODE
def get_sense_vlan(self)
Function to get sense_vlan attribute.
▶ EXPAND SOURCE CODE
def get_sense_vlan_2(self)
Function to get sense_vlan_2 attribute.
▶ EXPAND SOURCE CODE
def get_unidirectional(self)
Function to get unidirectional attribute.
▶ EXPAND SOURCE CODE
def set_events_to_wait(self, events)
Function to set events_to_wait attribute.
▶ EXPAND SOURCE CODE
def set_link_dst_state(self, state)
Function to set link_dst_state attribute.
▶ EXPAND SOURCE CODE
def set_link_src_state(self, state)
Function to set link_src_state attribute.
▶ EXPAND SOURCE CODE
def set_list_dst_endpoints(self, endpoints)
Function to set list_dst_endpoints attribute.
▶ EXPAND SOURCE CODE
def set_list_dst_rcsites(self, dst_rcsites)
Function to set list_dst_rcsites attribute.
▶ EXPAND SOURCE CODE
def set_list_src_endpoints(self, endpoints)
Function to set list_src_endpoints attribute.
▶ EXPAND SOURCE CODE
def set_list_src_rcsites(self, src_rcsites)
Function to set list_src_rcsites attribute.
▶ EXPAND SOURCE CODE
def set_max_throughput(self, threshold)
Function to set max_throughput attribute.
▶ EXPAND SOURCE CODE
def set_min_throughput(self, threshold)
Function to set min_throughput attribute.
▶ EXPAND SOURCE CODE
def set_num_circuits(self, circuits)
Function to set num_circuits attribute.
▶ EXPAND SOURCE CODE
def set_sense_uuid(self, uuid)
Function to set sense_uuid attribute.
▶ EXPAND SOURCE CODE
def set_sense_uuid_2(self, uuid)
Function to set sense_uuid_2 attribute.
▶ EXPAND SOURCE CODE
def set_sense_vlan(self, vlan)
Function to set sense_vlan attribute.
▶ EXPAND SOURCE CODE
def set_sense_vlan_2(self, vlan)
Function to set sense_vlan_2 attribute.
▶ EXPAND SOURCE CODE
def set_unidirectional(self, unidir)
Function to set unidirectional attribute.
▶ EXPAND SOURCE CODE