

Sections

- [Top](#)
- [Example code](#)
- [Authenticating](#)
- [OAuth Permissions](#)
- [Status codes](#)
- [Posting objects](#)
- [Sorting and paging](#)

- [Methods](#)
- [Result objects](#)

- [CORS](#)
- [ETags](#)
- ["Polling" for updates](#)
- [Activity feeds](#)
- [Debugging](#)

API Methods

- (top level)
 - [color_families](#) Retrieve list of color families
 - [current_user](#) Get current user
 - [fiber_attributes](#) Retrieve list of the current fiber attributes
 - [fiber_categories](#) List the current fiber categories
 - [search](#) Global search
 - [yarn_weights](#) Retrieve list of active yarn weights
- app
 - [config/delete](#) Delete a Ravelry-specific application configuration setting
 - [config/get](#) Get Ravelry-specific application configuration
 - [config/set](#) Set Ravelry-specific application configuration
 - [data/delete](#) Delete a user and application specific piece of data (key/value)
 - [data/get](#) Get user and application specific data
 - [data/set](#) Store user and application-specific data.
- bundled_items
 - [delete](#) Delete bundled item
 - [show](#) Get single bundled_item
- bundles
 - [create](#) Create bundle record
 - [delete](#) Delete a bundle record
 - [list](#) Get bundles list
 - [show](#) Get bundle record
 - [update](#) Update an existing bundle record
- carts
 - [add](#) Add a product to a cart. Used to integrate external pattern stores with the Ravelry library.
 - [create](#) Create a new cart. Used to integrate external pattern stores with the Ravelry library.

- [external_checkout](#) Notify Ravelry that a cart has been checked out (paid for) externally. This will create an invoice, mark it as paid, and deliver the products to the customer.
 - [loveknitting/external_checkout](#) Notify Ravelry that a cart has been checked out (paid for) at loveknitting.
- comments
 - [create](#) Post a comment related to an object
 - [delete](#) Delete a comment
 - [list](#) Get list of comments left by a user
- deliveries
 - [list](#) List the products that have been purchased by or gifted to the current user
 - [renew](#) Renew an expired digital product delivery token/url.
- designers
 - [show](#) Get designer details
- drafts
 - [create](#) Create a draft pattern
 - [create_photo](#) Add a photo to a draft pattern (using an uploaded image or URL as a source)
 - [list](#) Get a list of draft patterns that are associated with the current user's pro account(s)
 - [publish](#) Publish a draft pattern to Ravelry's pattern database.
 - [reorder_photos](#) Change order of associated photos
 - [show](#) Get draft pattern details
 - [unpublish](#) Undo a publish operation. See notes for limitations.
 - [update](#) Update a draft pattern
- extras
 - [create_attachment](#) Convert an upload into an (image) attachment that can be referenced in fields that accept markdown or HTML
- favorites
 - [add_to_bundle](#) Add a favorite record to a bundle
 - [create](#) Create favorite record
 - [delete](#) Delete a favorite record
 - [list](#) Get favorite list
 - [remove_from_bundle](#) Remove a favorite record from a bundle
 - [show](#) Retrieve a favorite record
 - [update](#) Update a favorite record
- fiber
 - [comments](#) Retrieve a stashed fiber's comments
 - [create](#) Create fiber stash record
 - [create_photo](#) Add a photo to a stashed fiber (using an uploaded image or URL as a source)
 - [delete](#) Permanently delete a fiber stash entry
 - [show](#) Get fiber stash record
 - [update](#) Update an existing fiber stash record
- fiber_attribute_groups
 - [list](#) Retrieve list of fiber attribute groups
- forum_posts
 - [show](#) Get single forum post
 - [unread](#) Get list of unread posts, across all forums
 - [update](#) Update a forum post
 - [vote](#) Update your vote on one of the forum post voting buttons
- forums
 - [filtered_topics](#) Filter topics across all forums/groups to find those that are relevant to the

- authenticated user
- [sets](#) Get forum sets for current user (or default set)
- [topics](#) Get topic list for a specific forum, personalize for the authenticated user
- friends
 - [activity](#) Retrieve recent friends' activity
 - [create](#) Add a friend
 - [destroy](#) Delete a friendship record
 - [list](#) Get friend list
- groups
 - [groups](#) Search the group directory
- in_store_sales
 - [add](#) Add a product to a cart
 - [add_by_pattern](#) Add a product to a cart using a pattern ID of a related pattern.
 - [checkout](#) Checkout a cart. The wholesale price will be added to your monthly bill.
 - [create](#) Create a new cart
 - [show](#) View a previously created cart
- languages
 - [languages](#) Retrieve list of available languages
- library
 - [search](#) Search a library
- messages
 - [archive](#) Archive a message
 - [create](#) Create and send a private message to another Ravelry user
 - [delete](#) Delete a message
 - [list](#) Get message list
 - [mark_read](#) Mark a message as read
 - [mark_unread](#) Mark a message as unread
 - [reply](#) Reply to a private message to another Ravelry user, same as create but links the messages together as a conversat
 - [show](#) Get message
 - [unarchive](#) Archive a message
- needles
 - [list](#) Get needle records
 - [sizes](#) Get available sizes for each needle type
 - [types](#) Get needle types
- packs
 - [create](#) Create pack
 - [delete](#) Delete pack
 - [show](#) Get single pack
 - [update](#) Update a pack
- pages
 - [show](#) Get page
 - [update](#) Update page
- pattern_attributes
 - [list](#) List the current pattern attributes
- pattern_categories
 - [list](#) List the current pattern categories
- pattern_source_types
 - [list](#) List the current pattern source types

- [pattern_sources](#)
 - [patterns](#) Get the set of patterns that a given source contains
 - [search](#) Search pattern source database
 - [show](#) Get pattern source details
- [patterns](#)
 - [comments](#) Retrieve a pattern's comments
 - [create_photo](#) Add a photo to a pattern (using an uploaded image or URL as a source)
 - [highlights](#) Get pattern highlights for the current user
 - [patterns](#) Get pattern details for multiple patterns
 - [projects](#) Retrieve the list of projects that are linked to this pattern
 - [reorder_photos](#) Change order of associated photos
 - [search](#) Search pattern database
 - [show](#) Get pattern details
 - [update](#) Update a pattern
- [people](#)
 - [show](#) Get user profile
 - [update](#) Update user profile
- [photos](#)
 - [delete](#) Delete photo
 - [dimensions](#) Get photo thumbnail dimensions
 - [sizes](#) Get available photo sizes
 - [status](#) Get the status of a photo creation that is in progress
 - [update](#) Update photo attributes
- [product_attachments](#)
 - [delete](#) Remove a product attachment from a product
 - [generate_download_link](#) Generate an expiring link that can be used to directly download the PDF associated with a product attachment
 - [show](#) Retrieve a product attachment
 - [update](#) Update a product attachment
 - [upload](#) Upload a new product attachment
- [products](#)
 - [activate](#) Activate a product (make it available for sale)
 - [attachments](#) Retrieve attached documents for this product
 - [create](#) Create a new product
 - [deactivate](#) Deactivate a product (make it unavailable for sale)
 - [loveknitting/export](#) Get loveknitting data for a product
 - [loveknitting/update_status](#) Update status of an associated loveknitting product
 - [show](#) Retrieve product information
 - [update](#) Update product information
- [projects](#)
 - [comments](#) Retrieve a project's comments
 - [crafts](#) Get list of crafts that are valid for use within projects
 - [create](#) Create project
 - [create_photo](#) Add a photo to a project (using an uploaded image or URL as a source)
 - [delete](#) Permanently delete a project
 - [list](#) Get project list
 - [project_statuses](#) Get list of statuses that are valid for use within projects
 - [reorder_photos](#) Change order of associated photos
 - [search](#) Search the project database

- [show](#) Get project detail
 - [update](#) Update project
- queue
 - [create](#) Create a queued project
 - [delete](#) Delete a queued project
 - [list](#) Get queued project list
 - [order](#) Get queue ordering (list of all names, ids, and positions)
 - [reposition](#) Move a queued project to a new position
 - [show](#) Get queued project detail
 - [update](#) Update a queued project
- saved_searches
 - [list](#) Get list of saved searches for the current user
- shops
 - [search](#) Search yarn shop database
 - [show](#) Get shop details
- stash
 - [comments](#) Retrieve a stashed yarn's comments
 - [create](#) Create stash record
 - [create_photo](#) Add a photo to a stashed yarn (using an uploaded image or URL as a source)
 - [delete](#) Permanently delete a stash entry
 - [list](#) Get stash list
 - [reorder_photos](#) Change order of associated photos
 - [search](#) Search the project database
 - [show](#) Get stash list
 - [unified/list](#) Get unified stash list that combines yarn stash with fiber stash
 - [update](#) Update a stash record
- stores
 - [list](#) List the current user's pattern stores
 - [products](#) List the products in a user's stores
 - [purchases](#) Export purchase (transaction) history
- topics
 - [create](#) Create a new topic
 - [posts](#) Get post list for a specific forum, personalize for the authenticated user
 - [read](#) Update read/unread marker for a specific topic
 - [reply](#) Post a reply to a topic
 - [show](#) Get topic information
 - [update](#) Update a topic
- upload
 - [image](#) Upload an image file for later processing or attaching
 - [request_token](#) Generate an upload token
 - [status](#) Get uploaded image IDs
- volumes
 - [apply_updates](#) Apply any unapplied updates to a volume and any related volumes (in the case of a product with multiple PDF documents attached)
 - [create](#) Create a new volume (library entry) in the current user's library
 - [delete](#) Delete a volume
 - [show](#) Get volume details
 - [update](#) Create a new volume (library entry)
- yarn_attributes

- [list](#) List the current pattern attributes
- yarn_companies
 - [search](#) Search the yarn company directory
- yarns
 - [comments](#) Retrieve a yarns's comments
 - [search](#) Search yarn database
 - [show](#) Get yarn details
 - [yarns](#) Get yarn details for multiple yarns

Result objects

- [Activity](#)
- [Ad](#)
- [AttributeGroup](#)
- [Bookmark](#)
- [Bundle](#)
- [BundledItem](#)
- [Business](#)
- [Cart](#)
- [CartItem](#)
- [Collection](#)
- [ColorFamily](#)
- [Colorway](#)
- [CombinedCart](#)
- [Comment](#)
- [ComponentYarn](#)
- [Craft](#)
- [Delivery](#)
- [Document](#)
- [DownloadLink](#)
- [DraftComponentYarn](#)
- [DraftErrataLink](#)
- [DraftNeedleSize](#)
- [DraftPattern](#)
- [DraftPatternSource](#)
- [DraftPatternYarn](#)
- [FiberAttribute](#)
- [FiberAttributeGroup](#)
- [FiberCategory](#)
- [FiberPack](#)
- [FiberStash](#)
- [FiberType](#)
- [Forum](#)
- [ForumPost](#)
- [ForumPreference](#)
- [ForumSet](#)
- [ForumStatisticSummary](#)
- [Friendship](#)

- [Group](#)
- [InStoreSale](#)
- [Invoice](#)
- [InvoiceLineItem](#)
- [Language](#)
- [Message](#)
- [NeedleRecord](#)
- [NeedleSize](#)
- [NeedleType](#)
- [Pack](#)
- [Page](#)
- [Pattern](#)
- [PatternAttribute](#)
- [PatternAuthor](#)
- [PatternCategory](#)
- [PatternClassification](#)
- [PatternLanguage](#)
- [PatternNeedleSize](#)
- [PatternSource](#)
- [PatternSourceType](#)
- [PatternTagging](#)
- [Payment](#)
- [Photo](#)
- [Printing](#)
- [Product](#)
- [ProductAttachment](#)
- [ProductNotification](#)
- [Project](#)
- [ProjectStatus](#)
- [QueuedProject](#)
- [QueuedStash](#)
- [Saleable](#)
- [SavedSearch](#)
- [Shop](#)
- [ShopCustomer](#)
- [ShopSchedule](#)
- [SocialSite](#)
- [Stash](#)
- [StashStatus](#)
- [Store](#)
- [Tool](#)
- [Topic](#)
- [UnifiedStash](#)
- [User](#)
- [UserSite](#)
- [Volume](#)
- [VolumeAttachment](#)
- [Yarn](#)

- [YarnAttributeGroup](#)
- [YarnCompany](#)
- [YarnCountry](#)
- [YarnFiber](#)
- [YarnProvenance](#)
- [YarnWeight](#)



Ravelry API Documentation

Last updated 2026-03-30



Welcome!

Once you decide which type of credentials you need, create your App and keys by visiting <https://www.ravelry.com/pro/developer>. If you do not already have a free Pro account you'll be prompted to create one.

This documentation lists the API methods, inputs, and outputs but it doesn't describe **how** to put it all together. You may find the [Ravelry API group](#) to be helpful.

You are also very welcome to email us at api@ravelry.com. Most API improvements originate from requests from users.

Accessing Ravelry with HTTP Basic Auth: read only access

If you only need to use read-only API methods, read-only Basic Auth is the simplest way to get started.

When you use your read-only credentials, you will only be able to call API methods that are not marked as "authenticated" in the documentation.

Use HTTP Basic Authentication with your HTTP client and supply the username and password taken from your app's credentials. SSL is required.

Example:

```
curl -u basic_auth_username:basic_auth_password https://api.ravelry.com/current_user.json
```

Authenticating via HTTP Basic Auth: personal account access

If you only need to sign in to Ravelry as yourself, you can use this simple method to access the API. You do not have to request specific permissions when authenticating this way - all permissions are granted.

Use HTTP Basic Authentication with your HTTP client and supply your access key as the username and your personal key (not your secret key) as the password. Note that SSL is required: you will receive a 403 error if you do not use HTTPS.

IMPORTANT: "Basic Auth: personal account access" credentials provide **full access to the Ravelry account that they are associated with**. This is intended for personal projects.

A quick example:

```
curl -u basic_auth_username:basic_auth_personal_key https://api.ravelry.com/current_user.json
```

Authenticating with Ravelry via OAuth 2.0

Use your client ID and client secret to authenticate with Ravelry using any [OAuth 2 library](#).

The OAuth 2 URLs are:

- <https://www.ravelry.com/oauth2/token>
- <https://www.ravelry.com/oauth2/auth>

See "OAuth scope" below for information on requesting specific permissions.

When requesting your token, we support basic auth (the "Authorization" header) for passing your client ID and secret. Submitting these as form parameters (also called "body auth") is not supported.

OAuth 2 tokens expire in 24 hours. You will probably want to request the "offline" scope so that you can receive a refresh token. Your OAuth client library should allow you to refresh your access token before it expires so that you do not have to re-authorize. Your application should handle HTTP 401 Unauthorized responses by re-authenticating the user.

Authenticating with Ravelry via OAuth 1.0a

Use your consumer key and consumer secret authenticate with Ravelry using any [OAuth 1.0a library](#).

The OAuth URLs are:

- https://www.ravelry.com/oauth/request_token
- https://www.ravelry.com/oauth/access_token
- <https://www.ravelry.com/oauth/authorize>

See "OAuth scope" below for information on requesting specific permissions.

OAuth tokens are long-lived but they can expire after a period of inactivity or if the user revokes access. **Your application should handle HTTP 401 Unauthorized** responses by re-authenticating the user.

OAuth scopes (permissions)

The OAuth request_token and OAuth 2 token methods accept an optional "scope" parameter. Use this parameter when your application needs to request additional privileges that aren't granted by default. To request several privileges, separate the values with a space.

If you are using a personal key instead of OAuth, you do not need to request specific permissions.

Key	Description
offline	<i>standard OAuth 2.0 scope for requesting refresh tokens</i>
forum-write	create, edit, and delete forum posts
message-write	create (ie. send messages to other users) and delete private messages
patternstore-read	enumerate the pattern stores that the user administers as well as the products within those stores
patternstore-pdf	(currently limited access, available by request) generate download links for PDF files within the user's pattern stores
deliveries-read	list the products that have been purchased by or gifted to the current user
library-pdf	directly download PDFs from a user's library using generate download link . note: tokens that request this scope will expire more quickly than usual and may also expire if a rate limit is exceeded. You may want to hold both a normal token and a library-pdf token for each user when this permission is requested.

There are also scopes which allow you to select a minimal set of privileges.

Key	Description
profile-only	allows access to /current_user.json and nothing else
carts-only	allows access to /carts/*.json and nothing else

HTTP Status Codes

Your application may encounter the following client errors (4xx) and server errors (5xx)

- 400 Bad Request: Your API call is not valid. Check the parameters supplied against the documentation.
- 401 Unauthorized: Your OAuth token has expired or the user has revoked access.
- 403 Forbidden: OAuth token is not valid, API keys are not valid, or authenticated user is not permitted to use the requested method.
- 404 Not Found: you attempted to access a resource that no longer exists
- 405 Method Not Allowed: you attempted to POST to a GET API method or vice-versa
- 413 Request Entity Too Large: your POST was too large, refer to documentation for per-method limits.
- 429 Too Many Requests: refer to the documentation for per-method limits.
- 500 Server Error: outside of OAuth flow, this signals an error on Ravelry's side. We do receive an error notification but please report a bug.
- 500 Server Error: outside of OAuth flow, this signals an error on Ravelry's side. We do receive an error notification but please report a bug.
- 503 Service Unavailable: returned if the Ravelry API is down / not available
- 504 Gateway Time-out: your request was cancelled because it took more than 10 seconds to generate your response. If you are paginating, make sure you choose a reasonable page size. If a page size <= 100 times out, it is considered our bug.

Input Objects

Some API calls show a parameter named "data" with a TypeName#POST object as the parameter data type.

For these methods, you may submit either a JSON object or name/value pairs. To submit JSON, you may POST it normally with the parameter name "data" (recommended) or submit it as the raw POST data. Note that you must submit JSON instead of name/value pairs if you want to include nested data.

Examples with the usual form encoding left out:

JSON as the raw post:

```
POST {name: "Bond", nickname: "007"}
```

JSON with a key/value:

```
POST data={name: "Bond", nickname: "007"}
```

Plain parameters: if you don't need to or want to nest data. Note that each parameter is submitted individually and not nested under "data"

```
POST name=foo&nickname=007
```

Sorting and Pagination

Unless otherwise specified, all API calls that accept a "sort" sort order parameter have 2 special features:

- Multiple sort orders can be applied by using a space delimited string of sort orders
- Sort orders can be reversed by adding an _ (underscore) suffix. So the reverse of "name" would be "name_".

Methods that paginate accept "page_size" and "page" parameters and return a result object that contains a Paginator. A paginator object includes the following properties: page_count, page, page_size, results, last_page

Additional documentation

- [Cross origin requests \(CORS\)](#)
- [Use Etags to eliminate redundant result retrieval](#)
- ["Polling" for unread messages](#)
- [Activity feeds](#)
- [Debugging requests](#)

API Methods

/

/color_families

GET /color_families.json
Retrieve list of color families

Return Values

Name	Type	Required	Description
color_families	Array, ColorFamily	Yes	All color families

Example

/color_families.json

/current_user

authenticated

GET /current_user.json
Get current user

Return Values

Name	Type	Required	Description
user	User (full)	Yes	User

Example

/current_user.json

/fiber_attributes

GET /fiber_attributes.json
Retrieve list of the current fiber attributes

Return Values

Name	Type	Required	Description
fiber_attributes	Array, FiberAttribute	Yes	All fiber attributes

Notes

Fiber attributes seldom change, I'd recommend caching them for up to 24 hours. This method does not require an API key.

Example

/fiber_attributes.json

/fiber_categories

GET /fiber_categories.json
List the current fiber categories

Return Values

Name	Type	Required	Description
fiber_categories	Array, FiberCategory (list)	Yes	List of all fiber categories

Notes

Fiber categories seldom change, I'd recommend caching them for up to 24 hours. This method does not require an API key.

/search

GET /search.json
Global search

Parameters

Name	Type	Required	Description
query	String	Yes	Search term for fulltext searching yarns
limit	Integer		Number of results to retrieve. Default = 50, maximum = 500
types	String		Optional space delimited list of result types to include. Available options: User, PatternAuthor, PatternSource, Pattern, YarnCompany, Yarn, Group, Event, Project, Page, Topic, Shop

Return Values

Name	Type	Required	Description
------	------	----------	-------------

Name	Type	Required	Description
results	Array, Object	Yes	Search results, see below for details about the contents of the result object

Notes

Global search is a simple text-only search that returns basic information about each search result. *****For more powerful search APIs*****, see `/patterns/search.json`, `/yarns/search.json`, etc.

Result object contents

Key	Description										
title	Title of the object										
type_name	Type of object, suitable for displaying to end users										
caption	(optional) Caption/description related to object, suitable for displaying to end users										
tiny_image_url	(optional) Image suitable for displaying inline with text. Typically 24x24.										
image_url	(optional) Primary image associated with the object. Typically 500px on the longest side.										
	Nested object with information about the matching record										
	<table> <tr> <th>Key</th><th>Description</th></tr> <tr> <td>type</td><td>Type of record, corresponds with API Result Types</td></tr> <tr> <td>id</td><td>id of record</td></tr> <tr> <td>permalink</td><td>current permalink for record</td></tr> <tr> <td>uri</td><td>API URI for retrieving information about the record</td></tr> </table>	Key	Description	type	Type of record, corresponds with API Result Types	id	id of record	permalink	current permalink for record	uri	API URI for retrieving information about the record
Key	Description										
type	Type of record, corresponds with API Result Types										
id	id of record										
permalink	current permalink for record										
uri	API URI for retrieving information about the record										
record											

/yarn_weights

GET `/yarn_weights.json`

Retrieve list of active yarn weights

Return Values

Name	Type	Required	Description
yarn_weights	Array, YarnWeight	Yes	All active yarn weights

Example

`/yarn_weights.json`

app

app/config/delete authenticated

POST `/app/config/delete.json`

Delete a Ravelry-specific application configuration setting

Parameters

Name	Type	Required	Description
keys	String	Yes	Space delimited list of keys to delete

Return Values

Name	Type	Required	Description
config	Hash	Yes	Previous contents of keys that were deleted

Example

/app/config/delete.json?keys=foo+bar

app/config/get authenticated

GET /app/config/get.json

Get Ravelry-specific application configuration

Parameters

Name	Type	Required	Description
keys	String		Space delimited list of keys to retrieve

Return Values

Name	Type	Required	Description
config	Hash	Yes	Contents of keys that were updated

Example

/app/config/set.json?keys=foo+bar

app/config/set authenticated

POST /app/config/set.json

Set Ravelry-specific application configuration

Parameters

Name	Type	Required	Description
(key_names)	String	Yes	Key/value pairs to set

Return Values

Name	Type	Required	Description
config	Hash	Yes	Contents of keys that were updated

Notes

Send each key/value that you want to set as query parameters. Currently supported parameters are:

- "profile_badge" [0|1] enable application badge in user's profile. This should be an *opt-in* setting in your app.

Example

/app/config/set.json?profile_badge=1

app/data/delete authenticated

POST /app/data/delete.json

Delete a user and application specific piece of data (key/value)

Parameters

Name	Type	Required	Description
------	------	----------	-------------

keys	String	Yes	Space delimited list of keys to delete
------	--------	-----	--

Return Values

Name	Type	Required	Description
------	------	----------	-------------

data	Hash	Yes	Previous contents of keys that were deleted
------	------	-----	---

Example

/app/data/delete.json?keys=foo+bar

app/data/get authenticated

GET /app/data/get.json

Get user and application specific data

Parameters

Name	Type	Required	Description
------	------	----------	-------------

keys	String		Space delimited list of keys to retrieve
------	--------	--	--

Return Values

Name	Type	Required	Description
------	------	----------	-------------

data	Hash	Yes	Contents of keys that were updated
------	------	-----	------------------------------------

Notes

You are welcome to use Ravelry's key/value storage to store any application specific data. This could be used to offer syncing, backup of settings or data, etc. to your users.

Example

/app/data/get.json?keys=foo

app/data/set authenticated

POST /app/data/set.json

Store user and application-specific data.

Parameters

Name	Type	Required	Description
(key_names)	String	Yes	Key/value pairs to set

Return Values

Name	Type	Required	Description
data	Hash	Yes	Contents of keys that were updated

Notes

You are welcome to use Ravelry's key/value storage to store any application specific data. This could be used to offer syncing, backup of settings or data, etc. to your users. Send each key/value that you want to set as query parameters.

Example

/app/data/set.json?foo=bar

bundled_items

bundled_items/delete authenticated

DELETE /bundled_items/{bundled_item_id}.json

Delete bundled item

URI Parameters

Name	Type	Required	Description
bundled_item_id	Integer	Yes	Bundled item to delete

Return Values

Name	Type	Required	Description
item	BundledItem (full)	Yes	Bundled item that was deleted

bundled_items/show authenticated

GET /bundled_items/{bundled_item_id}.json
Get single bundled_item

URI Parameters

Name	Type	Required	Description
bundled_item_id	Integer	Yes	Bundled item to retrieve

Return Values

Name	Type	Required	Description
bundled_item	BundledItem (full)	Yes	Bundled item
item	Object	Yes	Item

bundles

bundles/create authenticated

POST /people/{username}/bundles/create.json
Create bundle record

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to create bundle for

Parameters

Name	Type	Required	Description
data	Bundle (POST)	Yes	Bundle JSON object

Return Values

Name	Type	Required	Description
bundle	Bundle (full)	Yes	Bundle

Example

/people/username/bundles/create.json { "name": "my awesome bundle", "notes": "stuff that is awesome." }

bundles/delete authenticated

DELETE /people/{username}/bundles/{id}.json

Delete a bundle record

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to retrieve bundle from
id	Integer	Yes	Id of the bundle record that should be deleted

Return Values

Name	Type	Required	Description
bundle	Bundle (full)	Yes	The deleted record

bundles/list authenticated

GET /people/{username}/bundles/list.json

Get bundles list

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to retrieve bundles from

Parameters

Name	Type	Required	Description
owner_types	Array, String		Space delimited list of types of bundles to retrieve. Accepted options: designer, group, personal. Defaults to all types.
query	String		Search query for bundles.
page	Integer		Result page to retrieve. Defaults to 1 (the first page).
page_size	Integer		Defaults to 25. Maximum size accepted = 100

Return Values

Name	Type	Required	Description
bundles	Array, Bundle (list)	Yes	Matching bundles
paginator	Paginator	Yes	Pagination object with total results, pages

Notes

Bundles are returned in ordered by creation date, descending. If you request a mix of different types of bundles, you can use the "type" key to determine the type of bundle that you are receiving.

Example

/people/username/bundles/list.json

bundles/show authenticated

GET /people/{username}/bundles/{id}.json

Get bundle record

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to retrieve bundle from
id	Integer	Yes	Bundle to retrieve

Return Values

Name	Type	Required	Description
bundle	Bundle (full)	Yes	Bundle

Example

/people/username/bundles/989.json

bundles/update authenticated

POST /people/{username}/bundles/{id}.json

Update an existing bundle record

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the bundle
id	Integer	Yes	ID of the bundle to update

Parameters

Name	Type	Required	Description
data	Bundle (POST)	Yes	Bundle JSON object

Return Values

Name	Type	Required	Description
------	------	----------	-------------

Name	Type	Required	Description
bundle	Bundle (full)	Yes	Bundle

Example

```
/people/username/bundle/989.json { "name": "an updated name" }
```

carts

carts/add authenticated

POST /carts/{id}/add.json

Add a product to a cart. Used to integrate external pattern stores with the Ravelry library.

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	ID of the cart to update

Parameters

Name	Type	Required	Description
item_code	String	Yes	SKU of the product to add. Configurable in your Ravelry store as alphanumeric "Item number".

Return Values

Name	Type	Required	Description
cart	Cart (full)	Yes	The cart and its current contents

carts/create authenticated

POST /carts/create.json

Create a new cart. Used to integrate external pattern stores with the Ravelry library.

Parameters

Name	Type	Required	Description
store_id	Integer	Yes	ID of store to associate with the cart. Contact Ravelry for your cart access and your store ID.

Return Values

Name	Type	Required	Description
cart	Cart (full)	Yes	The newly created cart

Notes

You can access Cart API methods after asking Ravelry to enable this option for your app. You will then be able to create and checkout carts in stores that are associated with the Pro Account that your app is associated with.

carts/external_checkout authenticated

POST /carts/{id}/external_checkout.json

Notify Ravelry that a cart has been checked out (paid for) externally. This will create an invoice, mark it as paid, and deliver the products to the customer.

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	ID of the cart to checkout

Parameters

Name	Type	Required	Description
payment_reference	String		Custom text to associate with the Ravelry invoice/receipt. Not visible to customer. Normally, you'd use your internal invoice number

Return Values

Name	Type	Required	Description
invoice	Invoice (cart)	Yes	The generated invoice. You may want to store the ID for future reference.

Notes

You can access Cart API methods after asking Ravelry to enable this option for your app. You will then be able to create and checkout carts in stores that are associated with the Pro Account that your app is associated with. If you are only using the Ravelry API for external checkouts (adding patterns to a user's Ravelry library), we recommend using the carts-only OAuth scope so that the user does not have to provide unnecessary access to their Ravelry account. See **OAuth Permissions**.

carts/loveknitting/external_checkout authenticated

POST /carts/loveknitting/{id}/external_checkout.json

Notify Ravelry that a cart has been checked out (paid for) at loveknitting.

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	ID of the cart to checkout

Parameters

Name	Type	Required	Description
payment_reference	String		Custom text to associate with the Ravelry invoice/receipt. Not visible to customer. Normally, you'd use your internal invoice number
product_id_list	String		Space delimited list of product IDs that were purchased.

Return Values

Name	Type	Required	Description
invoice	Invoice (cart)	Yes	The generated invoice. You may want to store the ID for future reference.

comments

comments/create

POST /comments/create.json
Post a comment related to an object

Parameters

Name	Type	Required	Description
type	String	Yes	The type of item that is being commented on. One of: project, pattern, yarn, stash.
commented_id	Integer	Yes	ID of item being commented on.
body	String	Yes	Comment body. Text, Markdown, HTML or some combination of those is accepted.
reply_to_id	Integer		ID of comment being replied to. Only the owner of a project, stash, yarn or pattern can post replies.

Return Values

Name	Type	Required	Description
comment	Comment (full)	Yes	The newly created comment

Required permissions

[message-write](#)

Notes

Creates and immediately posts a comment. Comments cannot be edited after they are created but they can be deleted. Note that the returned comment body may differ from the submitted text because Markdown will be processed and unacceptable HTML tags will be removed. This method requires message-write permission

comments/delete

DELETE /comments/{id}.json

Delete a comment

URI Parameters

Name	Type	Required	Description
id	Integer		ID of the comment being deleted.

Return Values

Name	Type	Required	Description
comment	Comment (full)	Yes	The deleted comment

Required permissions

[message-write](#)

Notes

A user may delete their own comments as well as any comments posted on items that they own. This method requires message-write permission

comments/list

GET /people/{username}/comments/list.json
Get list of comments left by a user

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to retrieve projects from

Parameters

Name	Type	Required	Description
page	Integer		Result page to retrieve. Defaults to 1 (the first page).
page_size	Integer		Defaults to 25. Maximum size accepted = 100

Return Values

Name	Type	Required	Description
comments	Array, Comment (history)	Yes	

Notes

The comment histories of other Ravelry users cannot be retrieved.

deliveries

deliveries/list

GET /deliveries/list.json

List the products that have been purchased by or gifted to the current user

Parameters

Name	Type	Required	Description
page	Integer		Result page to retrieve. Defaults to 1 (the first page).
page_size	Integer		Defaults to 25. Maximum size accepted = 100

Return Values

Name	Type	Required	Description
deliveries	Array, Delivery (list)	Yes	Results
paginator	Paginator	Yes	Pagination object with total results, pages

Required permissions

[deliveries-read](#)

Notes

A delivery will contain one more more products. Each product may be associated with some number of patterns or pattern sources. Deliveries are returned in ordered by creation date, descending. This method requires deliveries-read permission

Example

/deliveries/list.json

deliveries/renew

POST /deliveries/{id}/renew.json

Renew an expired digital product delivery token/url.

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Delivery ID

Parameters

Name	Type	Required	Description
------	------	----------	-------------

Name	Type	Required	Description
customer_email_address	String	Yes	The email address supplied during the initial checkout

Return Values

Name	Type	Required	Description
delivery	Delivery (receipt)	Yes	the renewed delivery

Notes

Renews an expired delivery link/token so that the delivery_url in the returned object is useable by an end user. Note that this API method is only useful to retail shops who are participating in the In Store Sales program.

designers

designers/show authenticated

GET /designers/{id}.json
Get designer details

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Designer ID or permalink

Parameters

Name	Type	Required	Description
include	Array, String		Extra result parts to include. Space delimited. Accepted options: featured_bundles

Return Values

Name	Type	Required	Description
pattern_author	PatternAuthor (full)	Yes	Designer (pattern author) profile
featured_bundles	Array, Bundle (list)		Featured bundles, if requested

Notes

To search/sort a designer's patterns, use the pattern search API and set the "designer-link" parameter to the designer permalink (preferred) or set the "designs-by" parameter to the designer's name.

About profile notes: on Ravelry.com, the user blurb (pattern_author.users[0].blurb) is displayed if the designer does not have any profile notes.

Example

/designers/1.json?include=featured_bundles

drafts

drafts/create

POST /drafts/patterns/create.json

Create a draft pattern

Parameters

Name	Type	Required	Description
data	DraftPattern (POST)	Yes	Draft pattern data

Return Values

Name	Type	Required	Description
draft_pattern	DraftPattern (full)	Yes	Draft pattern

Required permissions

[patternstore-read](#) OR [patternstore-write](#)

Notes

Note: You must supply a draft_business_id. The draft pattern will be associated with this business (pro account) One way to see available businesses is by using the /patterns/drafts/list.json API call

drafts/create_photo authenticated

POST /drafts/patterns/{draft_pattern_id}/create_photo.json

Add a photo to a draft pattern (using an uploaded image or URL as a source)

URI Parameters

Name	Type	Required	Description
draft_pattern_id	String	Yes	Draft pattern id

Parameters

Name	Type	Required	Description
image_id	Integer		Uploaded image to use, created via /upload/image.json
source_url	String		URL of the image to use (preferably high-res and 1600px on the smallest side minimum)

Return Values

Name	Type	Required	Description
status_token	String	Yes	Token that can be used to check the status of the photo

Notes

See the [projects/create_photo](#) documentation for more information on how this works.

Photos can be deleted/removed with the [photos/delete](#) method.

drafts/list

GET /drafts/patterns/list.json

Get a list of draft patterns that are associated with the current user's pro account(s)

Parameters

Name	Type	Required	Description
business_id	Integer		If supplied, only return the draft patterns associated with this business

Return Values

Name	Type	Required	Description
businesses	Array, Business (list)	Yes	
draft_patterns	Array, DraftPattern (full)	Yes	

Required permissions

[patternstore-read](#) OR [patternstore-write](#)

Notes

Returns a list of [businesses](#) (ie. pro accounts) that the current user is associated with and the [draft patterns](#) associated with the user's businesses (via draft_business_id).

Example

/patterns/drafts/list.json

drafts/publish

authenticated

POST /drafts/patterns/{draft_pattern_id}/publish.json

Publish a draft pattern to Ravelry's pattern database.

URI Parameters

Name	Type	Required	Description
draft_pattern_id	Integer	Yes	Draft pattern to publish

Parameters

Name	Type	Required	Description
preview	Boolean		If set to "true", the pattern will be validated for errors/warnings but not published.

Return Values

Name	Type	Required	Description
draft_pattern	DraftPattern (full)	Yes	Draft pattern
pattern	Pattern (full)		The published pattern
published	Boolean	Yes	True if the pattern was published successfully
preview_url	String		URL to preview the pattern on ravelry.com. Only returned if no errors are present.
errors	Array, Hash	Yes	List of errors. Errors will prevent a pattern from being published.
warnings	Array, Hash	Yes	List of warnings. Warnings will not prevent a pattern from being published.

Notes

Apps should preview and display warnings to the user before publishing a pattern.

drafts/reorder_photos authenticated

POST /drafts/patterns/{draft_pattern_id}/reorder_photos.json
Change order of associated photos

URI Parameters

Name	Type	Required	Description
draft_pattern_id	Integer	Yes	Draft pattern ID

Parameters

Name	Type	Required	Description
sort_order	String	Yes	List of photo IDs, space delimited

Return Values

Name	Type	Required	Description
photos	Array, Photo (full)	Yes	Set of photos with updated ordering

Notes

The first photo becomes the primary photo for the pattern

drafts/show

GET /drafts/patterns/{id}.json

Get draft pattern details

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Draft pattern to retrieve

Return Values

Name	Type	Required	Description
draft_pattern	DraftPattern (full)	Yes	Draft pattern

Required permissions

[patternstore-read](#) OR [patternstore-write](#)

Example

/drafts/patterns/100.json

drafts/unpublish authenticated

POST /drafts/patterns/{draft_pattern_id}/unpublish.json

Undo a publish operation. See notes for limitations.

URI Parameters

Name	Type	Required	Description
draft_pattern_id	Integer	Yes	Draft pattern to unpublish

Return Values

Name	Type	Required	Description
draft_pattern	DraftPattern (full)	Yes	Draft pattern

Notes

A draft pattern can be unpublished via the API if:

- The pattern was published less than 7 days ago
- The pattern has not been sold or downloaded
- The pattern has not been linked to a project or queued project

drafts/update authenticated

PUT /drafts/patterns/{draft_pattern_id}.json

Update a draft pattern

URI Parameters

Name	Type	Required	Description
draft_pattern_id	Integer	Yes	Draft pattern to update

Parameters

Name	Type	Required	Description
data	DraftPattern (POST)	Yes	Draft pattern JSON object

Return Values

Name	Type	Required	Description
draft_pattern	DraftPattern (full)	Yes	Draft pattern

extras

extras/create_attachment authenticated

POST /extras/create_attachment.json

Convert an upload into an (image) attachment that can be referenced in fields that accept markdown or HTML

Parameters

Name	Type	Required	Description
image_id	Integer	Yes	Uploaded image to use, created via /upload/image.json

Return Values

Name	Type	Required	Description
image_path	String	Yes	Relative image URL that can be inserted into a forum post or other markdown document

Notes

This method can be used to allow Ravelry Extras (<http://ravelry.com/extras>) subscribers to host their media files on Ravelry and reference them in forum posts, messages, and other fields that accept images in markdown or HTML. Files that are not images are not accepted and will not be processed.

To test whether or not a user has access to Extras, call this method with no parameters. A HTTP 403 Forbidden return code will indicate that the user does not have this feature.

This method does not return until the image has been processed. This can take a few seconds.

favorites

favorites/add_to_bundle authenticated

POST /people/{username}/favorites/{id}/add_to_bundle.json

Add a favorite record to a bundle

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the favorite record
id	Integer	Yes	Id of the favorite record

Parameters

Name	Type	Required	Description
bundle_id	Integer	Yes	Id of the bundle the favorite should be added to

Return Values

Name	Type	Required	Description
bookmark	Bookmark (full)	Yes	The bundled record

favorites/create authenticated

POST /people/{username}/favorites/create.json

Create favorite record

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the favorite record

Parameters

Name	Type	Required	Description
data	Bookmark (POST)	Yes	Bookmark (favorite) JSON object

Return Values

Name	Type	Required	Description
bookmark	Bookmark (full)	Yes	The newly created record

Example

```
/people/username/favorites/create.json { "type": "pattern", "favorited_id": 1, "comment": "This is a comment" }
```

favorites/delete authenticated

DELETE /people/{username}/favorites/{id}.json
Delete a favorite record

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the favorite record
id	Integer	Yes	Id of the favorite record that should be deleted

Return Values

Name	Type	Required	Description
bookmark	Bookmark (full)	Yes	The deleted record

favorites/list authenticated

GET /people/{username}/favorites/list.json
Get favorite list

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to retrieve projects from

Parameters

Name	Type	Required	Description
types	Array, String		Space delimited list of types of favorites to retrieve. Accepted options: project, pattern, yarn, stash, forumpost, designer, yarnbrand, yarnshop, bundle. Defaults to all types.
query	String		Search query for full text search. Cannot be combined with "tag" parameter.
deep_search	Boolean		Full text search should search inside text of favorited items (notes, etc). Defaults to false.

Name	Type	Required	Description
tag	String		Search query for tag search. Cannot be combined with "query" parameter.
page	Integer		Result page to retrieve. Defaults to 1 (the first page).
page_size	Integer		Defaults to 25. Maximum size accepted = 100

Return Values

Name	Type	Required	Description
favorites	Array, Bookmark (list)	Yes	Matching favorites
paginator	Paginator	Yes	Pagination object with total results, pages

Notes

Favorites are returned in ordered by creation date, descending. The favorited item is nested in the JSON result under the key "favorited". If you request a mix of different types of favorites, you can use the "type" key to determine the type of favorite that you are receiving.

Example

/people/username/favorites/list.json

favorites/remove_from_bundle authenticated

POST /people/{username}/favorites/{id}/remove_from_bundle.json
Remove a favorite record from a bundle

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the favorite record
id	Integer	Yes	Id of the favorite record

Parameters

Name	Type	Required	Description
bundle_id	Integer	Yes	Id of the bundle the favorite should be removed from

Return Values

Name	Type	Required	Description
bookmark	Bookmark (full)	Yes	The unbundled record

favorites/show authenticated

GET /people/{username}/favorites/{id}.json

Retrieve a favorite record

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the favorite record
id	Integer	Yes	ID of the favorite to retrieve

Return Values

Name	Type	Required	Description
bookmark	Bookmark (full)	Yes	The newly created record

Example

/people/username/favorites/42.json

favorites/update authenticated

POST /people/{username}/favorites/{id}.json
Update a favorite record

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the favorite record
id	Integer	Yes	Id of the favorite record that should be updated

Parameters

Name	Type	Required	Description
data	Bookmark (POST)	Yes	Bookmark (favorite) JSON object

Return Values

Name	Type	Required	Description
bookmark	Bookmark (full)	Yes	The updated record

Example

/people/username/favorites/42.json { "comment": "This is an updated comment" }

fiber

fiber/comments

GET /people/{username}/fiber/{id}/comments.json

Retrieve a stashed fiber's comments

Parameters

Name	Type	Required	Description
page	Integer		Result page to retrieve. Defaults to first page.
page_size	Integer		Defaults to 25 comments per page. Maximum is 100.
sort	String		Sort order . Options are: time (and time_ for a descending sort)

Return Values

Name	Type	Required	Description
comments	Array, Comment	Yes	Comments with nested replies.
paginator	Paginator	Yes	Pagination object with total results, pages, etc

Notes

Comments have one level of nesting. Replies from the owner of the stashed fiber may be nested under the "replies" attribute.

fiber/create authenticated

POST /people/{username}/fiber/create.json

Create fiber stash record

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to create fiber stash for

Parameters

Name	Type	Required	Description
data	FiberStash (POST)	Yes	Fiber Stash JSON object

Return Values

Name	Type	Required	Description
fiber_stash	FiberStash (full)	Yes	Fiber Stash

Example

```
/people/username/fiber/create.json { "yarn_id": 1, "dye_lot": "42" }
```

fiber/create_photo authenticated

POST /people/{username}/fiber/{id}/create_photo.json

Add a photo to a stashed fiber (using an uploaded image or URL as a source)

URI Parameters

Name	Type	Required	Description
username	String	Yes	Username of the user who owns the fiber stash entry
id	String	Yes	Fiber Stash ID

Parameters

Name	Type	Required	Description
image_id	Integer		Uploaded image to use, created via /upload/image.json
source_url	Integer		URL of the image to use (preferably high-res)

Return Values

Name	Type	Required	Description
status_token	String	Yes	Token that can be used to check the status of the photo

Notes

See the projects create_photo documentation for more information on how this works.

fiber/delete authenticated

DELETE /people/{username}/fiber/{id}.json

Permanently delete a fiber stash entry

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the fiber stash entry
id	Integer	Yes	Fiber stash ID

Return Values

Name	Type	Required	Description
fiber_stash	FiberStash (full)	Yes	Fiber stash that was deleted

fiber/show authenticated

GET /people/{username}/fiber/{id}.json

Get fiber stash record

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to retrieve stash from
id	Integer	Yes	Stash to retrieve

Return Values

Name	Type	Required	Description
fiber_stash	FiberStash (full)	Yes	Stash
user	User (small)	Yes	User

Example

/people/username/fiber/989.json

fiber/update authenticated

POST /people/{username}/fiber/{id}.json
Update an existing fiber stash record

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the fiber entry
id	Integer	Yes	ID of the fiber stash entry to update

Parameters

Name	Type	Required	Description
data	FiberStash (POST)	Yes	Fiber Stash JSON object

Return Values

Name	Type	Required	Description
fiber_stash	FiberStash (full)	Yes	Fiber Stash

Example

/people/username/fiber/989.json { dye_lot": "43" }

fiber_attribute_groups

fiber_attribute_groups/list

GET /fiber_attribute_groups/list.json

Retrieve list of fiber attribute groups

Return Values

Name	Type	Required	Description
fiber_attribute_groups	Array, FiberAttributeGroup	Yes	All fiber attribute groups

Notes

Fiber attribute groups seldom change, I'd recommend caching them for up to 24 hours. This method does not require an API key.

Example

/fiber_attribute_groups.json

forum_posts

forum_posts/show authenticated

GET /forum_posts/{forum_post_id}.json

Get single forum post

URI Parameters

Name	Type	Required	Description
forum_post_id	Integer	Yes	Forum post to retrieve

Return Values

Name	Type	Required	Description
forum_post	ForumPost (full)	Yes	Forum post

forum_posts/unread

GET /forum_posts/unread.json

Get list of unread posts, across all forums

Parameters

Name	Type	Required	Description
include	Array, String		Extra result parts to include. Space delimited. Accepted options: vote_totals, user_votes

Name	Type	Required	Description
page	Integer		Result page to retrieve. Defaults to first page.
page_size	Integer		Page size. Defaults to 25.

Return Values

Name	Type	Required	Description
posts	Array, ForumPost (list)	Yes	List of posts
vote_totals	ForumMarkers		vote_totals are returned if they are requested with the "include" parameter
user_votes	Array, String		user_votes are returned if they are requested with the "include" parameter
paginator	Paginator	Yes	Pagination object with total results, pages, etc

Notes

this is being called too much

Example

/forum_posts/unread.json

forum_posts/update authenticated

POST /forum_posts/{forum_post_id}.json
Update a forum post

URI Parameters

Name	Type	Required	Description
forum_post_id	Integer	Yes	Forum post to update

Parameters

Name	Type	Required	Description
body	String	Yes	New forum post body

Return Values

Name	Type	Required	Description
forum_post	ForumPost (full)	Yes	Updated forum post

forum_posts/vote authenticated

GET /forum_posts/{forum_post_id}/vote.json
Update your vote on one of the forum post voting buttons

URI Parameters

Name	Type	Required	Description
forum_post_id	Integer	Yes	Forum post to vote on

Parameters

Name	Type	Required	Description
vote	Boolean	Yes	Your vote. Accepted values are 0 and 1: 1 to set your vote, 0 to clear it
type	String	Yes	Type of vote to cast. Accepted options: interesting, educational, funny, agree, disagree, love

Return Values

Name	Type	Required	Description
vote_totals	ForumMarkers	Yes	Totals (grouped by by type) of all votes on this post
user_votes	Array, String	Yes	List of the types that the current user has voted on

Notes

Note that voting is rate limited to prevent automated voting. Normal activity will not trigger it but if you provide features like "vote all" (which is discouraged), you will likely run into rate limiting.

Example

POST /forum_posts/1000/vote.json type=funny&vote=1

forums

forums/filtered_topics authenticated

GET /forums/filtered_topics.json
Filter topics across all forums/groups to find those that are relevant to the authenticated user

Parameters

Name	Type	Required	Description
status	String	Yes	One of: mine, reading, posting, watching, ignoring
sort	String		One of: started, replied, posts, topic. Defaults to "replied"
page	Integer	Yes	Result page to retrieve. Defaults to first page.
page_size	Integer	Yes	Defaults to 25, maximum is 100.

Return Values

Name	Type	Required	Description
topics	Array, Topic (list)	Yes	List of matching topics
paginator	Paginator	Yes	Pagination object with total results, pages, etc

Notes

This API call is analogous to the <https://www.ravelry.com/discuss/browse> page on Ravelry

Accepted statuses:

- mine: threads that the user has started
- reading: threads that the user has viewed
- posting: threads that the user has posted in
- watching: watched threads
- ignoring: ignored threads

Accepted sort orders. Ascending/descending and multiple selections are supported. See [Sorting and Pagination](#)

- started: time since the topic was started
- replied: time since the latest reply to the topic
- posts: number of posts in the topic
- topic: title of the topic

Example

/forums/filtered_topics.json?status=mine

forums/sets authenticated

GET /forums/sets.json

Get forum sets for current user (or default set)

Return Values

Name	Type	Required	Description
forum_sets	Array, ForumSet	Yes	Forum sets

Example

/forums/sets.json

forums/topics authenticated

GET /forums/{forum_id}/topics.json

Get topic list for a specific forum, personalize for the authenticated user

URI Parameters

Name	Type	Required	Description
forum_id	Integer	Yes	Forum to retrieve topics from

Parameters

Name	Type	Required	Description
page	Integer	Yes	Result page to retrieve. Defaults to first page.

Return Values

Name	Type	Required	Description
forum	Forum (list)	Yes	Selected forum
topics	Array, Topic (list)	Yes	List of topics
paginator	Paginator	Yes	Pagination object with total results, pages, etc

Example

/forums/3/topics.json

friends

friends/activity authenticated

GET /people/{username}/friends/activity.json
Retrieve recent friends' activity

URI Parameters

Name	Type	Required	Description
username	String	Yes	Friends will be selected from this user

Parameters

Name	Type	Required	Description
page	Integer		Result page to retrieve. Defaults to 1 (the first page).
page_size	Integer		Defaults to 25. Maximum size accepted = 50
activity_type_keys	String		Space delimited list of activity types. Currently accepted types: added-project-photo, added-stash-photo, queued-pattern, added-favorite, added-handspun-photo

Return Values

Name	Type	Required	Description
------	------	----------	-------------

Name	Type	Required	Description
activities	Array, Activity (list)	Yes	List of activity records
paginator	Paginator	Yes	Pagination object with total results, pages

Notes

A feed of friends' activity on Ravelry. This information is displayed on the "people" tab on the site as well as in the "Friends" section of users' Ravelry notebook. Note: activity that is older than 30 days is not available.

Example

GET /people/username/friends/activity.json?activity_type_keys=added-project-photo+added-stash-photo

friends/create authenticated

POST /people/{username}/friends/create.json
Add a friend

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the friendship record (ie. the currently logged in user)

Parameters

Name	Type	Required	Description
friend_user_id	Integer	Yes	User ID of the user who should be added as a friend

Return Values

Name	Type	Required	Description
friendship	Friendship (full)	Yes	The newly created friendship record

Example

POST /people/username/friends/create.json friend_user_id=1

friends/destroy authenticated

POST /people/{username}/friends/{id}/destroy.json
Delete a friendship record

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the friendship record (ie. the currently logged in user)

Name	Type	Required	Description
id	Integer	Yes	ID of the friendship record that should be deleted (not the user ID)

Return Values

Name	Type	Required	Description
friendship	Friendship (full)	Yes	The deleted friendship record

Example

POST /people/username/friends/42/destroy.json

friends/list authenticated

GET /people/{username}/friends/list.json
Get friend list

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to retrieve projects from

Return Values

Name	Type	Required	Description
collections	Array, Collection		Friend sets
friendships	Array, Friendship (list)	Yes	All friendships

Example

/people/username/friends/list.json

groups

groups/groups

GET /groups/search.json
Search the group directory

Parameters

Name	Type	Required	Description
query	String		Search term for fulltext searching
page	Integer		Result page to retrieve. Defaults to first page.
page_size	Integer		Defaults to 50 results per page.

Name	Type	Required	Description
sort	String		Sort order . Options are: best, added, favorites

Return Values

Name	Type	Required	Description
groups	Array, Group (list)	Yes	Matching groups
paginator	Paginator	Yes	Pagination object with total results, pages, etc

Notes

Note that you may also use any of the parameters for filters that are available in the on-site group search.

Example

```
/groups/search.json?query=wollmeise
```

in_store_sales

in_store_sales/add

POST /in_store_sales/carts/{id}/add.json

Add a product to a cart

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Cart ID

Parameters

Name	Type	Required	Description
product_id	Integer	Yes	Product ID. An error will be returned if this product is not available for sale.

Return Values

Name	Type	Required	Description
combined_cart	CombinedCart (full)	Yes	the newly updated cart

in_store_sales/add_by_pattern

POST /in_store_sales/carts/{id}/add_by_pattern.json

Add a product to a cart using a pattern ID of a related pattern.

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Cart ID

Parameters

Name	Type	Required	Description
pattern_id	Integer	Yes	Pattern ID. An error will be returned if the pattern is not associated with a single product or if the product is not available for sale.

Return Values

Name	Type	Required	Description
combined_cart	CombinedCart (full)	Yes	the newly updated cart

Notes

Note that this API method is only useful to retail shops who are participating in the In Store Sales program.

in_store_sales/checkout

POST /in_store_sales/carts/{id}/checkout.json

Checkout a cart. The wholesale price will be added to your monthly bill.

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Cart ID

Parameters

Name	Type	Required	Description
disable_email_notification	Boolean		Defaults to false (0) Set to 1 to prevent Ravelry from sending out a download receipt to the purchaser via email

Return Values

Name	Type	Required	Description
in_store_sales	Array, InStoreSale (receipt)	Yes	the completed sales records (including any digital deliveries)

Notes

This completes a purchase. The wholesale price will be added to your monthly bill. Note that this API method is only useful to retail shops who are participating in the In Store Sales program.

in_store_sales/create

POST /in_store_sales/carts/create.json

Create a new cart

Parameters

Name	Type	Required	Description
customer_name	String		
customer_email_address	String		Email address for email notification
customer_user_id	String		Ravelry user ID

Return Values

Name	Type	Required	Description
combined_cart	CombinedCart (full)	Yes	the newly created cart

Notes

At minimum, either customer_email address or customer_user_id must be supplied. Note that this API method is only useful to retail shops who are participating in the In Store Sales program.

in_store_sales/show

GET /in_store_sales/carts/{id}.json

View a previously created cart

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	

Return Values

Name	Type	Required	Description
combined_cart	CombinedCart (full)	Yes	the cart

Notes

Note that this API method is only useful to retail shops who are participating in the In Store Sales program.

languages

languages/languages

GET /languages/list.json
Retrieve list of available languages

Return Values

Name	Type	Required	Description
languages	Array, Language	Yes	All languages

Notes

Note that there is a special language - "Universal"/"Universal - no written language". The "universal" attribute will be set to true for this language.

Example

/languages/list.json

library

library/search authenticated

GET /people/{username}/library/search.json
Search a library

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to search

Parameters

Name	Type	Required	Description
query	String		Full text search string
query_type	String		One of "patterns" (to search pattern full text) or "tags" to search tags in queued items
type	String		Type of source. Accepted options: book, magazine, booklet, pattern, pdf
sort	String		Sort order . Accepted options: title, added, published, author. Multiple space-delimited options are accepted.
page	Integer		Result page to retrieve. Defaults to 1 (the first page).
page_size	Integer		Number of results per page. Defaults to 100

Return Values

Name	Type	Required	Description
paginator	Paginator	Yes	Pagination object with total results, pages

Name	Type	Required	Description
volumes	Array, Volume (list)	Yes	Matching volumes

Notes

Note that PDF patterns (type=pdf, Ravelry downloads) will only appear in search results if you are searching your own library.

Example

/people/username/library/search.json?type=book&query=Dogs

messages

messages/archive

POST /messages/{id}/archive.json
Archive a message

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Message ID to archive

Return Values

Name	Type	Required	Description
message	Message (full)	Yes	Message

Required permissions

[message-write](#)

Notes

Moves a message from "inbox" to the "saved" box

Example

/messages/22237804/archive.json

messages/create

POST /messages/create.json
Create and send a private message to another Ravelry user

Parameters

Name	Type	Required	Description
data	Message (POST)	Yes	Message JSON object

Return Values

Name	Type	Required	Description
message	Message (full)	Yes	The newly created message

Required permissions

[message-write](#)

Notes

Creates and immediately sends a message. Messages cannot be edited or changed after they are created. This method requires message-write permission This method will return a 403 status code with errors if either the sender or recipient has Ravelry messaging disabled in their profile.

messages/delete

DELETE /messages/{id}.json
Delete a message

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Message ID to delete

Return Values

Name	Type	Required	Description
message	Message (full)	Yes	Message

Required permissions

[message-write](#)

Example

DELETE /messages/22237804.json

messages/list authenticated

GET /messages/list.json

Get message list

Parameters

Name	Type	Required	Description
folder	String	Yes	Folder to list - one of: inbox, sent, archived
page	Integer		Result page to retrieve. Defaults to first page.
page_size	Integer		Size of result pages. Defaults to 100.
search	String		Search term for fulltext searching messages
unread_only	Boolean		Set to 1 to only return unread messages
output_format	String		Output format. Accepted options: list, full. Defaults to list (Message#list)
sort	String		Sort order . Accepted options: "time" (oldest first), "time_" (descending / newest first). Defaults to "time_"

Return Values

Name	Type	Required	Description
messages	Array, Message (list)	Yes	Messages
paginator	Paginator	Yes	Pagination object with total results, pages, etc

Notes

Smaller page sizes are recommended if you are using the "full" output format. It's not uncommon for users to have very large inboxes or even very large numbers messages that have been marked as unread.

Example

```
/messages/list.json?folder=inbox&format=full&unread_only=1&page_size=20
```

messages/mark_read authenticated

POST /messages/{id}/mark_read.json
Mark a message as read

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Message ID to mark

Return Values

Name	Type	Required	Description
message	Message (full)	Yes	Message

Example

/messages/22237804/mark_read.json

messages/mark_unread authenticated

POST /messages/{id}/mark_unread.json

Mark a message as unread

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Message ID to mark

Return Values

Name	Type	Required	Description
message	Message (full)	Yes	Message

Example

/messages/22237804/mark_unread.json

messages/reply

POST /messages/{id}/reply.json

Reply to a private message to another Ravelry user, same as create but links the messages together as a conversat

URI Parameters

Name	Type	Required	Description
id	Integer		ID of the message being replied to. Must be a message that has the current user listed as the recipient

Parameters

Name	Type	Required	Description
data	Message (POST)	Yes	Message JSON object

Return Values

Name	Type	Required	Description
message	Message (full)	Yes	The newly created message

Required permissions

[message-write](#)

Notes

Creates and immediately sends a message. Messages cannot be edited or changed after they are created. This method requires message-write permission This method will return a 403 status code with errors if either the sender or recipient has Ravelry messaging disabled in their profile.

messages/show authenticated

GET /messages/{id}.json

Get message

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Message ID to retrieve

Return Values

Name	Type	Required	Description
message	Message (full)	Yes	Message

Example

/messages/22237804.json

messages/unarchive

POST /messages/{id}/unarchive.json

Archive a message

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Message ID to unarchive

Return Values

Name	Type	Required	Description
message	Message (full)	Yes	Message

Required permissions

[message-write](#)

Notes

Moves a message from "saved" back to "inbox"

Example

/messages/22237804/unarchive.json

needles

needles/list authenticated

GET /people/{username}/needles/list.json
Get needle records

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to retrieve needles for

Return Values

Name	Type	Required	Description
needle_records	Array, NeedleRecord (full)	Yes	Needle records

needles/sizes authenticated

GET /needles/sizes.json
Get available sizes for each needle type

Parameters

Name	Type	Required	Description
craft	String		Type of tool to return. "crochet" for hooks only, "knitting" for knitting needles only. Default is empty (return both)

Return Values

Name	Type	Required	Description
needle_sizes	Array, NeedleSize (list)	Yes	Needle sizes

needles/types authenticated

GET /needles/types.json

Get needle types

Return Values

Name	Type	Required	Description
needle_type	Array, NeedleType (full)	Yes	Needle types

packs

packs/create authenticated

POST /packs/create.json
Create pack

Parameters

Name	Type	Required	Description
data	Pack (POST)	Yes	Pack JSON object

Return Values

Name	Type	Required	Description
pack	Pack (full)	Yes	Pack

packs/delete authenticated

DELETE /packs/{pack_id}.json
Delete pack

URI Parameters

Name	Type	Required	Description
pack_id	Integer	Yes	Pack to delete

Return Values

Name	Type	Required	Description
pack	Pack (full)	Yes	Pack that was deleted

packs/show authenticated

GET /packs/{pack_id}.json
Get single pack

URI Parameters

Name	Type	Required	Description
pack_id	Integer	Yes	Pack to retrieve

Return Values

Name	Type	Required	Description
pack	Pack (full)	Yes	Pack

packs/update authenticated

PUT /packs/{pack_id}.json
Update a pack

URI Parameters

Name	Type	Required	Description
pack_id	Integer	Yes	Pack to update

Parameters

Name	Type	Required	Description
data	Pack (POST)	Yes	Pack JSON object

Return Values

Name	Type	Required	Description
pack	Pack (full)	Yes	Pack

Notes

Packs must be associated with either a project or stash entry.

If your pack is associated with a stash entry because you want to tie a portion of that stash entry to a project, then **nearly all of the attributes are inherited from that stash entry. For these packs, you can set weights and lengths to record how much yarn is allocated to a project (total_length, total_weight) Units will match the stash's units.**

pages

pages/show authenticated

GET /pages/{id}.json
Get page

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Page to retrieve

Return Values

Name	Type	Required	Description
page	Page (full)	Yes	Page

Example

/pages/1.json

pages/update authenticated

POST /pages/{id}.json
Update page

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Page to update

Parameters

Name	Type	Required	Description
page.title	String	Yes	Page title
page.body	String	Yes	Page body

Return Values

Name	Type	Required	Description
page	Page (full)	Yes	Updated page

Example

/pages/1.json?name=page+title&body=page+body

pattern_attributes

pattern_attributes/list

GET /pattern_attributes/groups.json
List the current pattern attributes

Return Values

Name	Type	Required	Description
attribute_groups	Array, AttributeGroup (list)	Yes	List of all current pattern attributes, organized into groups that contain attributes and possibly sub-groups

Notes

Pattern attributes seldom change, I'd recommend caching them for up to 24 hours. This method does not require an API key.

pattern_categories

pattern_categories/list

GET /pattern_categories/list.json
List the current pattern categories

Return Values

Name	Type	Required	Description
pattern_categories	Array, PatternCategory (list)	Yes	List of all pattern categories

Notes

Pattern categories seldom change, I'd recommend caching them for up to 24 hours. This method does not require an API key.

pattern_source_types

pattern_source_types/list

GET /pattern_source_types/list.json
List the current pattern source types

Return Values

Name	Type	Required	Description
pattern_source_types	Array, PatternSourceType (list)	Yes	List of all pattern categories

Notes

Pattern source types seldom change. This method does not require an API key.

pattern_sources

pattern_sources/patterns authenticated

GET /pattern_sources/{id}/patterns.json
Get the set of patterns that a given source contains

URI Parameters

Name	Type	Required	Description
id	String	Yes	ID of the pattern source

Parameters

Name	Type	Required	Description
page	Integer	Yes	Result page to retrieve. Defaults to 1 (the first page).
page_size	Integer	Yes	Defaults to 50 results per page.

Return Values

Name	Type	Required	Description
patterns	Array, Pattern (source list)	Yes	List of patterns contained in this source
paginator	Paginator	Yes	Pagination object with total results, pages, etc

Notes

About 1% of pattern sources contain more than 50 patterns.

Example

/pattern_sources/1/patterns.json

pattern_sources/search

GET /pattern_sources/search.json
Search pattern source database

Parameters

Name	Type	Required	Description
query	String		Search term for fulltext searching patterns
page	Integer		Result page to retrieve. Defaults to first page.
page_number	Integer		Number of results to retrieve. Defaults to 100.

Return Values

Name	Type	Required	Description
pattern_sources	Array, PatternSource (list)	Yes	Matching pattern sources
paginator	Paginator	Yes	Pagination object with total results, pages, etc

Notes

Note that you may also use any of the (many) parameters for filters that are available in the on-site pattern search.

Example

/pattern_sources/search.json?isbn=978-0984572601

pattern_sources/show

GET /pattern_sources/{id}.json

Get pattern source details

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Pattern source to retrieve

Return Values

Name	Type	Required	Description
pattern_source	PatternSource (full)	Yes	

Example

/pattern_sources/573.json

patterns

patterns/comments

GET /patterns/{id}/comments.json

Retrieve a pattern's comments

Parameters

Name	Type	Required	Description
page	Integer		Result page to retrieve. Defaults to first page.
page_size	Integer		Defaults to 25 comments per page. Maximum is 100.
sort	String		Sort order . Options are: time, helpful (and time_, helpful_ for a descending sort)
include	Array, String		Extra result parts to include. Space delimited. Accepted options: highlighted_project

Return Values

Name	Type	Required	Description
comments	Array, Comment	Yes	Comments with nested replies.
paginator	Paginator	Yes	Pagination object with total results, pages, etc

Notes

Comments have one level of nesting. Replies from the owner of the pattern may be nested under the "replies" attribute.

patterns/create_photo authenticated

POST /patterns/{id}/create_photo.json

Add a photo to a pattern (using an uploaded image or URL as a source)

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Pattern ID

Parameters

Name	Type	Required	Description
image_id	Integer		Uploaded image to use, created via /upload/image.json
source_url	String		URL of the image to use (preferably high-res)

Return Values

Name	Type	Required	Description
status_token	String	Yes	Token that can be used to check the status of the photo

Required permissions

[pattern-write](#) OR [patternstore-write](#)

Notes

This method will create a new photo using one of two sources:

- If image_id is supplied, the photo will be created from an image that was uploaded via [/upload/image.json](#)
- If source_url is supplied, the source image will be retrieved from a URL

This method returns immediately. The image will be added to the pattern as a photo once it has been processed and resized into the various sizes used by Ravelry. Any size image is accepted. Ravelry will store the original or a 1600x1600 version (whichever is smaller) in addition to all of the necessary thumbnails.

Photo creation time varies depending on the size of the image. It should complete within a few seconds. If

you'd like to monitor the status of the process, you can use the `status_token` that is returned with `/photos/status.json`

patterns/highlights

GET `/patterns/highlights.json`

Get pattern highlights for the current user

Parameters

Name	Type	Required	Description
days	Integer	Yes	Number of days of highlights to retrieve. Default = 30 (ie. 30 days ago to present), maximum = 90

Return Values

Name	Type	Required	Description
timeline_entries	Object	Yes	Timeline entries contain a <code>timeline_date</code> (Date), pattern (Pattern#full), and explanatory reasons for inclusion.

Example

`/patterns/highlights.json`

patterns/patterns

GET `/patterns.json`

Get pattern details for multiple patterns

Parameters

Name	Type	Required	Description
ids	Integer	Yes	Space delimited list of pattern IDs to retrieve

Return Values

Name	Type	Required	Description
patterns	Object	Yes	Map of <code>'Pattern#full'</code> results, indexed by pattern ID

Example

`/patterns.json?ids=600+601`

patterns/projects

GET `/patterns/{id}/projects.json`

Retrieve the list of projects that are linked to this pattern

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	ID of the pattern

Parameters

Name	Type	Required	Description
query	String		Supply a query to optionally full text search inside of linked projects
sort	String		Sort order . Accepted options are: favorites", and "completed". Default is "completed".
photoless	Boolean		Set to "1" if want to return results that do not have a photo
page	Integer		Result page to retrieve. Defaults to 1 (the first page).
page_size	Integer	Yes	Number of results per page. Defaults to 100

Return Values

Name	Type	Required	Description
projects	Array, Project	Yes	List of projects that are linked to the pattern
paginator	Paginator	Yes	Pagination object with total results, pages

Notes

The default sort ("completed") is completion date, start date in descending order. If you supply a sort parameter, your selected sort will be applied before ordering by date. (For more complex sort/filter options see the *forthcoming* project search API)

Example

/patterns/573/projects.json

patterns/reorder_photos authenticated

POST /patterns/{id}/reorder_photos.json
Change order of associated photos

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Pattern pattern ID

Parameters

Name	Type	Required	Description
sort_order	String	Yes	List of photo IDs, space delimited

Return Values

Name	Type	Required	Description
photos	Array, Photo (full)	Yes	Set of photos with updated ordering

Required permissions

[pattern-write](#) OR [patternstore-write](#)

Notes

The first photo becomes the primary photo for the pattern

patterns/search

GET /patterns/search.json
Search pattern database

Parameters

Name	Type	Required	Description
query	String		Search term for fulltext searching patterns
page	Integer		Result page to retrieve. Defaults to first page.
page_size	Integer		Number of results to retrieve. Defaults to 100.
personal_attributes	Boolean		set to 1 if you would like to return the personal_attributes hash in the result objects

Return Values

Name	Type	Required	Description
patterns	Array, Pattern (list)	Yes	Matching patterns
paginator	Paginator	Yes	Pagination object with total results, pages, etc

Notes

Note that you may also use any of the (many) parameters for filters that are available in the on-site pattern search. To filter by a list of pattern IDs, use the pattern_id parameter with a pipe (|) delimited list of integer IDs.

Example

/patterns/search.json?query=cow1

patterns/show

GET /patterns/{id}.json

Get pattern details

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Pattern to retrieve

Return Values

Name	Type	Required	Description
patterns	Pattern (full)	Yes	

Notes

If you'd like to retrieve multiple patterns in one call, you can use `/patterns.json` to do that.

You can directly link to a pattern page with the "buy" box open (if the pattern has a product for sale) by constructing a URL like `"ravelry.com/patterns/library/permalink?buy=1"`. If it is known that the user has a Ravelry account, and you would like to force a login, also add `"guest_buy=0"` to the query parameters.

Example

`/patterns/573.json`

patterns/update

PUT `/patterns/{id}.json`
Update a pattern

URI Parameters

Name	Type	Required	Description
pattern_id	Integer	Yes	Pattern to update

Parameters

Name	Type	Required	Description
data	Pattern (POST)	Yes	Pattern JSON object

Return Values

Name	Type	Required	Description
pattern	Pattern (full)	Yes	Updated pattern

Required permissions

[pattern-write OR patternstore-write](#)

Notes

This method updates a pattern. Currently, a pattern can only be updated by the user who created it.

The required scopes (pattern-write or patternstore-write) are only available to whitelisted apps.

If validation errors occur, a 400 Bad Request will be returned along with the errors.

people

people/show authenticated

GET /people/{id}.json

Get user profile

URI Parameters

Name	Type	Required	Description
id	String	Yes	Username of user to lookup. Integer identifiers are also accepted.

Return Values

Name	Type	Required	Description
user	User (full)	Yes	User

Example

/people/bob.json

people/update authenticated

POST /people/{id}.json

Update user profile

URI Parameters

Name	Type	Required	Description
id	String	Yes	Username of user to update. Integer identifiers are also accepted.

Parameters

Name	Type	Required	Description
data	User (POST)	Yes	User JSON object

Return Values

Name	Type	Required	Description
user	User (full)	Yes	Newly updated user

Required permissions

[profile-write](#)

Example

```
/people/username/stash/96647.json { "about_me": "It's me, bob" }
```

photos

photos/delete authenticated

DELETE /photos/{id}.json
Delete photo

URI Parameters

Name	Type	Required	Description
id	String	Yes	Photo to delete

Return Values

Name	Type	Required	Description
photo	Photo (full)	Yes	Photo that was deleted

photos/dimensions authenticated

GET /photos/dimensions.json
Get photo thumbnail dimensions

URI Parameters

Name	Type	Required	Description
photo_id_list	String	Yes	Space delimited list of photo IDs to look up.

Return Values

Name	Type	Required	Description
dimensions	Object	Yes	Photo dimension information, with photo IDs as keys. See notes.

Notes

NOTE: if you only need the aspect ratio, that is already available in most Photo responses. Photo dimensions are not currently returned as part of `Photo` results. You can use this method to retrieve that information. For each photo looked up, the result will contain the height and width, width, and height for each size. The possible sizes that will be returned for each photo are:

- small : 240 px on the longest side
- small2: 320 px on the longest side
- medium: 500 px on the longest side
- medium2: 640 px on the longest side, may not be present for small photos

Example

/photos/dimensions.json?photo_id_list=42+43

photos/sizes authenticated

GET /photos/{id}/sizes.json
Get available photo sizes

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Photo to lookup

Return Values

Name	Type	Required	Description
photo	Photo (full)	Yes	Photo
sizes	Array, PhotoSize	Yes	Photo sizes

Notes

NOTE: /photos/dimensions.json will return very similar information and it can retrieve data for multiple photos at once. You may want to use that method instead. This method will be most useful when you are looking for the large size in order to zoom in on a photo. The possible size keys returned are:

- square : always 75x75
- thumbnail : 100 px on the longest side
- small : 240 px on the longest side
- medium: 500 px on the longest side
- medium2: 640 px on the longest side, optional
- large: 1000 - 1600 px on the longest side, optional

This method may be relatively slow (several tenths of a second) if the dimensions for a given photo have never been requested

Example

/photos/1/sizes.json

photos/status authenticated

GET /photos/status.json

Get the status of a photo creation that is in progress

Parameters

Name	Type	Required	Description
status_token	String	Yes	Status token that you received when creating the photo

Return Values

Name	Type	Required	Description
photo	Photo (full)	Yes	Photo, if the process is complete
progress	Integer	Yes	Current progress, from 1..100
complete	Boolean	Yes	true if the photo creation has completed
failed	Boolean	Yes	true if the photo creation was not possible (most common cause is an unsupported file type)

Example

/photos/status.json?status_token=foo

photos/update authenticated

POST /photos/{id}.json

Update photo attributes

URI Parameters

Name	Type	Required	Description
id	String	Yes	Photo ID

Parameters

Name	Type	Required	Description
x_offset	Integer		X offset for centered photo. See notes.
y_offset	Integer		Y offset for centered photo. See notes.
copyright_notice	String		Copyright line. See notes.
caption	String		

Return Values

Name	Type	Required	Description
photo	Photo (full)	Yes	Photo object, after updates have been applied

Notes

The offsets are used to place the Photo's small image (small_url) in a 170x170 pixel square frame. By default, they are calculated such that the photo is centered in this frame.

If you prefer a larger thumbnail, you can approximate the center within a few pixels by using the medium_url image and a 350 pixel frame and doubling the offsets.

The "copyright_notice" field is displayed in various places on Ravelry underneath the photo. It is not required, and it will normally be set to the member's username for stash and project photos.

The "caption" field is not currently displayed anywhere on Ravelry

product_attachments

product_attachments/delete authenticated

DELETE /product_attachments/{id}.json
Remove a product attachment from a product

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	ID of the product attachment that should be deleted

Return Values

Name	Type	Required	Description
product_attachment	ProductAttachment (full)	Yes	The deleted record

Notes

This method requires the [patternstore-write permission](#)

product_attachments/generate_download_link authenticated

POST /product_attachments/{id}/generate_download_link.json
Generate an expiring link that can be used to directly download the PDF associated with a product attachment

Parameters

Name	Type	Required	Description
------	------	----------	-------------

Name	Type	Required	Description
id	Integer	Yes	ID of the product attachment

Return Values

Name	Type	Required	Description
download_link	DownloadLink	Yes	

Notes

This method requires the [library-pdf permission](#) (for normal users) or the [patternstore-pdf permission](#) (for pattern sellers) Note that OAuth keys that include the library-pdf scope will expire much faster than usual. This method will return a 429 Too Many Requests if the user has exceeded their daily request limit for this method. The daily limit is currently set to 100 requests.

product_attachments/show authenticated

GET /product_attachments/{id}.json
Retrieve a product attachment

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	ID of the product attachment

Return Values

Name	Type	Required	Description
product_attachment	ProductAttachment (full)	Yes	The requested product attachment

Notes

This method requires the [patternstore-write permission](#)

product_attachments/update authenticated

POST /product_attachments/{id}.json
Update a product attachment

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	ID of the product attachment

Return Values

Name	Type	Required	Description
product_attachment	ProductAttachment (full)	Yes	The updated product attachment

Notes

This method requires the [patternstore-write permission](#)

product_attachments/upload authenticated

POST /product_attachments/upload.json
Upload a new product attachment

Parameters

Name	Type	Required	Description
product_id	Integer	Yes	ID of the product to which the attachment should be added
file	File	Yes	The PDF file to upload

Return Values

Name	Type	Required	Description
success	Boolean	Yes	Whether the upload was successful. See notes.

Notes

This method requires the [patternstore-write permission](#).

This is an "upload" method and should be implemented as multipart form post (multipart/form-data). A "product_id" parameter is required and the name of the file parameter should be "file".

Note: there is not currently a way to be notified of upload progress. However, you can poll the product and your new attachment will appear inside the product when it is ready (usually within seconds)

products

products/activate

POST /products/{id}.json
Activate a product (make it available for sale)

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Product ID

Return Values

Name	Type	Required	Description
product	Product (full)	Yes	Product

Notes

This method requires the [patternstore-write permission](#).

products/attachments

GET /products/{id}/attachments.json

Retrieve attached documents for this product

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Product ID

Return Values

Name	Type	Required	Description
product_attachments	Array, ProductAttachment	Yes	Attachments for this product

Notes

This method requires the [patternstore-read permission](#).

Example

/products/1970/attachments.json

products/create

POST /products/create.json

Create a new product

Parameters

Name	Type	Required	Description
store_id	Integer	Yes	Store ID for the store that will contain the new product
pattern_id	Integer		see notes
pattern_source_id	Integer		see notes
draft_pattern_id	Integer		see notes

Return Values

Name	Type	Required	Description
------	------	----------	-------------

Name	Type	Required	Description
product	Product (full)	Yes	Product

Notes

This method creates a new product stub based on the supplied draft pattern, pattern or pattern source. Only one of the three parameters should be supplied. Once created, the product can be updated with price info, attachments, and activated. This method requires the [patternstore-write permission](#).

products/deactivate

POST /products/{id}.json

Deactivate a product (make it unavailable for sale)

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Product ID

Return Values

Name	Type	Required	Description
product	Product (full)	Yes	Product

Notes

This method requires the [patternstore-write permission](#).

products/loveknitting/export authenticated

GET /products/loveknitting/export.json

Get loveknitting data for a product

Parameters

Name	Type	Required	Description
product_id_list	String	Yes	Space delimited list of product IDs to export

Return Values

Name	Type	Required	Description
products	Array, LoveknittingProduct (full)	Yes	List of objects containing oroduct and pattern attributes for loveknitting

Required permissions

products/loveknitting/update_status authenticated

POST /products/{id}/loveknitting/update_status.json

Update status of an associated loveknitting product

Parameters

Name	Type	Required	Description
product_id	Integer	Yes	Ravelry ID of product to update
loveknitting_identifier	String		ID of the product within loveknitting
pdf_id	String		The PDF ID from /products/loveknitting/export.json, if a provided PDF is being used on LK
price	String		current LK price of the product
currency	String		current LK currency of the product (always GBP at the moment)
status	String		One of: pending, approved, rejected, deleted, published, disabled

Return Values

Name	Type	Required	Description
success	Boolean	Yes	

Notes

The Loveknitting API key has permission to use this method. Current status codes are: * pending * approved * rejected * deleted

products/show

GET /products/{id}.json

Retrieve product information

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Product ID

Return Values

Name	Type	Required	Description
product	Product	Yes	Product

Notes

This method requires the [patternstore-read permission](#).

Example

/products/1970.json

products/update

POST /products/{id}.json

Update product information

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Product ID

Parameters

Name	Type	Required	Description
data	Product (POST)	Yes	Product JSON object

Return Values

Name	Type	Required	Description
product	Product (full)	Yes	Product

Notes

This method requires the [patternstore-write permission](#).

projects

projects/comments

GET /projects/{username}/{id}/comments.json

Retrieve a project's comments

Parameters

Name	Type	Required	Description
page	Integer		Result page to retrieve. Defaults to first page.
page_size	Integer		Defaults to 25 comments per page. Maximum is 100.
sort	String		Sort order . Options are: time (and time_ for a descending sort)

Return Values

Name	Type	Required	Description
------	------	----------	-------------

Name	Type	Required	Description
comments	Array, Comment	Yes	Comments with nested replies.
paginator	Paginator	Yes	Pagination object with total results, pages, etc

Notes

Comments have one level of nesting. Replies from the owner of the project may be nested under the "replies" attribute.

projects/crafts authenticated

POST /projects/crafts.json

Get list of crafts that are valid for use within projects

Return Values

Name	Type	Required	Description
crafts	Array, Craft (list)	Yes	List of crafts

projects/create authenticated

POST /projects/{username}/create.json

Create project

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to create a project for

Parameters

Name	Type	Required	Description
data	Project (POST)	Yes	Project JSON object

Return Values

Name	Type	Required	Description
project	Project (full)	Yes	Project

Notes

Packs can be added to a project only on creation. A pack is an allocation of yarn. If associated with a stash entry, you only need to (optionally) supply the "total_weight" and "total_length" attributes. The rest are inherited. To update or delete a pack, use the pack API methods.

projects/create_photo authenticated

POST /projects/{username}/{id}/create_photo.json

Add a photo to a project (using an uploaded image or URL as a source)

URI Parameters

Name	Type	Required	Description
username	String	Yes	Username of the user who owns the project
id	Integer	Yes	Project ID

Parameters

Name	Type	Required	Description
image_id	Integer		Uploaded image to use, created via /upload/image.json
source_url	String		URL of the image to use (preferably high-res)

Return Values

Name	Type	Required	Description
status_token	String	Yes	Token that can be used to check the status of the photo

Notes

This method will create a new photo using one of two sources:

- If image_id is supplied, the photo will be created from an image that was uploaded via [/upload/image.json](#)
- If source_url is supplied, the source image will be retrieved from a URL

This method returns immediately. The image will be added to the project as a photo once it has been processed and resized into the various sizes used by Ravelry. Any size image is accepted. Ravelry will store the original or a 1600x1600 version (whichever is smaller) in addition to all of the necessary thumbnails.

Photo creation time varies depending on the size of the image. It should complete within a few seconds. If you'd like to monitor the status of the process, you can use the status_token that is returned with /photos/status.json

projects/delete authenticated

DELETE /projects/{username}/{id}.json

Permanently delete a project

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the project
id	Integer	Yes	Project ID

Return Values

Name	Type	Required	Description
project	Project (full)	Yes	Project that was deleted

projects/list authenticated

GET /projects/{username}/list.json
Get project list

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to retrieve projects from

Parameters

Name	Type	Required	Description
sort	String		Sort order . Accepted options: status, name, created, started, favorites, happiness. Multiple space-delimited options are accepted.
include	Array, String		Extra result parts to include. Accepted options: collections
page	Integer		Result page to retrieve. Defaults to 1 (the first page).
page_size	Integer		Defaults to null (the entire result set in 1 page)

Return Values

Name	Type	Required	Description
collections	Array, Collection		Project sets
projects	Array, Project (small)	Yes	All projects
paginator	Paginator	Yes	Pagination object with total results, pages

Example

/projects/cassidy/list.json?include=collections

projects/project_statuses authenticated

POST /projects/project_statuses.json
Get list of statuses that are valid for use within projects

Return Values

Name	Type	Required	Description
project_statuses	Array, ProjectStatus (list)	Yes	List of project statuses

projects/reorder_photos authenticated

POST /projects/{username}/{id}/reorder_photos.json

Change order of associated photos

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the project
id	Integer	Yes	Project ID

Parameters

Name	Type	Required	Description
sort_order	String	Yes	List of photo IDs, space delimited

Return Values

Name	Type	Required	Description
photos	Array, Photo (full)	Yes	Set of project photos with updated ordering

Notes

The first photo becomes the primary photo for the project

projects/search

GET /projects/search.json

Search the project database

Parameters

Name	Type	Required	Description
query	String		Search term for fulltext searching
page	Integer		Result page to retrieve. Defaults to first page.
page_size	Integer		Defaults to 50 results per page.
sort	String		Sort order . Options are: best, started, completed, favorites, helpful, updated, happiness
include	Array, String		Extra result parts to include. Space delimited. Accepted options: notes, packs (see Pack)
personal_attributes	Boolean		set to 1 if you would like to return the personal_attributes hash in the result objects

Return Values

Name	Type	Required	Description
projects	Array, Project	Yes	Matching projects
paginator	Paginator	Yes	Pagination object with total results, pages, etc

Notes

Note that you may also use any of the (many) parameters for filters that are available in the on-site project search. For example, searching for the tags "red OR blue" would be tag-list=red|blue. Searching for the tags red AND blue would be tag-list=red blue

Example

/projects/search.json?query=dalek

projects/show authenticated

GET /projects/{username}/{id}.json

Get project detail

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to retrieve projects from
id	Integer	Yes	Project ID or permalink

Parameters

Name	Type	Required	Description
include	Array, String		Extra result parts to include. Accepted options: comments

Return Values

Name	Type	Required	Description
project	Project (full)	Yes	Project
comments	Array, Comment		Comments

Example

/projects/shadiradio/1.json?include=comments

projects/update authenticated

POST /projects/{username}/{id}.json

Update project

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to update a project for
id	Integer	Yes	Project ID

Parameters

Name	Type	Required	Description
data	Project (POST)	Yes	Project JSON object

Return Values

Name	Type	Required	Description
project	Project (full)	Yes	Project

Notes

Packs can be added to a project only on creation. A pack is an allocation of yarn. If associated with a stash entry, you only need to (optionally) supply the "total_weight" and "total_length" attributes. The rest are inherited. To update or delete a pack, use the pack API methods.

queue

queue/create authenticated

POST /people/{username}/queue/create.json
Create a queued project

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the queued project

Parameters

Name	Type	Required	Description
data	QueuedProject (POST)	Yes	Queued project JSON object

Return Values

Name	Type	Required	Description
queued_project	QueuedProject (full_for_owner)	Yes	The newly created queued project

Notes

A typical **minimal** queue entry would consist of a pattern_id (to link to a pattern in Ravelry) and a

sort_order (to position the item within the users' queue)

Example

```
/people/username/queue/create.json {"pattern_id": 42, "sort_order": 2 }
```

queue/delete authenticated

DELETE /people/{username}/queue/{queued_project_id}.json

Delete a queued project

URI Parameters

Name	Type	Required	Description
queued_project_id	Integer	Yes	Queued project to delete

Return Values

Name	Type	Required	Description
queued_project	QueuedProject (full)	Yes	Queued project that was deleted

queue/list authenticated

GET /people/{username}/queue/list.json

Get queued project list

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to retrieve queued projects from

Parameters

Name	Type	Required	Description
pattern_id	Integer		Pattern ID to filter for
query	String		Full text search query
query_type	String		One of "patterns" (to search pattern full text) or "tags" to search tags in queued items. Default is 'patterns'
page	Integer	Yes	Result page to retrieve. Defaults to 1 (the first page).
page_size	Integer	Yes	Defaults to 50 results per page.

Return Values

Name	Type	Required	Description
queued_projects	Array, QueuedProject (small)	Yes	All queued projects

Name	Type	Required	Description
paginator	Paginator	Yes	Pagination object with total results, pages, etc

Example

/people/username/queue/list.json

queue/order authenticated

GET /people/{username}/queue/order.json

Get queue ordering (list of all names, ids, and positions)

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to retrieve queued projects from

Return Values

Name	Type	Required	Description
queued_projects	Array, QueuedProject (tiny)	Yes	All queued projects

Example

/people/username/queue/order.json

queue/reposition authenticated

POST /people/{username}/queue/{id}/reposition.json

Move a queued project to a new position

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the queued project
id	Integer	Yes	ID of the queued project

Parameters

Name	Type	Required	Description
insert_at	Integer	Yes	New position for the queued project, range from 1 - (number of items in queue)

Return Values

Name	Type	Required	Description
------	------	----------	-------------

Name	Type	Required	Description
queued_project	QueuedProject (tiny)	Yes	The updated queued project

Example

/people/username/queue/1/reposition.json

queue/show authenticated

GET /people/{username}/queue/{id}.json
Get queued project detail

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to retrieve queued project from
id	String	Yes	Queued project ID

Return Values

Name	Type	Required	Description
queued_project	QueuedProject (full)	Yes	Queued project

Example

/people/username/queue/1.json

queue/update authenticated

POST /people/{username}/queue/{id}/update.json
Update a queued projectn

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the queued project

Parameters

Name	Type	Required	Description
data	QueuedProject (POST)	Yes	Queued project JSON object. Attributes that are not being changed can be omitted.

Return Values

Name	Type	Required	Description
------	------	----------	-------------

Name	Type	Required	Description
queued_project	QueuedProject (full_for_owner)	Yes	The newly updated queued project

Example

```
/people/username/queue/1/update.json {"notes": "Blah blah"}
```

saved_searches

saved_searches/list

GET /saved_searches/list.json

Get list of saved searches for the current user

Return Values

Name	Type	Required	Description
saved_searches	Array, SavedSearch (list)	Yes	

shops

shops/search

GET /shops/search.json

Search yarn shop database

Parameters

Name	Type	Required	Description
query	String		search query for full text search
shop_type_id	Integer		restrict shop type, 1 = Local Yarn Store
lat	Float		latitude for geographical search
lng	Float		longitude for geographical search
radius	Integer		radius for geographical search
units	String		units for geo search, "miles" or "km"
page	Integer		result page to retrieve. Defaults to 1 (the first page).
page_size	Integer		number of results per page. Defaults to 100

Return Values

Name	Type	Required	Description
shops	Array, Shop (small)	Yes	
paginator	Paginator	Yes	Pagination object with total results, pages

Notes

All parameters are optional. Set shop_type_id to 1 to filter out online stores and chains/craft stores such as Wal-Mart, Michael's. When using geographical search (search radius around a point), lat, lon, radius, and units are all required parameters. Geo search can also be combined with a search term.

Example

```
/shops/search.json?lat=42.35892&lng=-71.05781&radius=100&query=yarn
```

shops/show

GET /shops/{id}.json

Get shop details

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Shop to retrieve

Parameters

Name	Type	Required	Description
include	Array, String		Extra result parts to include. Accepted options: brands, ad, schedules, photo

Return Values

Name	Type	Required	Description
shop	Shop (medium)	Yes	
brands	Array, Brand	Yes	Brands purchased at the store (verified => false and yarns array empty) and advertised by the store (verified => true and yarns array filled)
ad	Ad (shop)	Yes	
schedules	Array, ShopSchedule (shop)	Yes	
photo	Photo (small)	Yes	

Example

```
/shops/2588.json?include=brands+ad
```

stash

stash/comments

GET /people/{username}/stash/{id}/comments.json

Retrieve a stashed yarn's comments

Parameters

Name	Type	Required	Description
page	Integer		Result page to retrieve. Defaults to first page.
page_size	Integer		Defaults to 25 comments per page. Maximum is 100.
sort	String		Sort order . Options are: time (and time_ for a descending sort)

Return Values

Name	Type	Required	Description
comments	Array, Comment	Yes	Comments with nested replies.
paginator	Paginator	Yes	Pagination object with total results, pages, etc

Notes

Comments have one level of nesting. Replies from the owner of the stashed yarn may be nested under the "replies" attribute.

stash/create authenticated

POST /people/{username}/stash/create.json

Create stash record

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to create stash for

Parameters

Name	Type	Required	Description
data	Stash (POST)	Yes	Stash JSON object

Return Values

Name	Type	Required	Description
stash	Stash (full)	Yes	Stash

Example

```
/people/username/stash/create.json { "yarn_id": 1, "dye_lot": 42 }
```

stash/create_photo authenticated

POST /people/{username}/stash/{id}/create_photo.json

Add a photo to a stashed yarn (using an uploaded image or URL as a source)

URI Parameters

Name	Type	Required	Description
username	String	Yes	Username of the user who owns the stash entry
id	String	Yes	Stash ID

Parameters

Name	Type	Required	Description
image_id	Integer		Uploaded image to use, created via /upload/image.json
source_url	String		URL of the image to use (preferably high-res)

Return Values

Name	Type	Required	Description
status_token	String	Yes	Token that can be used to check the status of the photo

Notes

See the [projects/create_photo](#) documentation for more information on how this works.

stash/delete authenticated

DELETE /people/{username}/stash/{id}.json

Permanently delete a stash entry

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the stash entry
id	Integer	Yes	Stash ID

Return Values

Name	Type	Required	Description
stash	Stash (full)	Yes	Stash that was deleted

stash/list authenticated

GET /people/{username}/stash/list.json

Get stash list

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to retrieve stash from

Parameters

Name	Type	Required	Description
page	Integer		If paging is desired, result page to retrieve. Defaults to 1 (the first page).
page_size	Integer		If paging is desired, number of results per page. Defaults to 50 results per page.
sort	String		Sort order . Should be one of: recent, alpha, weight, colorfamily, yards. Defaults to "alpha".

Return Values

Name	Type	Required	Description
stash	Array, Stash (small)	Yes	All stash

Example

/people/username/stash/list.json

stash/reorder_photos authenticated

POST /people/{username}/stash/{id}/reorder_photos.json
Change order of associated photos

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the stash entry
id	Integer	Yes	Stash ID

Parameters

Name	Type	Required	Description
sort_order	String	Yes	List of photo IDs, space delimited

Return Values

Name	Type	Required	Description
photos	Array, Photo (full)	Yes	Set of project photos with updated ordering

Notes

The first photo becomes the primary photo for the project

stash/search

GET /stash/search.json
Search the project database

Parameters

Name	Type	Required	Description
query	String		Search term for fulltext searching
page	Integer		Result page to retrieve. Defaults to first page.
page_size	Integer		Defaults to 50 results per page.
sort	String		Sort order . Options are: best, added, favorites
include	Array, String		Extra result parts to include. Space delimited. Accepted options: notes

Return Values

Name	Type	Required	Description
stashs	Array, Stash	Yes	Matching stashed yarns
paginator	Paginator	Yes	Pagination object with total results, pages, etc

Notes

Note that you may also use any of the (many) parameters for filters that are available in the on-site stash search.

Example

/stash/search.json?query=wollmeise

stash/show authenticated

GET /people/{username}/stash/{id}.json
Get stash list

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to retrieve stash from
id	Integer	Yes	Stash ID or permalink

Return Values

Name	Type	Required	Description
stash	Stash (full)	Yes	Stash
user	User (small)	Yes	User

Example

/people/username/stash/96647.json

stash/unified/list authenticated

GET /people/{username}/stash/unified/list.json

Get unified stash list that combines yarn stash with fiber stash

URI Parameters

Name	Type	Required	Description
username	String	Yes	User to retrieve stash from

Parameters

Name	Type	Required	Description
page	Integer		If paging is desired, result page to retrieve. Defaults to 1 (the first page).
page_size	Integer		If paging is desired, number of results per page. Defaults to 50 results per page.
sort	String		Sort by should be one of: recent, alpha, weight, colorfamily, grams. Defaults to "alpha".

Return Values

Name	Type	Required	Description
unified_stash	Array, UnifiedStash (list)	Yes	List of unified stash records, either {stash: [Stash#list object]} or {fiber_stash: [FiberStash#list object]}

Example

/people/username/stash/list.json

stash/update authenticated

POST /people/{username}/stash/{id}.json

Update a stash record

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns stash

Name	Type	Required	Description
id	Integer	Yes	Stash record to update

Parameters

Name	Type	Required	Description
data	Stash (POST)	Yes	Stash JSON object

Return Values

Name	Type	Required	Description
stash	Stash (full)	Yes	Stash

Example

```
/people/username/stash/96647.json { "location": "Under the bed" }
```

stores

stores/list

GET /stores/list.json

List the current user's pattern stores

Return Values

Name	Type	Required	Description
stores	Array, Store (list)	Yes	List of pattern stores that the current user administers

Required permissions

[patternstore-read](#) OR [patternstore-write](#)

Notes

This method requires patternstore-read permissions.

stores/products

GET /stores/{store_id}/products.json

List the products in a user's stores

Parameters

Name	Type	Required	Description
store_id	Integer	Yes	Pattern store to query

Name	Type	Required	Description
page	Integer		Result page to retrieve. Defaults to 1 (the first page).
page_size	Integer		Defaults to null (the entire result set in 1 page)

Return Values

Name	Type	Required	Description
products	Array, Product (list)	Yes	List of active products in the selected store

Required permissions

[patternstore-read](#) OR [patternstore-write](#)

Notes

This method requires patternstore-read permissions.

stores/purchases

GET /stores/:id/purchases.json
Export purchase (transaction) history

Parameters

Name	Type	Required	Description
store_id	Integer	Yes	Pattern store to query
creator	String		One of "all", ravelry-purchase", "lys-sale", or "lys-payment"
min_paid_date	Date		Minimum paid date stamp as RFC 3339 timestamp with offset: YYYY-MM-DDTHH:mm:ss±HH:MM
sort	String		Sort order . Options are: date, paid_date (and date_, paid_date_ for a descending sort)
month	String		Export mode: if a month is supplied, all invoices for that month will be returned with no pagination. The month that you want to retrieve in YYYY-MM-DD format (day will always be "01")
page	Integer		Result page to retrieve. Defaults to 1 (the first page).
page_size	Integer		Defaults to 100. Maximum size accepted = 250

Return Values

Name	Type	Required	Description
invoices	Array, Invoice (sale)	Yes	List of invoices that match the criteria
paginator	Paginator		Pagination object with total results, pages. Not returned if month parameter is supplied (export mode).

Required permissions

[patternstore-purchases](#)

Notes

This method requires patternstore-purchases permissions. The patternstore-purchases scope is **not** available to OAuth apps/keys

Explanation of creator options:

- all = exports every transaction
- ravelry-purchase = Ravelry sales only, LYS payments and sales are omitted
- lys-sale = LYS sales (from an LYS to the LYS customer)
- lys-payment = LYS payment (payments from an LYS to designer, for previously sold patterns)

topics

topics/create

POST /topics/create.json

Create a new topic

URI Parameters

Name	Type	Required	Description
forum_id	Integer	Yes	Forum that should contain the created topic

Parameters

Name	Type	Required	Description
title	String	Yes	Title of this topic. 250 character limit.
tag_list	String		List of tags, space delimited
body	String		Content for the (first) forum post that will kick off this topic
summary	String		Summary of this topic. Can only be set by a moderator.
sticky	Boolean		Sticky status, show at top of board. Defaults to false. Can only be set by a moderator.
locked	Boolean		Locked status, new posts can not be added. Defaults to false. Can only be set by a moderator.
archived	Boolean		Archived. Post appears in "archive" section of forum. Can only be set by a moderator.

Return Values

Name	Type	Required	Description
topic	Topic (full)	Yes	Newly created topic

Name	Type	Required	Description
forum_post	ForumPost (full)	Yes	Newly created forum post, the first post in the topic

Required permissions

[forum-write](#)

Notes

This method requires forum-write permissions.

topics/posts authenticated

GET /topics/{topic_id}/posts.json

Get post list for a specific forum, personalize for the authenticated user

URI Parameters

Name	Type	Required	Description
topic_id	Integer	Yes	Topic to retrieve posts from

Parameters

Name	Type	Required	Description
page	Integer		Result page to retrieve. Defaults to first page.
page_size	Integer		Page size. Defaults to 25.
sort_reverse	Boolean		Default sort is oldest posts first. Set to 1 to reverse sort order .
include	Array, String		Extra result parts to include. Space delimited. Accepted options: vote_totals, user_votes

Return Values

Name	Type	Required	Description
posts	Array, ForumPost (list)	Yes	List of posts
paginator	Paginator	Yes	Pagination object with total results, pages, etc
vote_totals	ForumMarkers		vote_totals are returned if they are requested with the "include" parameter
user_votes	Array, String		user_votes are returned if they are requested with the "include" parameter

Example

/topics/848/posts.json

topics/read authenticated

POST /topics/{topic_id}/read.json
Update read/unread marker for a specific topic

URI Parameters

Name	Type	Required	Description
topic_id	Integer	Yes	Topic to update

Parameters

Name	Type	Required	Description
last_read	Integer	Yes	Last read post number
force	optional	Yes	1 = Force setting last read, even if has decreased

Return Values

Name	Type	Required	Description
topic_status	TopicStatus	Yes	Topic status - last read/latest reply/etc

Notes

Note the "force" parameter - setting to 1 forces an update. By default, the last read marker will only be updated if it is earlier than the post number that you are trying to set. The number can be forced to an earlier number (normally 0) if the user wishes to clear their read marker or reset the number.

Example

/topics/1/read.json?last_read=1

topics/reply

POST /topics/{topic_id}/reply.json
Post a reply to a topic

URI Parameters

Name	Type	Required	Description
topic_id	Integer	Yes	Topic to reply to

Parameters

Name	Type	Required	Description
body	String	Yes	Forum post content
parent_post_id	Integer		If replying to a specific post, ID of post being replied to

Return Values

Name	Type	Required	Description
forum_post	ForumPost (full)	Yes	Newly created forum post

Required permissions

[forum-write](#)

Notes

This method requires forum-write permissions.

topics/show authenticated

GET /topics/{topic_id}.json
Get topic information

URI Parameters

Name	Type	Required	Description
topic_id	Integer	Yes	Topic to retrieve

Return Values

Name	Type	Required	Description
topic	Topic (full)	Yes	Topic

Example

/topics/848.json

topics/update

POST /topics/{id}.json
Update a topic

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Topic to update

Parameters

Name	Type	Required	Description
title	String	Yes	Title of this topic. 250 character limit.
tag_list	String		List of tags, space delimited
summary	String		Summary of this topic. Can only be set by a moderator.

Name	Type	Required	Description
sticky	Boolean		Sticky status, show at top of board. Defaults to false. Can only be set by a moderator.
locked	Boolean		Locked status, new posts can not be added. Defaults to false. Can only be set by a moderator.
archived	Boolean		Archived. Post appears in "archive" section of forum. Can only be set by a moderator.

Return Values

Name	Type	Required	Description
topic	Topic (full)	Yes	Newly updated topic

Required permissions

[forum-write](#)

Notes

Note that regular (non-moderator) users can only update information for an existing topic during the grace period (5 minutes after it has been created). The first forum post that started the topic can be updated independently using the forum posts API. This method requires forum-write permissions.

upload

upload/image

POST /upload/image.json

Upload an image file for later processing or attaching

Parameters

Name	Type	Required	Description
upload_token	String	Yes	Upload token received from upload/request_token
file0	Multipart	Yes	File data
file1	Multipart		File data, second file
file2	Multipart		File data, third file...
file9	Multipart		File data, tenth file

Return Values

Name	Type	Required	Description
uploads	Object	Yes	Object with result for each uploaded file. See notes.

Notes

Supported image formats: PNG, JPEG and HEIF/HEIC.

Note that this method is NOT authenticated. OAuth headers or other signatures are not needed. You must supply an `upload_token` that you received from a separate `/upload/request_token.json` API request. The upload token can only be used once.

This should be a multipart POST and up to 10 files can be included. This method will return immediately once your POST has completed.

The size of a single POST cannot exceed **50 MB**. If you try to POST more than 50 MB of data you will receive HTTP Error 413: Request entity too large

The result will include keys for each file parameter that you supplied, and each will contain an object with an "image_id". This "image_id" can be used when adding photos to projects, stash, etc.

Example response:

```
{uploads: [{file0: {image_id: 16}}, {file1: {image_id: 17}}, {file2: {image_id: 18}}]}
```

upload/request_token

POST /upload/request_token.json

Generate an upload token

Return Values

Name	Type	Required	Description
upload_token	String	Yes	

Notes

In order to upload files, you must first request an upload token that will be included when you POST your file data.

Example

/upload/request_token.json

upload/status

GET /upload/image/status.json

Get uploaded image IDs

Parameters

Name	Type	Required	Description
upload_token	String	Yes	Upload token received from upload/request_token

Return Values

Name	Type	Required	Description
uploads	Object	Yes	Object with result for each uploaded file. See notes.

Notes

This method might be useful if you POST to /upload/image.json with code that does not communicate with your client code.

See POST /upload/image.json for an example response.

volumes

volumes/apply_updates authenticated

POST /volumes/{id}/apply_updates.json

Apply any unapplied updates to a volume and any related volumes (in the case of a product with multiple PDF documents attached)

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Volume ID to apply updates to

Return Values

Name	Type	Required	Description
success	Boolean	Yes	returns true if updates were applied successfully
added_volumes	Array, Volume (full)	Yes	Any newly added volumes (documents)
removed_volumes	Array, Volume (full)	Yes	Any removed volumes (replaced or removed documents)

volumes/create authenticated

POST /volumes/create.json

Create a new volume (library entry) in the current user's library

Parameters

Name	Type	Required	Description
data	Volume (POST)	Yes	Volume JSON object. Note that pattern_id or pattern_source_id is required.

Return Values

Name	Type	Required	Description
volume	Volume (full)	Yes	Volume

Notes

If a free pattern that is available on Ravelry is added to the library, the associated PDFs will be included automatically.

Users should be encouraged to use the library for recording items that they own (and not for some other purpose) All patterns and sources can be added to the library, but adding single non-free patterns to the library without purchasing should be relatively rare.

Adding arbitrary items to the library is not yet supported. You can add by pattern ID or pattern source ID. If you have an ISBN, you can use the pattern source search to look for a matching source or sources.

volumes/delete authenticated

DELETE /volumes/{id}.json

Delete a volume

URI Parameters

Name	Type	Required	Description
username	String	Yes	User who owns the volume
id	Integer	Yes	Id of the volume that should be deleted

Return Values

Name	Type	Required	Description
volume	Volume (full)	Yes	The deleted record

volumes/show authenticated

GET /volumes/{id}.json

Get volume details

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Volume ID to retrieve

Return Values

Name	Type	Required	Description
volume	Volume (full)	Yes	Volume object

Example

/volumes/42.json

volumes/update authenticated

POST /volumes/{id}/update.json
Create a new volume (library entry)

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	ID of the volume to update

Parameters

Name	Type	Required	Description
data	Volume (POST)	Yes	Volume JSON object.

Return Values

Name	Type	Required	Description
volume	Volume (full)	Yes	Volume

Notes

The pattern or pattern source of a volume cannot be changed after creation.

yarn_attributes

yarn_attributes/list

GET /yarn_attributes/groups.json
List the current pattern attributes

Return Values

Name	Type	Required	Description
yarn_attribute_groups	Array, YarnAttributeGroup (list)	Yes	List of all current yarn attributes, organized into groups that contain attributes and possibly sub-groups

Notes

Yarn attributes seldom change, I'd recommend caching them for up to 24 hours. This method does not require an API key.

yarn_companies

yarn_companies/search

GET /yarn_companies/search.json

Search the yarn company directory

Parameters

Name	Type	Required	Description
query	String		Search term for fulltext searching
page	Integer		Result page to retrieve. Defaults to first page.
page_size	Integer		Defaults to 48 results per page.
sort	String		Sort order . Options are: "best" (defaults to "best")

Return Values

Name	Type	Required	Description
yarn_companies	Array, YarnCompany (list)	Yes	Matching yarn companies
paginator	Paginator	Yes	Pagination object with total results, pages, etc

Notes

Note that you may also use any of the parameters for filters that are available in the on-site yarn brand search.

Example

/yarn_companies/search.json?query=wollmeise

yarns

yarns/comments

GET /yarns/{id}/comments.json

Retrieve a yarns's comments

Parameters

Name	Type	Required	Description
page	Integer		Result page to retrieve. Defaults to first page.
page_size	Integer		Defaults to 25 comments per page. Maximum is 100.
sort	String		Sort order . Options are: time, helpful (and time_, helpful_ for a descending sort)
include	Array, String		Extra result parts to include. Space delimited. Accepted options: highlighted_project

Return Values

Name	Type	Required	Description
comments	Array, Comment	Yes	Comments with nested replies.
paginator	Paginator	Yes	Pagination object with total results, pages, etc

Notes

Comments have one level of nesting. Replies from the owner of the yarn may be nested under the "replies" attribute.

yarns/search

GET /yarns/search.json
Search yarn database

Parameters

Name	Type	Required	Description
query	String		Search term for fulltext searching yarns
page	Integer		Result page to retrieve. Defaults to first page.
page_size	Integer		Defaults to 50 results per page.
sort	String		Sort order . Options are: best, rating, projects
personal_attributes	Boolean		set to 1 if you would like to return the personal_attributes hash in the result objects

Return Values

Name	Type	Required	Description
yarns	Array, Yarn (list)	Yes	Matching yarns
paginator	Paginator	Yes	Pagination object with total results, pages, etc

Notes

Note that you may also use any of the (many) parameters for filters that are available in the on-site yarn search.

Example

/yarns/search.json?query=cascade

yarns/show

GET /yarns/{id}.json
Get yarn details

URI Parameters

Name	Type	Required	Description
id	Integer	Yes	Yarn to retrieve

Parameters

Name	Type	Required	Description
include	Array, String		Extra result parts to include. Space delimited. Accepted options: colorways, availability

Return Values

Name	Type	Required	Description
yarn	Yarn (full)	Yes	
colorways	Array, Colorway (full)		
availability	Array, YarnCountry (full)		Note that yarn availability-by-country data is not a user-maintained part of the database. The returned records provide advertiser and recent project/stash "purchased at" data.

Example

/yarns/573.json

yarns/yarns

GET /yarns.json
Get yarn details for multiple yarns

Parameters

Name	Type	Required	Description
ids	Integer	Yes	Space delimited list of yarn IDs to retrieve

Return Values

Name	Type	Required	Description
yarns	Object	Yes	Map of `Yarn#full` results, indexed by yarn ID

Example

/yarns.json?ids=600+601

Business

Business

Attributes

Name	Type	Nullable	Description
id			
name			
permalink			
primary_url			

Business (list)

Attributes

Name	Type	Nullable	Description
id			
name			
permalink			
primary_url			

FiberPack

FiberPack (full)

Attributes

Name	Type	Nullable	Description
id	Integer		

FiberPack (POST)

Attributes

Name	Type	Nullable	Description
color_family_id	Integer	Yes	
colorway	String	Yes	
fiber_stash_id	Integer		
personal_brand	String	Yes	
personal_name	String	Yes	
purchased_at	String	Yes	
purchased_city	String	Yes	
purchased_country_id	Integer	Yes	
purchased_state_id			
purchased_url	String	Yes	
shop_id	Integer	Yes	

Name	Type	Nullable	Description
spinning_project_id	String		

NeedleSize

NeedleSize (list)

Attributes

Name	Type	Nullable	Description
hook	String		Crochet hook designation corresponding to this metric size, if one exists
id	Integer		Needle size ID
metric	Integer		Metric designation for hook size
name			
pretty_metric			
us	String		US size number corresponding to this metric size, if one exists

NeedleSize (full)

Attributes

Name	Type	Nullable	Description
hook	String		Crochet hook designation corresponding to this metric size, if one exists
id	Integer		Needle size ID
metric	Integer		Metric designation for hook size
name			
pretty_metric			
us	String		US size number corresponding to this metric size, if one exists

NeedleSize (POST)

Attributes

Name	Type	Nullable	Description
metric	Integer		Metric designation for hook size

YarnWeight

YarnWeight

Attributes

Name	Type	Nullable	Description
------	------	----------	-------------

Name	Type	Nullable	Description
crochet_gauge			
id			
knit_gauge			
max_gauge			
min_gauge			
name			
ply			
wpi			

YarnWeight (list)

Attributes

Name	Type	Nullable	Description
crochet_gauge			
id			
knit_gauge			
max_gauge			
min_gauge			
name			
ply			
wpi			

PatternNeedleSize

PatternNeedleSize (list)

Attributes

Name	Type	Nullable	Description
hook			
id			
metric			
needle_name			
needle_size_id			
pretty_metric			
pretty_us			
us			

PatternNeedleSize (POST)

Attributes

Name	Type	Nullable	Description
hook			
id			
needle_size_id			

Language

Language

Attributes

Name	Type	Nullable	Description
code	String		2 character Language code (ISO 639-1)
id	Integer		Language ID
name	String		Language name
permalink	String		Permalink
short_name	String		Short language name
universal	Boolean		True if this is the "Universal" (no written language) language

Language (list)

Attributes

Name	Type	Nullable	Description
code	String		2 character Language code (ISO 639-1)
id	Integer		Language ID
name	String		Language name
permalink	String		Permalink
short_name	String		Short language name
universal	Boolean		True if this is the "Universal" (no written language) language

DraftPatternYarn

DraftPatternYarn (full)

Attributes

Name	Type	Nullable	Description
created_at	Date		
draft_pattern_id	Integer		draft pattern id
id	Integer		
updated_at	Date		
yarn	Yarn (list)		Yarn

Name	Type	Nullable	Description
yarn_id	Integer		yarn id
yarn_name			
yarn_weight	YarnWeight (list)		Yarn weight

DraftPatternYarn (POST)

Attributes

Name	Type	Nullable	Description
id	Integer		
yarn_id	Integer		yarn id

QueuedProject

QueuedProject (tiny)

Attributes

Name	Type	Nullable	Description
id	Integer		
position_in_queue	Integer		
short_pattern_name	String		

QueuedProject (small)

Attributes

Name	Type	Nullable	Description
best_photo	Photo		
created_at	Date		
id	Integer		
name	String		
notes			
pattern_author_id			
pattern_author_name			
pattern_id	String	Yes	ID of pattern to be used for this project
pattern_name	String		
position_in_queue	Integer		
short_pattern_name	String		
skeins	Integer	Yes	# of skeins needed
sort_order	Integer	Yes	Position in queue. Defaults to last.
user_id	Integer		

Name	Type	Nullable	Description
yarn_id	String	Yes	ID of yarn to be used in this project
yarn_name	String		

QueuedProject (full)

Attributes

Name	Type	Nullable	Description
best_photo	Photo		
created_at	Date		
id	Integer		
name	String		
notes_html	String		
notes			
pattern	Pattern (full)		
pattern_id	String	Yes	ID of pattern to be used for this project
pattern_name	String		
position_in_queue	Integer		
queued_stashes	Array, Stash (full)		
skeins	Integer	Yes	# of skeins needed
sort_order	Integer	Yes	Position in queue. Defaults to last.
user_id	Integer		
yarn	Yarn (full)		
yarn_id	String	Yes	ID of yarn to be used in this project
yarn_name	String		

QueuedProject (small_for_owner)

Attributes

Name	Type	Nullable	Description
best_photo	Photo		
created_at	Date		
finish_by			
id	Integer		
make_for	String	Yes	Note about who the project is for. Limited to 128 characters.
name	String		
notes			
pattern_author_id			
pattern_author_name			
pattern_id	String	Yes	ID of pattern to be used for this project
pattern_name	String		

Name	Type	Nullable	Description
position_in_queue	Integer		
short_pattern_name	String		
skeins	Integer	Yes	# of skeins needed
sort_order	Integer	Yes	Position in queue. Defaults to last.
start_on	Date	Yes	Date to start the project date, in YYYY-MM-DD format.
user_id	Integer		
yarn_id	String	Yes	ID of yarn to be used in this project
yarn_name	String		

QueuedProject (full_for_owner)

Attributes

Name	Type	Nullable	Description
best_photo	Photo		
created_at	Date		
finish_by			
id	Integer		
make_for	String	Yes	Note about who the project is for. Limited to 128 characters.
name	String		
notes_html	String		
notes			
pattern	Pattern (full)		
pattern_id	String	Yes	ID of pattern to be used for this project
pattern_name	String		
position_in_queue	Integer		
queued_stashes	Array, Stash (full)		
skeins	Integer	Yes	# of skeins needed
sort_order	Integer	Yes	Position in queue. Defaults to last.
start_on	Date	Yes	Date to start the project date, in YYYY-MM-DD format.
user_id	Integer		
yarn	Yarn (full)		
yarn_id	String	Yes	ID of yarn to be used in this project
yarn_name	String		

QueuedProject (export)

Attributes

Name	Type	Nullable	Description
best_photo	Photo		
created_at	Date		

Name	Type	Nullable	Description
finish_by			
id	Integer		
make_for	String	Yes	Note about who the project is for. Limited to 128 characters.
name	String		
notes_html	String		
notes			
pattern	Pattern (full)		
pattern_id	String	Yes	ID of pattern to be used for this project
pattern_name	String		
position_in_queue	Integer		
queued_stashes	Array, Stash (full)		
skeins	Integer	Yes	# of skeins needed
sort_order	Integer	Yes	Position in queue. Defaults to last.
start_on	Date	Yes	Date to start the project date, in YYYY-MM-DD format.
user_id	Integer		
yarn	Yarn (full)		
yarn_id	String	Yes	ID of yarn to be used in this project
yarn_name	String		

QueuedProject (POST)

Attributes

Name	Type	Nullable	Description
fiber_stash_ids	Array, Integer	Yes	List of IDs for Fiber stash records that are associated with this queued item.
finish_by	Date	Yes	Date to finish the project by, in YYYY-MM-DD format.
make_for	String	Yes	Note about who the project is for. Limited to 128 characters.
notes	String		
pattern_id	String	Yes	ID of pattern to be used for this project
personal_pattern_author	String	Yes	Pattern author, if a Ravelry pattern is not linked
personal_pattern_name	String	Yes	Pattern name, if a Ravelry pattern is not linked
personal_pattern_url	String	Yes	Pattern URL, if a Ravelry pattern is not linked
personal_yarn_name	String	Yes	Yarn name, if a Ravelry yarn is not linked
skeins	Integer	Yes	# of skeins needed
sort_order	Integer	Yes	Position in queue. Defaults to last.
sort_order	Integer	Yes	Position in queue. Defaults to last.
start_on	Date	Yes	Date to start the project date, in YYYY-MM-DD format.
stash_ids	Array, Integer	Yes	List of IDs for Stash records that are associated with this queued item.
tag_names	Array, String	Yes	Array of tag names

Name	Type	Nullable	Description
yarn_id	String	Yes	ID of yarn to be used in this project

PatternSource

PatternSource

Attributes

Name	Type	Nullable	Description
amazon_rating	Float	Yes	
amazon_url	String	Yes	
author	String	Yes	
id	Integer		
list_price	Decimal	Yes	
name	String		
out_of_print	Boolean		
patterns_count	Integer		
permalink	String		
price	Decimal	Yes	
shelf_image_path	String	Yes	
url			

PatternSource (link_with_patterns)

Attributes

Name	Type	Nullable	Description
id	Integer		
name	String		
pattern_source_type			
patterns	Array, Pattern (link)		
permalink	String		

PatternSource (list)

Attributes

Name	Type	Nullable	Description
amazon_rating	Float	Yes	
amazon_url	String	Yes	
author	String	Yes	
id	Integer		

Name	Type	Nullable	Description
list_price	Decimal	Yes	
name	String		
out_of_print	Boolean		
pattern_source_type			
pattern_source_type_id			
patterns_count	Integer		
permalink	String		
price	Decimal	Yes	
shelf_image_path	String	Yes	
url			

PatternSource (public)

Attributes

Name	Type	Nullable	Description
author	String	Yes	
author_pattern_author_id			
created_at			
id	Integer		
isbn_13			
issue			
label			
name	String		
notes_html			
notes			
out_of_print	Boolean		
pattern_source_type			
pattern_source_type_id			
periodical			
permalink	String		
price	Decimal	Yes	
publication_date			
publisher_id			
source_group_id			
updated_at			
url			

PatternSource (full)

Attributes

Name	Type	Nullable	Description
amazon_rating	Float	Yes	
amazon_url	String	Yes	
author	String	Yes	
id	Integer		
list_price	Decimal	Yes	
name	String		
out_of_print	Boolean		
pattern_source_type			
patterns	Array, Pattern		
patterns_count	Integer		
permalink	String		
price	Decimal	Yes	
shelf_image_path	String	Yes	
url			

DraftNeedleSize

DraftNeedleSize (full)

Attributes

Name	Type	Nullable	Description
draft_pattern_id	Integer		
hook	Boolean		Tool is a crochet hook (as opposed to a needle)
id	Integer		
needle_size	Array, NeedleSize (list)		Length, name, etc attributes come from the associated needle size record

DraftNeedleSize (POST)

Attributes

Name	Type	Nullable	Description
hook	Boolean		Tool is a crochet hook (as opposed to a needle)
id	Integer		
needle_size_id	Integer		

Invoice

Invoice (cart)

Attributes

Name	Type	Nullable	Description
id			
invoice_number	Integer		Invoice number
paid	Boolean		paid or unpaid
payment_reference	String	Yes	Custom field for storage of reference data by API users

Invoice (receipt)

Attributes

Name	Type	Nullable	Description
id			
invoice_number	Integer		Invoice number
paid	Boolean		paid or unpaid
payment_reference	String	Yes	Custom field for storage of reference data by API users

Invoice (sale)

Attributes

Name	Type	Nullable	Description
amount_due	Decimal	Yes	Amount due to the seller
amount_due_to_lys	Decimal	Yes	Amount due to the LYS (for In Store Sales)
bill_to_email	String	Yes	The email of the payer, as reported by PayPal
bill_to_name	String	Yes	The name of the payer, as reported by PayPal
country	String	Yes	Country of the buyer for tax purposes. Typically the same as country_from_paypal.
country_from_paypal	String	Yes	Country of the buyer as reported by PayPal
creator_type	Integer	Yes	Flag to mark special kinds of invoice records. 1 = (reserved), 2 = free/gifted copy, 3 = record of transaction between LYS and customer
currency	String		Currency (3 letter ISO code)
id			
invoice_date	Date		Date the invoice was created
invoice_line_items	Array, InvoiceLineItem (sale)		Products purchased and promotions applied
invoice_number	Integer		Invoice number
paid	Boolean		paid or unpaid
payment_reference	String	Yes	Custom field for storage of reference data by API users
payments	Array, Payment		Associated payments (from PayPal)
ravelry_user_id	Integer	Yes	User ID of the buyer's Ravelry account, ONLY PRESENT if the buyer was logged in to Ravelry at the time of purchase

Name	Type	Nullable	Description
ravelry_username	String	Yes	Username of the buyer's Ravelry account, ONLY PRESENT if the buyer was logged in to Ravelry at the time of purchase

Invoice

Attributes

Name	Type	Nullable	Description
bill_to_email	String	Yes	The email of the payer, as reported by PayPal
bill_to_name	String	Yes	The name of the payer, as reported by PayPal
currency	String		Currency (3 letter ISO code)
id			
invoice_date	Date		Date the invoice was created
invoice_number	Integer		Invoice number
paid	Boolean		paid or unpaid

Document

Document

Attributes

Name	Type	Nullable	Description
bytes	Integer		Size of the file in bytes
content_type	String		MIME content type of the file
filename	String		File name
id	Integer		Document ID
notes	String	Yes	Seller-added notes about the content of the file
thumbnail_url	String		URL for a thumbnail image of the attachment or the first page of the attachment

YarnProvenance

YarnProvenance

Attributes

Name	Type	Nullable	Description
country_id			
country_name			
description			

Name	Type	Nullable	Description
id	Integer		identifier
phase_name			
state_id			
yarn_id	Integer		yarn identifier
yarn_phase_id	Integer		yarn phase identifier

YarnProvenance (full)

Attributes

Name	Type	Nullable	Description
country_id			
country_name			
description			
id	Integer		identifier
phase_name			
state_id			
yarn_id	Integer		yarn identifier
yarn_phase_id	Integer		yarn phase identifier

Delivery

Delivery (list)

Attributes

Name	Type	Nullable	Description
created_at	Date		
emailed_at	Date		
id	Integer		Delivery ID
products	Array, Product		Products that were purchased or gifted

Delivery (receipt)

Attributes

Name	Type	Nullable	Description
delivery_url	String		URL where the customer can pick their downloads
emailed_at	Date		
id	Integer		Delivery ID

Name	Type	Nullable	Description
product_attachments	Array, ProductAttachment (receipt)		Details about the file attachments
scheduled_for_sending	Boolean		

PatternAttribute

PatternAttribute

Attributes

Name	Type	Nullable	Description
id	Integer		
permalink	String		

PatternAttribute (list)

Attributes

Name	Type	Nullable	Description
description	String		Long attribute description
id	Integer		
name	String		Attribute name
sort_order	Integer		Sort order within the containing attribute group. If not present, sorting alphabetically is recommended.

Tool

Tool

Attributes

Name	Type	Nullable	Description
created_at	Date		
id	Integer		
make	String	Yes	
model	String	Yes	
name	String	Yes	
notes	String	Yes	
updated_at	Date		

Tool (full)

Attributes

Name	Type	Nullable	Description
created_at	Date		
id	Integer		
make	String	Yes	
model	String	Yes	
name	String	Yes	
notes	String	Yes	
updated_at	Date		

Store

Store

Attributes

Name	Type	Nullable	Description
business	Business		The business (Pro Account) associated with the store
id	Integer		Store ID
name	String		Store name
pattern_source			
paypal_account	String		(deprecated) For stores that use the legacy non-Marketplaces PayPal connection, the associated account
permalink	String		Store permalink
products_count	Integer		Number of products in the store

Store (list)

Attributes

Name	Type	Nullable	Description
business	Business		The business (Pro Account) associated with the store
id	Integer		Store ID
name	String		Store name
pattern_source			
paypal_account	String		(deprecated) For stores that use the legacy non-Marketplaces PayPal connection, the associated account
permalink	String		Store permalink
products_count	Integer		Number of products in the store

CartItem

CartItem (javascript)

Attributes

Name	Type	Nullable	Description
cart_id	Integer		cart identifier
currency	String		3 character currency code
id	Integer		cart item identifier
product	Array, Product (javascript)		list of products

CartItem (full)

Attributes

Name	Type	Nullable	Description
cart_id	Integer		cart identifier
currency	String		3 character currency code
id	Integer		cart item identifier
product	Array, Product (full)		list of products

FiberCategory

FiberCategory

Attributes

Name	Type	Nullable	Description
id	Integer		
name	String		Short category name
parent			
permalink	String		

FiberCategory (list)

Attributes

Name	Type	Nullable	Description
children	Array, FiberCategory (list)		Child categories (subcategories)
id	Integer		
name	String		Short category name
permalink	String		
short_name	String		Abbreviated category name

Bundle

Bundle (list)

Attributes

Name	Type	Nullable	Description
bundle_cover	Photo	Yes	A cover photo uploaded by the user - this takes precedence over first_photo
bundled_items_count	Integer	Yes	
first_photo	Photo	Yes	A photo of a bundled item within the bundle
id	Integer		
name	String		
notes	String	Yes	
user	User (small)		User that is the Bundle owner

Bundle (full)

Attributes

Name	Type	Nullable	Description
bundle_cover	Photo	Yes	A cover photo uploaded by the user - this takes precedence over first_photo
bundled_items	Array, BundledItem (list)	Yes	list of the items in the bundle
bundled_items_count	Integer	Yes	
created_at	Date		
favorites_count	Integer	Yes	
first_photo	Photo	Yes	A photo of a bundled item within the bundle
id	Integer		
name	String		
notes	String	Yes	
permalink	String		
updated_at	Date		
user	User (small)		User that is the Bundle owner

Bundle (export)

Attributes

Name	Type	Nullable	Description
bundle_cover	Photo	Yes	A cover photo uploaded by the user - this takes precedence over first_photo
bundled_items	Array, BundledItem (list)	Yes	list of the items in the bundle

Name	Type	Nullable	Description
bundled_items_count	Integer	Yes	
created_at	Date		
favorites_count	Integer	Yes	
first_photo	Photo	Yes	A photo of a bundled item within the bundle
id	Integer		
name	String		
notes	String	Yes	
permalink	String		
updated_at	Date		

Bundle (POST)

Attributes

Name	Type	Nullable	Description
name	String		
notes	String	Yes	
owner_id	Integer	Yes	The ID of the bundle owner - only needed for PatternAuthor or Group owner_types
owner_id	Integer	Yes	The ID of the bundle owner - only needed for PatternAuthor or Group owner_types
owner_type	String	Yes	Who owns the bundle. Either designer or group for designer or group bundles. Leave blank for personal bundles.
owner_type	String	Yes	Who owns the bundle. Either designer or group for designer or group bundles. Leave blank for personal bundles.

ColorFamily

ColorFamily

Attributes

Name	Type	Nullable	Description
color	String	Yes	HTML color code
id	Integer		
name	String		
permalink	String		
spectrum_order	Integer		sort order , (mostly) based on the spectrum

DraftComponentYarn

DraftComponentYarn

Attributes

Name	Type	Nullable	Description
created_at	Date		
draft_pattern_id	Integer		
id	Integer		
updated_at	Date		

DraftComponentYarn (full)

Attributes

Name	Type	Nullable	Description
created_at	Date		
draft_pattern_id	Integer		
held_together_group	Integer		
id	Integer		
updated_at	Date		
yarn	Yarn (list)		
yarn_weight	YarnWeight (list)		

DraftComponentYarn (POST)

Attributes

Name	Type	Nullable	Description
yarn_weight_id	Integer		

Comment

Comment

Attributes

Name	Type	Nullable	Description
comment_html	String		Comment body (HTML formatted)
created_at	Date		Creation time
highlighted_project	Project	Yes	If the commenter has a project that is related to their comment, it is provided here. Note that you have to request this information as part of the comments API call.
id	Integer		Comment ID
user	User (small)		The user who posted the comment

Comment (history)

Attributes

Name	Type	Nullable	Description
comment_html	String		Comment body (HTML formatted)
commentable			
created_at	Date		Creation time
id	Integer		Comment ID
user_id	Integer		The ID of the user who posted the comment

Comment (full)

Attributes

Name	Type	Nullable	Description
comment_html	String		Comment body (HTML formatted)
created_at	Date		Creation time
highlighted_project	Project	Yes	If the commenter has a project that is related to their comment, it is provided here. Note that you have to request this information as part of the comments API call.
id	Integer		Comment ID
replies	Array, Comment		Replies to the comment. Only the owner of the item that has been commented on can reply, nesting is limited to 1 level (replies cannot have replies)
user	User (small)		The user who posted the comment

Comment (export)

Attributes

Name	Type	Nullable	Description
comment_html	String		Comment body (HTML formatted)
created_at	Date		Creation time
id	Integer		Comment ID

Volume

Volume (full)

Attributes

Name	Type	Nullable	Description
------	------	----------	-------------

Name	Type	Nullable	Description
asking_price_cents			
asking_price_currency	String	Yes	
author_name	String	Yes	
cover_image_size			
cover_image_url			
created_at	Date		Creation date
first_photo			
for_sale			
for_trade			
has_downloads			
id	Integer		
notes	String	Yes	Notes related to this item
notes_html			
pattern_id	Integer	Yes	The pattern that this volume is related to
pattern_source_id	Integer	Yes	The pattern source that this volume is related to
patterns_count	Integer	Yes	
small_image_url			
square_image_url			
title	String	Yes	
unapplied_updates	Array, ProductNotification	Yes	List of unapplied updates for this volume, if any
updated_at	Date		Last update date
volume_attachments	Array, VolumeAttachment	Yes	Documents (PDF files) that are attached to this volume
volume_status_id	Integer	Yes	One of: 1 (no special status), 2 (for sale), 3 (for trade), 4 (for sale or trade)

Volume (list)

Attributes

Name	Type	Nullable	Description
author_name	String	Yes	
cover_image_size			
cover_image_url			
created_at	Date		Creation date
first_photo			
has_downloads			
id	Integer		
pattern_id	Integer	Yes	The pattern that this volume is related to
pattern_source_id	Integer	Yes	The pattern source that this volume is related to
patterns_count	Integer	Yes	

Name	Type	Nullable	Description
small_image_url			
square_image_url			
title	String	Yes	
updated_at	Date		Last update date

Volume (export)

Attributes

Name	Type	Nullable	Description
author_name	String	Yes	
cover_image_size			
cover_image_url			
created_at	Date		Creation date
first_photo			
has_downloads			
id	Integer		
pattern_id	Integer	Yes	The pattern that this volume is related to
pattern_source_id	Integer	Yes	The pattern source that this volume is related to
patterns_count	Integer	Yes	
small_image_url			
square_image_url			
title	String	Yes	
updated_at	Date		Last update date

Volume (POST)

Attributes

Name	Type	Nullable	Description
asking_price	String	Yes	Asking price, if the item is for sale
asking_price_currency	String	Yes	
location	String	Yes	Location where the item is stored, only visible to the owner
notes	String	Yes	Notes related to this item
pattern_id	Integer	Yes	The pattern that this volume is related to
pattern_source_id	Integer	Yes	The pattern source that this volume is related to
volume_status_id	Integer	Yes	One of: 1 (no special status), 2 (for sale), 3 (for trade), 4 (for sale or trade)

Shop

Shop

Attributes

Name	Type	Nullable	Description
address			
city			
closed			
country			
distance			
facebook_page			
free_wifi			
id			
latitude			
location			
longitude			
name			
parking			
permalink			
phone			
pos_online			
ravelry_retailer			
seating			
shop_email			
state			
twitter_id			
url			
wheelchair_access			
zip			

Shop (tiny)

Attributes

Name	Type	Nullable	Description
id			
name			
permalink			

Shop (small)

Attributes

Name	Type	Nullable	Description
address			

Name	Type	Nullable	Description
city			
closed			
country			
distance			
facebook_page			
free_wifi			
id			
latitude			
location			
longitude			
name			
parking			
permalink			
phone			
pos_online			
ravelry_retailer			
seating			
shop_email			
state			
twitter_id			
url			
wheelchair_access			
zip			

Shop (medium)

Attributes

Name	Type	Nullable	Description
address			
city			
closed			
country			
distance			
facebook_page			
free_wifi			
id			
latitude			
location			
longitude			
name			

Name	Type	Nullable	Description
notes_html			
parking			
permalink			
phone			
pos_online			
ravelry_retailer			
seating			
shop_email			
state			
twitter_id			
url			
wheelchair_access			
yarn_brands			
zip			

Cart

Cart (javascript)

Attributes

Name	Type	Nullable	Description
cart_items	Array, CartItem (javascript)	Yes	list of items in the cart
currency	String		3 letter code for the currency of the cart
id	Integer		cart identifier
store_id	Integer		store identifier

Cart (full)

Attributes

Name	Type	Nullable	Description
cart_items	Array, CartItem (full)	Yes	list of items in the cart
currency	String		3 letter code for the currency of the cart
id	Integer		cart identifier
store_id	Integer		store identifier

DownloadLink

DownloadLink

Attributes

Name	Type	Nullable	Description
activated_at			
expires_at			
url			

Stash

Stash

Attributes

Name	Type	Nullable	Description
color_family_name			
colorway_name			
comments_count	Integer		
created_at	Date		
dye_lot	String	Yes	
favorites_count	Integer		
first_photo	Photo		
handspun	Boolean		
has_photo	Boolean	Yes	
id	Integer		
location	String	Yes	Description of where the stashed yarn is stored
long_yarn_weight_name	String		Longer description of the yarn's weight. personal_yarn_weight is used if there is no associated yarn
name	String	Yes	User-added yarn name, typically present when there is no associated yarn
permalink	String		
personal_yarn_weight	YarnWeight	Yes	User-added yarn weight, typically present when there is no associated yarn
stash_status			
tag_names	Array, String		List of tags associated with this stash entry
updated_at	Date		
user	User (small)		User that is the Stash owner
yarn	Yarn (stash_list)		
yarn_weight_name	String		Name of the yarn's weight. personal_yarn_weight is used if there is no associated yarn

Stash (small)

Attributes

Name	Type	Nullable	Description
color_family_name			
colorway_name			
comments_count	Integer		
created_at	Date		
dye_lot	String	Yes	
favorites_count	Integer		
first_photo	Photo		
handspun	Boolean		
has_photo	Boolean	Yes	
id	Integer		
location	String	Yes	Description of where the stashed yarn is stored
name	String	Yes	User-added yarn name, typically present when there is no associated yarn
permalink	String		
stash_status			
tag_names	Array, String		List of tags associated with this stash entry
updated_at	Date		
yarn	Yarn (stash_list)		

Stash (list)

Attributes

Name	Type	Nullable	Description
color_family_name			
colorway_name			
comments_count	Integer		
created_at	Date		
dye_lot	String	Yes	
favorites_count	Integer		
first_photo	Photo		
handspun	Boolean		
has_photo	Boolean	Yes	
id	Integer		
location	String	Yes	Description of where the stashed yarn is stored
long_yarn_weight_name	String		Longer description of the yarn's weight. personal_yarn_weight is used if there is no associated yarn
name	String	Yes	User-added yarn name, typically present when there is no associated yarn
permalink	String		

Name	Type	Nullable	Description
personal_yarn_weight	YarnWeight	Yes	User-added yarn weight, typically present when there is no associated yarn
primary_pack	(stash)		
stash_status			
tag_names	Array, String		List of tags associated with this stash entry
updated_at	Date		
user	User (small)		User that is the Stash owner
yarn	Yarn (stash list)		
yarn_weight_name	String		Name of the yarn's weight. personal_yarn_weight is used if there is no associated yarn

Stash (list_with_notes)

Attributes

Name	Type	Nullable	Description
color_family_name			
colorway_name			
comments_count	Integer		
created_at	Date		
dye_lot	String	Yes	
favorites_count	Integer		
first_photo	Photo		
handspun	Boolean		
has_photo	Boolean	Yes	
id	Integer		
location	String	Yes	Description of where the stashed yarn is stored
long_yarn_weight_name	String		Longer description of the yarn's weight. personal_yarn_weight is used if there is no associated yarn
name	String	Yes	User-added yarn name, typically present when there is no associated yarn
notes_html			
notes			
permalink	String		
personal_yarn_weight	YarnWeight	Yes	User-added yarn weight, typically present when there is no associated yarn
primary_pack	(stash)		
stash_status			
tag_names	Array, String		List of tags associated with this stash entry
updated_at	Date		
user	User (small)		User that is the Stash owner

Name	Type	Nullable	Description
yarn	Yarn (stash_list)		
yarn_weight_name	String		Name of the yarn's weight. personal_yarn_weight is used if there is no associated yarn

Stash (full)

Attributes

Name	Type	Nullable	Description
color_family_name			
colorway_name			
comments_count	Integer		
created_at	Date		
dye_lot	String	Yes	
favorites_count	Integer		
handspun	Boolean		
has_photo	Boolean	Yes	
id	Integer		
location	String	Yes	Description of where the stashed yarn is stored
long_yarn_weight_name	String		Longer description of the yarn's weight. personal_yarn_weight is used if there is no associated yarn
name	String	Yes	User-added yarn name, typically present when there is no associated yarn
name	String	Yes	User-added yarn name, typically present when there is no associated yarn
notes_html			
notes			
packs	(stash)		
permalink	String		
personal_yarn_weight	YarnWeight	Yes	User-added yarn weight, typically present when there is no associated yarn
photos	(full)		
stash_status			
tag_names	Array, String		List of tags associated with this stash entry
updated_at	Date		
user	User (small)		User that is the Stash owner
user_id			
yarn	Yarn (full)		
yarn_weight_name	String		Name of the yarn's weight. personal_yarn_weight is used if there is no associated yarn

Stash (full_for_owner)

Attributes

Name	Type	Nullable	Description
color_family_name			
colorway_name			
comments_count	Integer		
created_at	Date		
dye_lot	String	Yes	
favorites_count	Integer		
handspun	Boolean		
has_photo	Boolean	Yes	
id	Integer		
location	String	Yes	Description of where the stashed yarn is stored
long_yarn_weight_name	String		Longer description of the yarn's weight. personal_yarn_weight is used if there is no associated yarn
name	String	Yes	User-added yarn name, typically present when there is no associated yarn
name	String	Yes	User-added yarn name, typically present when there is no associated yarn
notes_html			
notes			
packs	(stash_for_owner)		
permalink	String		
personal_yarn_weight	YarnWeight	Yes	User-added yarn weight, typically present when there is no associated yarn
photos	(full)		
stash_status			
tag_names	Array, String		List of tags associated with this stash entry
updated_at	Date		
user	User (small)		User that is the Stash owner
user_id			
yarn	Yarn (full)		
yarn_weight_name	String		Name of the yarn's weight. personal_yarn_weight is used if there is no associated yarn

Stash (export)

Attributes

Name	Type	Nullable	Description
color_family_name			

Name	Type	Nullable	Description
colorway_name			
comments_count	Integer		
created_at	Date		
dye_lot	String	Yes	
favorites_count	Integer		
handspun	Boolean		
has_photo	Boolean	Yes	
id	Integer		
location	String	Yes	Description of where the stashed yarn is stored
long_yarn_weight_name	String		Longer description of the yarn's weight. personal_yarn_weight is used if there is no associated yarn
name	String	Yes	User-added yarn name, typically present when there is no associated yarn
name	String	Yes	User-added yarn name, typically present when there is no associated yarn
notes_html			
notes			
packs	(stash)		
permalink	String		
personal_yarn_weight	YarnWeight	Yes	User-added yarn weight, typically present when there is no associated yarn
photos	(full)		
stash_status			
tag_names	Array, String		List of tags associated with this stash entry
updated_at	Date		
user_id			
yarn	Yarn (full)		
yarn_weight_name	String		Name of the yarn's weight. personal_yarn_weight is used if there is no associated yarn

Stash (POST)

Attributes

Name	Type	Nullable	Description
dye_lot	String	Yes	
handspun	Boolean		
location	String	Yes	Description of where the stashed yarn is stored
notes			
pack	Pack (POST)	Yes	The pack record contains detailed information about an allocation of yarn

Name	Type	Nullable	Description
stash_status_id	Integer		1 = active, 2 = used up, 3 = will trade/sell, 4 = gone/sold, 5 = in progress (only available on handspun)
tag_list	String	Yes	List of tags, space delimited
yarn_id	Integer	Yes	Yarn to link the stash entry to

Forum

Forum (small)

Attributes

Name	Type	Nullable	Description
id	Integer		
name	String		
permalink	String		
sort_order	Integer		
topics_count	Integer		

Forum (list)

Attributes

Name	Type	Nullable	Description
id	Integer		
name	String		
permalink	String		
sort_order	Integer		
topics_count	Integer		

Project

Project

Attributes

Name	Type	Nullable	Description
comments_count	Integer		
completed	Date	Yes	
completed_day_set	Boolean		If set to false, the "completed" date day is unknown. It represents a month and year only
craft_id	Integer	Yes	
craft_name			

Name	Type	Nullable	Description
created_at	Date		
ends_per_inch	Decimal	Yes	
favorites_count	Integer		
first_photo	Photo	Yes	
gauge_divisor	Integer	Yes	
gauge	Decimal	Yes	
gauge_pattern	String	Yes	
gauge_repeats	Integer	Yes	
id	Integer		
links	Object		Links to the project on Ravelry
made_for	String	Yes	
made_for_user_id	Integer	Yes	
name	String		
pattern_id	Integer	Yes	A project might have a pattern name and no pattern ID (if it is not linked to a Ravelry database pattern)
pattern_name	String	Yes	
permalink	String		
personal_attributes	Hash	Yes	Hash containing information related to this project's status in the current user's notebook (favorited, bookmark_id, ...)
photos_count	Integer		
picks_per_inch	Decimal	Yes	
progress	Integer	Yes	
project_status_changed			
project_status_id	Integer	Yes	
rating	Integer	Yes	
row_gauge	Decimal	Yes	
size	String	Yes	
started	Date	Yes	
started_day_set	Boolean		If set to false, the "started" date day is unknown. It represents a month and year only
status_name	String	Yes	
tag_names	Array	Yes	Array of tags (tags cannot contain commas)
updated_at	Date		
user	User (small)		User that is the Project owner
user_id			

Project (notes)

Attributes

Name	Type	Nullable	Description
------	------	----------	-------------

Name	Type	Nullable	Description
comments_count	Integer		
completed	Date	Yes	
completed_day_set	Boolean		If set to false, the "completed" date day is unknown. It represents a month and year only
craft_id	Integer	Yes	
craft_name			
created_at	Date		
ends_per_inch	Decimal	Yes	
favorites_count	Integer		
first_photo	Photo	Yes	
gauge_divisor	Integer	Yes	
gauge	Decimal	Yes	
gauge_pattern	String	Yes	
gauge_repeats	Integer	Yes	
id	Integer		
links	Object		Links to the project on Ravelry
made_for	String	Yes	
made_for_user_id	Integer	Yes	
name	String		
notes_html	String	Yes	Public project notes
notes	String	Yes	Public project notes, raw markdown before rendering as HTML and sanitizing
pattern_id	Integer	Yes	A project might have a pattern name and no pattern ID (if it is not linked to a Ravelry database pattern)
pattern_name	String	Yes	
permalink	String		
personal_attributes	Hash	Yes	Hash containing information related to this project's status in the current user's notebook (favorited, bookmark_id, ...)
photos_count	Integer		
picks_per_inch	Decimal	Yes	
progress	Integer	Yes	
project_status_changed			
project_status_id	Integer	Yes	
rating	Integer	Yes	
row_gauge	Decimal	Yes	
size	String	Yes	
started	Date	Yes	
started_day_set	Boolean		If set to false, the "started" date day is unknown. It represents a month and year only
status_name	String	Yes	
tag_names	Array	Yes	Array of tags (tags cannot contain commas)
updated_at	Date		

Name	Type	Nullable	Description
user	User (small)		User that is the Project owner
user_id			

Project (list_with_packs)

Attributes

Name	Type	Nullable	Description
comments_count	Integer		
completed	Date	Yes	
completed_day_set	Boolean		If set to false, the "completed" date day is unknown. It represents a month and year only
craft_id	Integer	Yes	
craft_name			
created_at	Date		
ends_per_inch	Decimal	Yes	
favorites_count	Integer		
first_photo	Photo	Yes	
gauge_divisor	Integer	Yes	
gauge	Decimal	Yes	
gauge_pattern	String	Yes	
gauge_repeats	Integer	Yes	
id	Integer		
links	Object		Links to the project on Ravelry
made_for	String	Yes	
made_for_user_id	Integer	Yes	
name	String		
notes_html	String	Yes	Public project notes
notes	String	Yes	Public project notes, raw markdown before rendering as HTML and sanitizing
packs	Pack (full)	Yes	Array of pack records containing detailed information about an allocation of yarn. Only allowed on project creation. For updating or deleting use the pack API methods.
pattern_id	Integer	Yes	A project might have a pattern name and no pattern ID (if it is not linked to a Ravelry database pattern)
pattern_name	String	Yes	
permalink	String		
personal_attributes	Hash	Yes	Hash containing information related to this project's status in the current user's notebook (favorited, bookmark_id, ...)
photos_count	Integer		
picks_per_inch	Decimal	Yes	
progress	Integer	Yes	

Name	Type	Nullable	Description
project_status_changed			
project_status_id	Integer	Yes	
rating	Integer	Yes	
row_gauge	Decimal	Yes	
size	String	Yes	
started	Date	Yes	
started_day_set	Boolean		If set to false, the "started" date day is unknown. It represents a month and year only
status_name	String	Yes	
tag_names	Array	Yes	Array of tags (tags cannot contain commas)
updated_at	Date		
user	User (small)		User that is the Project owner
user_id			

Project (small)

Attributes

Name	Type	Nullable	Description
comments_count	Integer		
completed	Date	Yes	
completed_day_set	Boolean		If set to false, the "completed" date day is unknown. It represents a month and year only
craft_id	Integer	Yes	
craft_name			
created_at	Date		
ends_per_inch	Decimal	Yes	
favorites_count	Integer		
first_photo	Photo	Yes	
gauge_divisor	Integer	Yes	
gauge	Decimal	Yes	
gauge_pattern	String	Yes	
gauge_repeats	Integer	Yes	
id	Integer		
links	Object		Links to the project on Ravelry
made_for	String	Yes	
made_for_user_id	Integer	Yes	
name	String		
pattern_id	Integer	Yes	A project might have a pattern name and no pattern ID (if it is not linked to a Ravelry database pattern)
pattern_name	String	Yes	

Name	Type	Nullable	Description
permalink	String		
photos_count	Integer		
picks_per_inch	Decimal	Yes	
progress	Integer	Yes	
project_status_changed			
project_status_id	Integer	Yes	
rating	Integer	Yes	
row_gauge	Decimal	Yes	
size	String	Yes	
started	Date	Yes	
started_day_set	Boolean		If set to false, the "started" date day is unknown. It represents a month and year only
status_name	String	Yes	
tag_names	Array	Yes	Array of tags (tags cannot contain commas)
updated_at	Date		
user_id			

Project (full)

Attributes

Name	Type	Nullable	Description
comments_count	Integer		
completed	Date	Yes	
completed_day_set	Boolean		If set to false, the "completed" date day is unknown. It represents a month and year only
craft_id	Integer	Yes	
craft_name			
created_at	Date		
ends_per_inch	Decimal	Yes	
favorites_count	Integer		
gauge_divisor	Integer	Yes	
gauge	Decimal	Yes	
gauge_pattern	String	Yes	
gauge_repeats	Integer	Yes	
id	Integer		
links	Object		Links to the project on Ravelry
made_for	String	Yes	
made_for_user_id	Integer	Yes	
name	String		
needle_sizes			
notes_html	String	Yes	Public project notes

Name	Type	Nullable	Description
notes	String	Yes	Public project notes, raw markdown before rendering as HTML and sanitizing
packs	Pack (full)	Yes	Array of pack records containing detailed information about an allocation of yarn. Only allowed on project creation. For updating or deleting use the pack API methods.
pattern_id	Integer	Yes	A project might have a pattern name and no pattern ID (if it is not linked to a Ravelry database pattern)
pattern_name	String	Yes	
permalink	String		
personal_attributes	Hash	Yes	Hash containing information related to this project's status in the current user's notebook (favorited, bookmark_id, ...)
photos	(full)		
photos_count	Integer		
picks_per_inch	Decimal	Yes	
progress	Integer	Yes	
project_status_changed			
project_status_id	Integer	Yes	
rating	Integer	Yes	
row_gauge	Decimal	Yes	
size	String	Yes	
started	Date	Yes	
started_day_set	Boolean		If set to false, the "started" date day is unknown. It represents a month and year only
status_name	String	Yes	
tag_names	Array (full)	Yes	Array of tags (tags cannot contain commas)
tools			
updated_at	Date		
user	User (small)		User that is the Project owner
user_id			

Project (full_for_owner)

Attributes

Name	Type	Nullable	Description
comments_count	Integer		
completed	Date	Yes	
completed_day_set	Boolean		If set to false, the "completed" date day is unknown. It represents a month and year only
craft_id	Integer	Yes	
craft_name			
created_at	Date		

Name	Type	Nullable	Description
ends_per_inch	Decimal	Yes	
favorites_count	Integer		
gauge_divisor	Integer	Yes	
gauge	Decimal	Yes	
gauge_pattern	String	Yes	
gauge_repeats	Integer	Yes	
id	Integer		
links	Object		Links to the project on Ravelry
made_for	String	Yes	
made_for_user_id	Integer	Yes	
name	String		
needle_sizes			
notes_html	String	Yes	Public project notes
notes	String	Yes	Public project notes, raw markdown before rendering as HTML and sanitizing
packs	Pack (full for owner)	Yes	Array of pack records containing detailed information about an allocation of yarn. Only allowed on project creation. For updating or deleting use the pack API methods.
pattern_id	Integer	Yes	A project might have a pattern name and no pattern ID (if it is not linked to a Ravelry database pattern)
pattern_name	String	Yes	
permalink	String		
personal_attributes	Hash	Yes	Hash containing information related to this project's status in the current user's notebook (favorited, bookmark_id, ...)
photos	(full)		
photos_count	Integer		
picks_per_inch	Decimal	Yes	
private_notes_html	String	Yes	Private project notes, only viewable by the project owner
private_notes	String	Yes	Private project notes, raw markdown before rendering as HTML and sanitizing
progress	Integer	Yes	
project_status_changed			
project_status_id	Integer	Yes	
rating	Integer	Yes	
row_gauge	Decimal	Yes	
size	String	Yes	
started	Date	Yes	
started_day_set	Boolean		If set to false, the "started" date day is unknown. It represents a month and year only
status_name	String	Yes	

Name	Type	Nullable	Description
tag_names	Array	Yes	Array of tags (tags cannot contain commas)
tools	(full)		
updated_at	Date		
user	User (small)		User that is the Project owner
user_id			

Project (export)

Attributes

Name	Type	Nullable	Description
comments_count	Integer		
completed	Date	Yes	
completed_day_set	Boolean		If set to false, the "completed" date day is unknown. It represents a month and year only
craft_id	Integer	Yes	
craft_name			
created_at	Date		
ends_per_inch	Decimal	Yes	
favorites_count	Integer		
gauge_divisor	Integer	Yes	
gauge	Decimal	Yes	
gauge_pattern	String	Yes	
gauge_repeats	Integer	Yes	
id	Integer		
links	Object		Links to the project on Ravelry
made_for	String	Yes	
made_for_user_id	Integer	Yes	
name	String		
needle_sizes			
notes_html	String	Yes	Public project notes
notes	String	Yes	Public project notes, raw markdown before rendering as HTML and sanitizing
packs	Pack (full)	Yes	Array of pack records containing detailed information about an allocation of yarn. Only allowed on project creation. For updating or deleting use the pack API methods.
pattern_id	Integer	Yes	A project might have a pattern name and no pattern ID (if it is not linked to a Ravelry database pattern)
pattern_name	String	Yes	
permalink	String		
personal_attributes	Hash	Yes	Hash containing information related to this project's status in the current user's notebook (favorited, bookmark_id, ...)

Name	Type	Nullable	Description
photos	(full)		
photos_count	Integer		
picks_per_inch	Decimal	Yes	
private_notes_html	String	Yes	Private project notes, only viewable by the project owner
private_notes	String	Yes	Private project notes, raw markdown before rendering as HTML and sanitizing
progress	Integer	Yes	
project_status_changed			
project_status_id	Integer	Yes	
rating	Integer	Yes	
row_gauge	Decimal	Yes	
size	String	Yes	
started	Date	Yes	
started_day_set	Boolean		If set to false, the "started" date day is unknown. It represents a month and year only
status_name	String	Yes	
tag_names	Array	Yes	Array of tags (tags cannot contain commas)
tools	(full)		
updated_at	Date		
user_id			

Project (POST)

Attributes

Name	Type	Nullable	Description
completed	Date	Yes	
completed	Date	Yes	
craft_id	Integer	Yes	
craft_id	Integer	Yes	
ends_per_inch			
gauge			
gauge_divisor			
gauge_pattern			
gauge_repeats			
made_for	String	Yes	
made_for_user_id	Integer	Yes	
made_for_user_id	Integer	Yes	
name	String		
needle_sizes	Array, Object (POST)	Yes	List of needle size IDs. We will replace any existing needles with the contents of this array.

Name	Type	Nullable	Description
notes	String	Yes	Public project notes
packs	Pack (POST)	Yes	Array of pack records containing detailed information about an allocation of yarn. Only allowed on project creation. For updating or deleting use the pack API methods.
pattern_id	Integer	Yes	A project might have a pattern name and no pattern ID (if it is not linked to a Ravelry database pattern)
personal_pattern_name	String	Yes	
picks_per_inch			
private_notes	String	Yes	Private project notes, only viewable by the project owner
progress	Integer	Yes	
project_status_id	Integer	Yes	
project_status_id	Integer	Yes	
rating	Integer	Yes	
row_gauge			
size	String	Yes	
started	Date	Yes	
started	Date	Yes	
tag_names	Array (POST)	Yes	Array of tags (tags cannot contain commas)

ForumStatisticSummary

ForumStatisticSummary

Attributes

Name	Type	Nullable	Description
forum_id	Integer		
new_topics_30day	Integer		
new_topics_7day	Integer		
new_topics_avg	Integer		
pageviews_30day	Integer		
pageviews_7day	Integer		
pageviews_avg	Integer		
posts_30day	Integer		
posts_7day	Integer		
posts_avg	Integer		
unique_pageviews_30day	Integer		
unique_pageviews_7day	Integer		
unique_pageviews_avg	Integer		

PatternTagging

PatternTagging

Attributes

Name	Type	Nullable	Description
id	Integer		
pattern_attribute_id	Integer		
pattern_id	Integer		

PatternTagging (list)

Attributes

Name	Type	Nullable	Description
id	Integer		
pattern_attribute	PatternAttribute (list)		Pattern attribute
pattern_attribute_id	Integer		
pattern_id	Integer		

PatternTagging (POST)

Attributes

Name	Type	Nullable	Description
id	Integer		
pattern_attribute_id	Integer		

AttributeGroup

AttributeGroup (list)

Attributes

Name	Type	Nullable	Description
children	Array, AttributeGroup (list)		Child attribute groups (subgroups)
id	Integer		
name	String		Attribute group name
pattern_attributes	Array, PatternAttribute (list)		Attributes contained in this group
permalink	String		

YarnAttributeGroup

YarnAttributeGroup

Attributes

Name	Type	Nullable	Description
id	Integer		
name	String		Attribute group name
permalink	String		

YarnAttributeGroup (full)

Attributes

Name	Type	Nullable	Description
id	Integer		
name	String		Attribute group name
permalink	String		

YarnAttributeGroup (list)

Attributes

Name	Type	Nullable	Description
children	Array, YarnAttributeGroup (list)		Child yarn attribute groups (subgroups)
id	Integer		
name	String		Attribute group name
permalink	String		
yarn_attributes			

YarnCountry

YarnCountry

Attributes

Name	Type	Nullable	Description
advertising_shops	Integer		Number of shops that are advertising this yarn
country_id	Integer		Country identifier
id	Integer		
shops_with_patrons	Integer		Number of unique shops where this yarn was purchased (recently or at any time in the past)
shops_with_patrons_30days	Integer		Number of unique shops where this yarn was purchased during the last 30 days
shops_with_patrons_60days	Integer		Number of unique shops where this yarn was purchased during the last 60 days

Name	Type	Nullable	Description
shops_with_patrons_90days	Integer		Number of unique shops where this yarn was purchased during the last 90 days
yarn_id	Integer		Yarn identifier

YarnCountry (full)

Attributes

Name	Type	Nullable	Description
advertising_shops	Integer		Number of shops that are advertising this yarn
country_id	Integer		Country identifier
country_name			
id	Integer		
shops_with_patrons	Integer		Number of unique shops where this yarn was purchased (recently or at any time in the past)
shops_with_patrons_30days	Integer		Number of unique shops where this yarn was purchased during the last 30 days
shops_with_patrons_60days	Integer		Number of unique shops where this yarn was purchased during the last 60 days
shops_with_patrons_90days	Integer		Number of unique shops where this yarn was purchased during the last 90 days
yarn_id	Integer		Yarn identifier

FiberType

FiberType (full)

Attributes

Name	Type	Nullable	Description
animal_fiber	Boolean		
id	Integer		
name	String		
synthetic	Boolean		
vegetable_fiber	Boolean		

Pack

Pack (stash)

Attributes

Name	Type	Nullable	Description
------	------	----------	-------------

Name	Type	Nullable	Description
color_attributes			
color_family_id	String	Yes	Color family. See /color_families.json
colorway			
dye_lot	String	Yes	Dye lot, name or number from ball band or free-form text
grams_per_skein			
id			
meters_per_skein			
ounces_per_skein			
personal_name	String	Yes	Personal name, use if not linking to a database yarn
prefer_metric_length			
prefer_metric_weight			
primary_pack_id			
project_id	Integer	Yes	Project the pack is affiliated with
quantity_description			
shop_id	Integer	Yes	Shop that the yarn was purchased from. See /shops/
shop_name			
skeins	String	Yes	# of skeins of this yarn.
stash_id	Integer	Yes	Stash the pack is affiliated with
thread_size			
total_grams			
total_meters			
total_ounces			
total_yards			
yards_per_skein			
yarn_id	Integer	Yes	Yarn that this pack (allocation of yarn) is linked to. NOTE: you only need to supply the yarn if you are associating a pack with a project and that pack is not also associated with a stash entry. On Ravelry, this would be akin to adding a yarn to your project and linking it to a yarn (and not a stash entry)

Pack (stash_for_owner)

Attributes

Name	Type	Nullable	Description
color_attributes			
color_family_id	String	Yes	Color family. See /color_families.json
colorway			
dye_lot	String	Yes	Dye lot, name or number from ball band or free-form text
grams_per_skein			
id			
meters_per_skein			

Name	Type	Nullable	Description
ounces_per_skein			
personal_name	String	Yes	Personal name, use if not linking to a database yarn
prefer_metric_length			
prefer_metric_weight			
primary_pack_id			
project_id	Integer	Yes	Project the pack is affiliated with
quantity_description			
shop_id	Integer	Yes	Shop that the yarn was purchased from. See /shops/
shop_name			
skeins	String	Yes	# of skeins of this yarn.
stash_id	Integer	Yes	Stash the pack is affiliated with
thread_size			
total_grams			
total_meters			
total_ounces			
total_paid_currency			
total_paid			
total_yards			
yards_per_skein			
yarn_id	Integer	Yes	Yarn that this pack (allocation of yarn) is linked to. NOTE: you only need to supply the yarn if you are associating a pack with a project and that pack is not also associated with a stash entry. On Ravelry, this would be akin to adding a yarn to your project and linking it to a yarn (and not a stash entry)

Pack (full)

Attributes

Name	Type	Nullable	Description
color_family_id	String	Yes	Color family. See /color_families.json
colorway			
dye_lot	String	Yes	Dye lot, name or number from ball band or free-form text
grams_per_skein			
id			
meters_per_skein			
ounces_per_skein			
personal_name	String	Yes	Personal name, use if not linking to a database yarn
prefer_metric_length			
prefer_metric_weight			
primary_pack_id			
project_id	Integer	Yes	Project the pack is affiliated with

Name	Type	Nullable	Description
quantity_description			
shop_id	Integer	Yes	Shop that the yarn was purchased from. See /shops/
shop_name			
skeins	String	Yes	# of skeins of this yarn.
stash_id	Integer	Yes	Stash the pack is affiliated with
thread_size			
total_grams			
total_meters			
total_ounces			
total_yards			
yards_per_skein			
yarn			
yarn_id	Integer	Yes	Yarn that this pack (allocation of yarn) is linked to. NOTE: you only need to supply the yarn if you are associating a pack with a project and that pack is not also associated with a stash entry. On Ravelry, this would be akin to adding a yarn to your project and linking it to a yarn (and not a stash entry)
yarn_name			
yarn_weight			

Pack (full_for_owner)

Attributes

Name	Type	Nullable	Description
color_family_id	String	Yes	Color family. See /color_families.json
colorway			
dye_lot	String	Yes	Dye lot, name or number from ball band or free-form text
grams_per_skein			
id			
meters_per_skein			
ounces_per_skein			
personal_name	String	Yes	Personal name, use if not linking to a database yarn
prefer_metric_length			
prefer_metric_weight			
primary_pack_id			
project_id	Integer	Yes	Project the pack is affiliated with
quantity_description			
shop_id	Integer	Yes	Shop that the yarn was purchased from. See /shops/
shop_name			
skeins	String	Yes	# of skeins of this yarn.
stash_id	Integer	Yes	Stash the pack is affiliated with

Name	Type	Nullable	Description
thread_size			
total_grams			
total_meters			
total_ounces			
total_paid_currency			
total_paid			
total_yards			
yards_per_skein			
yarn			
yarn_id	Integer	Yes	Yarn that this pack (allocation of yarn) is linked to. NOTE: you only need to supply the yarn if you are associating a pack with a project and that pack is not also associated with a stash entry. On Ravelry, this would be akin to adding a yarn to your project and linking it to a yarn (and not a stash entry)
yarn_name			
yarn_weight			

Pack (public)

Attributes

Name	Type	Nullable	Description
id			
yarn_id	Integer	Yes	Yarn that this pack (allocation of yarn) is linked to. NOTE: you only need to supply the yarn if you are associating a pack with a project and that pack is not also associated with a stash entry. On Ravelry, this would be akin to adding a yarn to your project and linking it to a yarn (and not a stash entry)

Pack (POST)

Attributes

Name	Type	Nullable	Description
color_family_id	String	Yes	Color family. See /color_families.json
colorway	String	Yes	Colorway. Number or name from ball band or free form description.
dye_lot	String	Yes	Dye lot, name or number from ball band or free-form text
length_units	String	Yes	One of 'yards', 'meters'
personal_gauge_divisor	String	Yes	Personal gauge info, use if not linking to a database yarn
personal_max_gauge	Integer	Yes	Personal gauge info, use if not linking to a database yarn
personal_min_gauge	Integer	Yes	Personal gauge info, use if not linking to a database yarn
personal_name	String	Yes	Personal name, use if not linking to a database yarn
personal_shop_name	String	Yes	Personal purchase information, use if not linking to a shop

Name	Type	Nullable	Description
personal_thread_size			
personal_yarn_weight_id	Integer	Yes	Personal yarn weight, use if not linking to a yarn. See /yarn_weights.json
project_id	Integer	Yes	Project the pack is affiliated with
purchased_city	String	Yes	Personal purchase information, use if not linking to a shop
purchased_country_id	Integer	Yes	Personal purchase information, use if not linking to a shop
purchased_date	Date	Yes	Date that the yarn was purchased. YYYY-MM-DD format.
purchased_state_id	Integer	Yes	Personal purchase information, use if not linking to a shop
purchased_url	String	Yes	Personal purchase information, use if not linking to a shop
shop_id	Integer	Yes	Shop that the yarn was purchased from. See /shops/
skein_length	String	Yes	length of a skein of this yarn.
skein_weight	String	Yes	weight of a skein of this yarn.
skeins	String	Yes	# of skeins of this yarn.
stash_id	Integer	Yes	Stash the pack is affiliated with
total_length	String	Yes	length of this allocation of yarn.
total_paid	String	Yes	Amount paid for this quantity of yarn
total_paid_currency	String	Yes	3 character currency code
total_weight	String	Yes	weight of this allocation of yarn.
weight_units	String	Yes	One of 'grams', 'ounces'
yarn_id	Integer	Yes	Yarn that this pack (allocation of yarn) is linked to. NOTE: you only need to supply the yarn if you are associating a pack with a project and that pack is not also associated with a stash entry. On Ravelry, this would be akin to adding a yarn to your project and linking it to a yarn (and not a stash entry)

Topic

Topic (list)

Attributes

Name	Type	Nullable	Description
archived	Boolean		
created_at	Date		
forum_id	Integer		
forum_images_count	Integer		
forum_posts_count	Integer		
id	Integer		
ignored			
last_read	Integer		Post number for the last post that the current user has read
latest_reply	Integer		Post number for the latest reply
locked	Boolean		Topic is marked as "locked" and does not accept replies

Name	Type	Nullable	Description
no_chat			
replied_at	Date		
sticky	Boolean		Topic is marked as "no chat" and does not accept replies to individual posts
title	String		
watched			

Topic (browse)

Attributes

Name	Type	Nullable	Description
archived	Boolean		
created_at	Date		
forum	Forum (small)		
forum_id	Integer		
forum_images_count	Integer		
forum_posts_count	Integer		
id	Integer		
ignored			
last_read	Integer		Post number for the last post that the current user has read
latest_reply	Integer		Post number for the latest reply
locked	Boolean		Topic is marked as "locked" and does not accept replies
no_chat			
replied_at	Date		
sticky	Boolean		Topic is marked as "no chat" and does not accept replies to individual posts
title	String		
watched			

Topic (full)

Attributes

Name	Type	Nullable	Description
archived	Boolean		
can_edit_as_moderator			
created_at	Date		
created_by_user			
forum	Forum (small)		

Name	Type	Nullable	Description
forum_id	Integer		
forum_images_count	Integer		
forum_posts_count	Integer		
id	Integer		
ignored			
last_read			
latest_reply	Integer		Post number for the latest reply
locked	Boolean		Topic is marked as "locked" and does not accept replies
no_chat			
replied_at	Date		
sticky	Boolean		Topic is marked as "no chat" and does not accept replies to individual posts
summary_html	String	Yes	Summary/notes section rendered into HTML
summary			
title	String		
watched			

Group

Group (list)

Attributes

Name	Type	Nullable	Description
badge_url	String	Yes	URL to badge image
banner_url	String	Yes	URL to banner image
created_at	Date		
forum	Forum (list)		The forum associated with this group
forum_id	Integer		
id	Integer		
mature	Boolean		True if the owners have marked the group as "mature"
name	String		Name of this group
permalink	String		
short_description	String		Short description of this group

UnifiedStash

UnifiedStash (list)

Attributes

Name	Type	Nullable	Description
------	------	----------	-------------

Name	Type	Nullable	Description
fiber_stash	FiberStash	Yes	If this is a fiber stash result, the fiber stash model will be present under this key
stash	Stash	Yes	If this is a stash result, the stash model will be present under this key

ProductNotification

ProductNotification

Attributes

Name	Type	Nullable	Description
created_at	Date		Creation date
id	Integer		Product notification identifier
message	String	Yes	Message included in the notification, in markdown format
message_html	String	Yes	Message included in the notification, in HTML format
product_id	Integer		ID of the product this notification is related to
version	String	Yes	File version info for this notification

Saleable

Saleable

Attributes

Name	Type	Nullable	Description
created_at	Date		When the record was created
id	Integer		Saleable ID. A Saleable record connects a Product to the Pattern or PatternSource page where that Product is listed for sale.
product_id	Integer		Product ID
saleable_id	Integer		ID for the associated record (a Pattern, PatternSource, or DraftPattern)
saleable_type	String		Type of the associated record ("Pattern", "PatternSource", or "DraftPattern")
updated_at	Date		When the record was last updated

Product

Product (javascript)

Attributes

Name	Type	Nullable	Description
active	Boolean		Product is active and available for purchase. Can be set to false at any time, can be set to true if the product is set up (including attachments) and the store

Name	Type	Nullable	Description
			is open for business.
id	Integer		Product identifier
pretty_price	String		price with currency symbol
price	String	Yes	Price, for non-free products
sku	String		Product SKU. Typically you will keep the default unless matching SKUs in external systems is needed/desirable
store_id	String		Store identifier
title	String		Product title/description

Product (list)

Attributes

Name	Type	Nullable	Description
active	Boolean		Product is active and available for purchase. Can be set to false at any time, can be set to true if the product is set up (including attachments) and the store is open for business.
attachment_bytes	Integer		total size of files attached to the product
currency	String	Yes	3 character currency code, for non-free products
designer_photos_count	Integer		the number of photos associated with the product that were created by the designer (ie. contributed user photos are not included)
free	Boolean	Yes	Free, true for free products
has_notes			
id	Integer		Product identifier
languages	Array, String		list of language codes that the included files cover (ISO 639-1 language codes) If the list is not known, an empty array is returned.
mature_content	Boolean		true if the linked item's subject matter, title, or image is classified as "mature content"
photos_count	Integer		the number of photos associated with the product
pretty_price	String		price with currency symbol
price	String	Yes	Price, for non-free products
product_type			
saleables			
sku	String		Product SKU. Typically you will keep the default unless matching SKUs in external systems is needed/desirable
square_thumbnail_url			
store_id	String		Store identifier
title	String		Product title/description

Product (full)

Attributes

Name	Type	Nullable	Description
active	Boolean		Product is active and available for purchase. Can be set to false at any time, can be set to true if the product is set up (including attachments) and the store is open for business.
attachments			
currency	String	Yes	3 character currency code, for non-free products
free	Boolean	Yes	Free, true for free products
id	Integer		Product identifier
pattern_sources	Array, PatternSource		The pattern sources that are currently associated with this product
patterns	Array, Pattern		The patterns that are currently associated with this product
pretty_price	String		price with currency symbol
pretty_wholesale_price	String	Yes	wholesale price with currency symbol
price	String	Yes	Price, for non-free products
product_type			
saleables			
sku	String		Product SKU. Typically you will keep the default unless matching SKUs in external systems is needed/desirable
store_id	String		Store identifier
title	String		Product title/description
wholesale_price	String	Yes	price paid by yarn stores participating in In Store Sales

Product (delivery)

Attributes

Name	Type	Nullable	Description
active	Boolean		Product is active and available for purchase. Can be set to false at any time, can be set to true if the product is set up (including attachments) and the store is open for business.
id	Integer		Product identifier
pattern_sources	Array, PatternSource		The pattern sources that are currently associated with this product
patterns	Array, Pattern		The patterns that are currently associated with this product
product_type			
sku	String		Product SKU. Typically you will keep the default unless matching SKUs in external systems is needed/desirable
store_id	String		Store identifier
title	String		Product title/description

Product (POST)

Attributes

Name	Type	Nullable	Description
active	Boolean		Product is active and available for purchase. Can be set to false at any time, can be set to true if the product is set up (including attachments) and the store is open for business.
currency	String	Yes	3 character currency code, for non-free products
free	Boolean	Yes	Free, true for free products
price	String	Yes	Price, for non-free products
reporting_tag	String	Yes	Optional tag that appears in data exports. Not visible to customers.
sku	String		Product SKU. Typically you will keep the default unless matching SKUs in external systems is needed/desirable
title	String		Product title/description
wholesale	Boolean	Yes	For stores that are enrolled in In Store Sales program, set this to true to make a product available to Local Yarn Stores via In Store Sales

Ad

Ad (shop)

Attributes

Name	Type	Nullable	Description
logo_url			
target_url	String		

ForumPreference

ForumPreference (list)

Attributes

Name	Type	Nullable	Description
forum	Forum		
position	Integer		User's sort order for this forum

DraftErrataLink

DraftErrataLink (full)

Attributes

Name	Type	Nullable	Description
created_at			

Name	Type	Nullable	Description
draft_pattern_id			
id			
updated_at			
url			

NeedleRecord

NeedleRecord (small)

Attributes

Name	Type	Nullable	Description
comment			
id			
needle_type_id			

NeedleRecord (full)

Attributes

Name	Type	Nullable	Description
comment			
id			
needle_type			
needle_type_id			

QueuedStash

QueuedStash (full)

Attributes

Name	Type	Nullable	Description
created_at			
id			
queued_project_id			
stash			
stash_id			
updated_at			

FiberStash

FiberStash

Attributes

Name	Type	Nullable	Description
colorway_name			
comments_count	Integer		
created_at	Date		
favorites_count	Integer		
fiber_company_name	String	Yes	
first_photo	Photo		
has_photo	Boolean	Yes	
id	Integer		
location	String	Yes	
long_name	String	Yes	name including the fiber company name
name	String	Yes	The name that the user has given this stash entry
permalink	String		
stash_status	StashStatus	Yes	
updated_at	Date		
user	User (small)		
user_id	Integer		

FiberStash (list)

Attributes

Name	Type	Nullable	Description
colorway_name			
comments_count	Integer		
created_at	Date		
favorites_count	Integer		
fiber_company_name	String	Yes	
first_photo	Photo		
has_photo	Boolean	Yes	
id	Integer		
location	String	Yes	
long_name	String	Yes	name including the fiber company name
name	String	Yes	The name that the user has given this stash entry
permalink	String		
stash_status	StashStatus	Yes	
updated_at	Date		
user	User (small)		
user_id	Integer		

FiberStash (full)

Attributes

Name	Type	Nullable	Description
colorway_name			
comments_count	Integer		
created_at	Date		
favorites_count	Integer		
fiber_company_name	String	Yes	
fiber_packs	FiberPack (stash)		
has_photo	Boolean	Yes	
id	Integer		
location	String	Yes	
long_name	String	Yes	name including the fiber company name
name	String	Yes	The name that the user has given this stash entry
notes_html	String		Notes for this entry, rendered as HTML
permalink	String		
photos	Photo (full)		
stash_status	StashStatus	Yes	
updated_at	Date		
user	User (small)		
user_id	Integer		

FiberStash (export)

Attributes

Name	Type	Nullable	Description
colorway_name			
comments_count	Integer		
created_at	Date		
favorites_count	Integer		
fiber_company_name	String	Yes	
fiber_packs	FiberPack (stash)		
has_photo	Boolean	Yes	
id	Integer		
location	String	Yes	
long_name	String	Yes	name including the fiber company name
name	String	Yes	The name that the user has given this stash entry
notes_html	String		Notes for this entry, rendered as HTML
permalink	String		
photos	Photo (full)		

Name	Type	Nullable	Description
stash_status	StashStatus	Yes	
updated_at	Date		
user_id	Integer		

FiberStash (POST)

Attributes

Name	Type	Nullable	Description
fiber_company_name	String	Yes	
fiber_pack			
location	String	Yes	
name	String	Yes	The name that the user has given this stash entry
notes			
stash_status_id			

YarnCompany

YarnCompany

Attributes

Name	Type	Nullable	Description
id			
logo_url			
name			
permalink			
url			
yarns_count			

YarnCompany (full)

Attributes

Name	Type	Nullable	Description
id			
logo_url			
name			
permalink			
url			
yarns_count			

YarnCompany (list)

Attributes

Name	Type	Nullable	Description
id			
logo_url			
name			
permalink			
url			
yarns_count			

YarnCompany (public)

Attributes

Name	Type	Nullable	Description
id			
name			
permalink			
url			

YarnCompany (shop)

Attributes

Name	Type	Nullable	Description
advertised			
id			
most_recent_purchase			
name			
permalink			
purchases			

InvoiceLineItem

InvoiceLineItem (sale)

Attributes

Name	Type	Nullable	Description
amount	Decimal		Amount of the invoice attributed to this item. Will be negative for promotions.

Name	Type	Nullable	Description
id	Integer		Invoice line item ID
product_id	Integer	Yes	Promotion ID, if this item is a promotion
promotion_id	Integer	Yes	Product ID, if this item is a product
promotional_discount_applied	Decimal	Yes	If a promotion was applied to this product, `promotional_discount_applied` will contain the share of the discount that relates to this line item
title			

YarnFiber

YarnFiber (full)

Attributes

Name	Type	Nullable	Description
fiber_category	FiberCategory (full)		
fiber_type	FiberType (full)		
id	Integer		
percentage	Integer		

YarnFiber (public)

Attributes

Name	Type	Nullable	Description
fiber_category_id			
fiber_type_id			
id	Integer		
percentage	Integer		

PatternCategory

PatternCategory

Attributes

Name	Type	Nullable	Description
id	Integer		
name	String		Short category name
parent			
permalink	String		

PatternCategory (list)

Attributes

Name	Type	Nullable	Description
children	Array, PatternCategory (list)		Child categories (subcategories)
id	Integer		
long_name	String		Descriptive category name
name	String		Short category name
permalink	String		

Photo

Photo

Attributes

Name	Type	Nullable	Description
aspect_ratio	Float		Aspect ratio of the photo
caption	String	Yes	Photo caption
caption_html	String	Yes	Photo caption, with image tags instead of emoji
copyright_holder			
id			
medium2_url	String		Medium2 image, 640 pixels on the longest side. For larger images suitable for zooming, see /photos/{id}/sizes.json
medium_url	String		Medium image, 500 pixels on the longest side. You can get exact dimensions by using /photos/dimensions.json.
small2_url	String		Small2 image, 320 pixels on the longest side. You can get exact dimensions by using /photos/dimensions.json.
small_url	String		Small image, 240 pixels on the longest side. You can get exact dimensions by using /photos/dimensions.json.
sort_order			
square_url	String		A tiny, square thumbnail, 75 x 75px
thumbnail_url	String		Thumbnail, 100 pixels on the longest side
user_id	Integer		User ID of the photo's owner/uploader
x_offset	Integer	Yes	X offset for centered photo. See POST /photos/{id}.json for more information.
y_offset	Integer	Yes	Y offset for centered photo. See POST /photos/{id}.json for more information.

Photo (small)

Attributes

Name	Type	Nullable	Description
aspect_ratio	Float		Aspect ratio of the photo
caption	String	Yes	Photo caption
caption_html	String	Yes	Photo caption, with image tags instead of emoji
copyright_holder_id			
medium2_url	String		Medium2 image, 640 pixels on the longest side. For larger images suitable for zooming, see /photos/{id}/sizes.json
medium_url	String		Medium image, 500 pixels on the longest side. You can get exact dimensions by using /photos/dimensions.json.
small2_url	String		Small2 image, 320 pixels on the longest side. You can get exact dimensions by using /photos/dimensions.json.
small_url	String		Small image, 240 pixels on the longest side. You can get exact dimensions by using /photos/dimensions.json.
sort_order			
square_url	String		A tiny, square thumbnail, 75 x 75px
thumbnail_url	String		Thumbnail, 100 pixels on the longest side
user_id	Integer		User ID of the photo's owner/uploader
x_offset	Integer	Yes	X offset for centered photo. See POST /photos/{id}.json for more information.
y_offset	Integer	Yes	Y offset for centered photo. See POST /photos/{id}.json for more information.

Photo (full)

Attributes

Name	Type	Nullable	Description
aspect_ratio	Float		Aspect ratio of the photo
caption	String	Yes	Photo caption
caption_html	String	Yes	Photo caption, with image tags instead of emoji
copyright_holder_id			
flickr_url			
id			
medium2_url	String		Medium2 image, 640 pixels on the longest side. For larger images suitable for zooming, see /photos/{id}/sizes.json
medium_url	String		Medium image, 500 pixels on the longest side. You can get exact dimensions by using /photos/dimensions.json.
shelved_url	String	Yes	A book cover image, 150 pixels wide
small2_url	String		Small2 image, 320 pixels on the longest side. You can get exact dimensions by using /photos/dimensions.json.
small_url	String		Small image, 240 pixels on the longest side. You can get exact dimensions by using /photos/dimensions.json.
sort_order			

Name	Type	Nullable	Description
square_url	String		A tiny, square thumbnail, 75 x 75px
thumbnail_url	String		Thumbnail, 100 pixels on the longest side
user_id	Integer		User ID of the photo's owner/uploader
x_offset	Integer	Yes	X offset for centered photo. See POST /photos/{id}.json for more information.
y_offset	Integer	Yes	Y offset for centered photo. See POST /photos/{id}.json for more information.

BundledItem

BundledItem (small)

Attributes

Name	Type	Nullable	Description
bundle_id	Integer		Bundle ID
id	Integer		bundled item identifier
item_id	Integer		item identifier. May only be set during creation.
item_type	String		the type of item - clipping, pattern, designer, project, stash, yarn_company, yarn, shop, forum_post, fiber_stash, bundle, or pattern_source
user	User (small)		User that is the item owner

BundledItem (list)

Attributes

Name	Type	Nullable	Description
bookmark	Bookmark (list)	Yes	Bookmark attached to bundled item
bundle_id	Integer		Bundle ID
created_at	Date		
id	Integer		bundled item identifier
item_id	Integer		item identifier. May only be set during creation.
item_type	String		the type of item - clipping, pattern, designer, project, stash, yarn_company, yarn, shop, forum_post, fiber_stash, bundle, or pattern_source
notes	String	Yes	
updated_at	Date		

BundledItem (full)

Attributes

Name	Type	Nullable	Description
bookmark	Bookmark (full)	Yes	Bookmark attached to bundled item
bundle_id	Integer		Bundle ID
created_at	Date		
id	Integer		bundled item identifier
item_id	Integer		item identifier. May only be set during creation.
item_type	String		the type of item - clipping, pattern, designer, project, stash, yarn_company, yarn, shop, forum_post, fiber_stash, bundle, or pattern_source
notes	String	Yes	
updated_at	Date		
user	User (small)		User that is the item owner

BundledItem (POST)

Attributes

Name	Type	Nullable	Description
bookmark_id	Integer		Bookmark ID, if this item is associated with a favorite
bundle_id	Integer		Bundle ID
item_id	Integer		item identifier. May only be set during creation.
item_id	Integer		item identifier. May only be set during creation.
item_type	String		the type of item - clipping, pattern, designer, project, stash, yarn_company, yarn, shop, forum_post, fiber_stash, bundle, or pattern_source
item_type	String		the type of item - clipping, pattern, designer, project, stash, yarn_company, yarn, shop, forum_post, fiber_stash, bundle, or pattern_source
notes	String	Yes	
user_id	Integer		User ID of the item owner.

ProjectStatus

ProjectStatus (list)

Attributes

Name	Type	Nullable	Description
id			
name			
permalink			

ComponentYarn

ComponentYarn

Attributes

Name	Type	Nullable	Description
combined_yarn_weight_id	Integer		Combined (effective) weight of all yarns held together
id	Integer		
pattern_id	Integer		Pattern ID
yarn_id	Integer		Yarn ID

ComponentYarn (list)

Attributes

Name	Type	Nullable	Description
combined_yarn_weight_id	Integer		Combined (effective) weight of all yarns held together
created_at	Date		
held_together_group	Integer	Yes	
id	Integer		
pattern_id	Integer		Pattern ID
updated_at	Date		
yarn_id	Integer		Yarn ID

ComponentYarn (POST)

Attributes

Name	Type	Nullable	Description
combined_yarn_weight_id	Integer		Combined (effective) weight of all yarns held together
id	Integer		
yarn_id	Integer		Yarn ID

PatternSourceType

PatternSourceType

Attributes

Name	Type	Nullable	Description
can_add_to_library			
id	Integer		
long_name			
name	String		Name of the source type

Name	Type	Nullable	Description
requires_url	Boolean		true if sources of this type require a URL

PatternSourceType (list)

Attributes

Name	Type	Nullable	Description
can_add_to_library			
id	Integer		
long_name			
name	String		Name of the source type
requires_url	Boolean		true if sources of this type require a URL

ForumSet

ForumSet (list)

Attributes

Name	Type	Nullable	Description
default			
id			
name			
permalink			
selected_forums			
sort_order			

InStoreSale

InStoreSale (receipt)

Attributes

Name	Type	Nullable	Description
deliveries	Array, Delivery (receipt)		Details about digital products that are being delivered to the customer
id	Integer		In Store Sale ID
invoice	Invoice (receipt)		Invoice details
seller_store_name	String		Name of the seller store that is being purchased from

Page

Page (full)

Attributes

Name	Type	Nullable	Description
body			
name			

Pattern

Pattern

Attributes

Name	Type	Nullable	Description
designer	PatternAuthor		
first_photo	Photo	Yes	
id	Integer		
name	String		Pattern name
pattern_author	PatternAuthor		
pattern_sources			
permalink	String		

Pattern (link)

Attributes

Name	Type	Nullable	Description
id	Integer		
name	String		Pattern name
permalink	String		

Pattern (list)

Attributes

Name	Type	Nullable	Description
designer	PatternAuthor		
first_photo	Photo	Yes	
free	Boolean		Free pattern (available free from Ravelry or free from some other source)
id	Integer		
name	String		Pattern name

Name	Type	Nullable	Description
pattern_author	PatternAuthor		
pattern_sources			
permalink	String		
personal_attributes	Hash		Hash containing information related to this pattern's status in the current user's notebook (queued, favorited, bookmark_id)

Pattern (source_list)

Attributes

Name	Type	Nullable	Description
first_photo	Photo	Yes	
id	Integer		
name	String		Pattern name
pattern_author	PatternAuthor		
permalink	String		

Pattern (full)

Attributes

Name	Type	Nullable	Description
comments_count	Integer		
craft	Craft (list)		
created_at	Date		Date that this pattern record was created
currency	String		Currency for price. Will be a PayPal-supported currency: https://www.paypal.com/cgi-bin/webscr?cmd=p/sell/mc/mc_wa-outside
currency_symbol			
difficulty_average	Float		
difficulty_count	Integer		
download_location	DownloadLocation		Where to download or purchase the pattern - contains a URL, free flag, and type ("ravelry" or "external")
downloadable	Boolean		
favorites_count	Integer		
free	Boolean		Free pattern (available free from Ravelry or free from some other source)
free	Boolean		Free pattern (available free from Ravelry or free from some other source)
gauge	String		Gauge
gauge_description	String		

Name	Type	Nullable Description
gauge_divisor	Integer	Gauge divisor (ie. stitches per [divisor]"), in inches. Accepted options: 1, 2, 4 corresponding to 1" (2.5cm), 2" (5cm), 4" (10cm).
gauge_pattern	String	Pattern for gauge (free form text)
gauge_repeats	String	
generally_available	Date	Our best estimate of the date when this pattern first became available to the public. Not displayed on the pattern page.
has_uk_terminology	Boolean	Crochet pattern includes UK terminology
has_us_terminology	Boolean	Crochet pattern includes US terminology
id	Integer	
languages		
name	String	Pattern name
notes_html	String	Pattern notes rendered as HTML.
notes		
packs	Pack (full)	Packs connect a pattern to a suggested yarn. Within a pack, only "yarn_id" is required.
pattern_attributes	Array, PatternAttribute	
pattern_author	PatternAuthor	
pattern_categories	Array, PatternCategory	
pattern_needle_sizes	String	
pattern_type		
pdf_in_library	Boolean	Set to "true" if the user's library contains PDF files for this pattern.
pdf_url	String	
permalink	String	
personal_attributes	Hash	Hash containing information related to this pattern's status in the current user's notebook (queued, favorited, bookmark_id)
photos	Array, Photo	
price	String	Price. If the pattern is associated with a Ravelry download, the price is retrieved from the product and the price attribute is read-only.
printings	Printing (list)	
product_id	Integer	Product ID for the product that is currently listed on the pattern page as a "buy now" option, if any
projects_count	Integer	
published	Date	Date the pattern was published, displayed on the pattern page (also see "generally_available")
queued_projects_count	Integer	
rating_average	Float	

Name	Type	Nullable	Description
rating_count	Integer		
ravelry_download	Boolean		
row_gauge	String		Row gauge
sizes_available	String		
unlisted_product_ids	Array, Integer		Product IDs for products that are not currently listed on the pattern page as a "buy now" option. Only present if the current user has editing permissions.
updated_at	Date		Date that this pattern record was last updated
url	String		
volumes_in_library	Array, Integer	Yes	If the user has pattern PDFs in their library, the Volume IDs will be included. See /volumes/{id}.json
yardage	Integer		
yardage_description	String		
yardage_max	Integer		Maximum yardage. To supply meterage instead, see meterage_max.
yarn_list_type			
yarn_weight	YarnWeight (list)		
yarn_weight_description	String		

Pattern (public)

Attributes

Name	Type	Nullable	Description
craft_id	Integer		craft ID (crochet = 1, knitting = 2)
created_at	Date		Date that this pattern record was created
currency	String		Currency for price. Will be a PayPal-supported currency: https://www.paypal.com/cgi-bin/webscr?cmd=p/sell/mc/mc_wa-outside
currency_symbol			
downloadable	Boolean		
free	Boolean		Free pattern (available free from Ravelry or free from some other source)
free	Boolean		Free pattern (available free from Ravelry or free from some other source)
gauge	String		Gauge
gauge_description	String		
gauge_divisor	Integer		Gauge divisor (ie. stitches per [divisor]), in inches. Accepted options: 1, 2, 4 corresponding to 1" (2.5cm), 2" (5cm), 4" (10cm).
gauge_pattern	String		Pattern for gauge (free form text)
gauge_repeats	String		

Name	Type	Nullable	Description
generally_available	Date		Our best estimate of the date when this pattern first became available to the public. Not displayed on the pattern page.
has_uk_terminology	Boolean		Crochet pattern includes UK terminology
has_us_terminology	Boolean		Crochet pattern includes US terminology
id	Integer		
name	String		Pattern name
notes_html	String		Pattern notes rendered as HTML.
notes			
packs	Pack (public)		Packs connect a pattern to a suggested yarn. Within a pack, only "yarn_id" is required.
pattern_attribute_ids			
pattern_author_id			
pattern_category_ids			
pattern_needle_sizes	String		
pdf_url	String		
permalink	String		
price	String		Price. If the pattern is associated with a Ravelry download, the price is retrieved from the product and the price attribute is read-only.
printings	Printing (public)		
published	Date		Date the pattern was published, displayed on the pattern page (also see "generally_available")
row_gauge	String		Row gauge
sizes_available	String		
updated_at	Date		Date that this pattern record was last updated
url	String		
yardage	Integer		
yardage_description	String		
yardage_max	Integer		Maximum yardage. To supply meterage instead, see meterage_max.
yarn_list_type			
yarn_weight_description	String		
yarn_weight_id	Integer		Yarn weight ID. See yarn_weights.json

Pattern (oembed)

Attributes

Name	Type	Nullable	Description
currency_code			
name	String		Pattern name
price			

Name	Type	Nullable	Description
title			
url			

Pattern (POST)

Attributes

Name	Type	Nullable	Description
component_yarns	ComponentYarn (POST)		(Only for patterns with yarns held together) Yarns held together to create a single strand of yarn for the pattern. Each contains a yarn ID and the final (combined) yarn weight ID (see yarn_weights.json)
craft_id	Integer		craft ID (crochet = 1, knitting = 2)
currency	String		Currency for price. Will be a PayPal-supported currency: https://www.paypal.com/cgi-bin/webscr?cmd=p/sell/mc/mc_wa-outside
free	Boolean		Free pattern (available free from Ravelry or free from some other source)
gauge	String		Gauge
gauge_divisor	Integer		Gauge divisor (ie. stitches per [divisor]"), in inches. Accepted options: 1, 2, 4 corresponding to 1" (2.5cm), 2" (5cm), 4" (10cm).
gauge_divisor	Integer		Gauge divisor (ie. stitches per [divisor]"), in inches. Accepted options: 1, 2, 4 corresponding to 1" (2.5cm), 2" (5cm), 4" (10cm).
gauge_pattern	String		Pattern for gauge (free form text)
gauge_repeats	String		
has_uk_terminology	Boolean		Crochet pattern includes UK terminology
has_us_terminology	Boolean		Crochet pattern includes US terminology
meterage_max	Integer		Maximum meterage. To supply yardage instead, see yardage_max.
meterage_min	Integer		Minimum meterage. To supply yardage instead, see yardage_min.
name	String		Pattern name
notes	String		Raw notes. May be mixed Markdown and HTML. Generally only useful when presenting a pattern notes editor.
only_available_with_yarn_purchase			

Name	Type	Nullable	Description
packs	Pack (POST)		Packs connect a pattern to a suggested yarn. Within a pack, only "yarn_id" is required.
pattern_classifications	PatternClassification (POST)		
pattern_languages	PatternLanguage (POST)		
pattern_needle_sizes	PatternNeedleSize (POST)		
pattern_taggings	PatternTagging (POST)		
price	String		Price. If the pattern is associated with a Ravelry download, the price is retrieved from the product and the price attribute is read-only.
printings	Printing (POST)		
row_gauge	String		Row gauge
sizes_available	String		Sizes available (free form text)
url	String		
yardage_max	Integer		Maximum yardage. To supply meterage instead, see meterage_max.
yardage_min	Integer		Minimum yardage. To supply meterage instead, see meterage_min.
yarn_held_together	Boolean		"true" if component yarns are all held together
yarn_list_type			
yarn_weight_id	Integer		Yarn weight ID. See yarn_weights.json

ForumPost

ForumPost

Attributes

Name	Type	Nullable	Description
created_at	Date		
deleted	Boolean		If deleted, this flag will be set to true and the post body will contain a deletion message
editable	Boolean		True if the current user can edit this post
id	Integer		
parent_post_id	Integer	Yes	Post ID of the parent post (the post that was replied to)
parent_post_number	Integer	Yes	Post number of the parent post (the post that was replied to)
post_number	Integer		

Name	Type	Nullable	Description
reply_count	Integer		The number of replies to this post
topic	Topic (list)		The topic (thread) containing the post
topic_id	Integer		
updated_at	Date		
user	User (small)		The user who authored the post

ForumPost (list)

Attributes

Name	Type	Nullable	Description
body			
body_html			
created_at	Date		
deleted	Boolean		If deleted, this flag will be set to true and the post body will contain a deletion message
editable	Boolean		True if the current user can edit this post
id	Integer		
parent_post_id	Integer	Yes	Post ID of the parent post (the post that was replied to)
parent_post_number	Integer	Yes	Post number of the parent post (the post that was replied to)
parent_post_user	(small)		
post_number	Integer		
reply_count	Integer		The number of replies to this post
topic_id	Integer		
updated_at	Date		
user	User (small)		The user who authored the post

ForumPost (full)

Attributes

Name	Type	Nullable	Description
body			
body_html			
created_at	Date		
deleted	Boolean		If deleted, this flag will be set to true and the post body will contain a deletion message
editable	Boolean		True if the current user can edit this post
id	Integer		
parent_post_id	Integer	Yes	Post ID of the parent post (the post that was replied to)

Name	Type	Nullable	Description
parent_post_number	Integer	Yes	Post number of the parent post (the post that was replied to)
parent_post_user	(small)		
post_number	Integer		
reply_count	Integer		The number of replies to this post
short_abstract			
topic_id	Integer		
updated_at	Date		
user	User (small)		The user who authored the post

ForumPost (export)

Attributes

Name	Type	Nullable	Description
body			
body_html			
created_at	Date		
deleted	Boolean		If deleted, this flag will be set to true and the post body will contain a deletion message
editable	Boolean		True if the current user can edit this post
id	Integer		
parent_post_id	Integer	Yes	Post ID of the parent post (the post that was replied to)
parent_post_number	Integer	Yes	Post number of the parent post (the post that was replied to)
post_number	Integer		
reply_count	Integer		The number of replies to this post
short_abstract			
topic_id	Integer		
updated_at	Date		

PatternLanguage

PatternLanguage

Attributes

Name	Type	Nullable	Description
created_at			
id	Integer		
language_id	Integer		
pattern_id	Integer		
updated_at			

PatternLanguage (list)

Attributes

Name	Type	Nullable	Description
created_at			
id	Integer		
language	Language (list)		Language
language_id	Integer		
pattern_id	Integer		
updated_at			

PatternLanguage (POST)

Attributes

Name	Type	Nullable	Description
id	Integer		
language_id	Integer		

ShopSchedule

ShopSchedule (shop)

Attributes

Name	Type	Nullable	Description
closed			
closing_time	Date		Closing time in local time. Note that a (useless) date is currently included but a timezone is not included.
day_name			
day_of_week			
opening_time	Date		Opening time in local time. Note that a (useless) date is currently included but a timezone is not included.

CombinedCart

CombinedCart (full)

Attributes

Name	Type	Nullable	Description
cart_items	Array, CartItem (full)		Contents of the cart

Name	Type	Nullable	Description
created_at	Date		
created_by_user_id	Integer		API user who created the cart
id	Integer		
shop_customer	ShopCustomer		Customer associated with the cart
updated_at	Date		

CombinedCart (POST)

Attributes

Name	Type	Nullable	Description
shop_customer	ShopCustomer (POST)		Customer associated with the cart

Printing

Printing (list)

Attributes

Name	Type	Nullable	Description
created_at	Date		
id	Integer		
pattern_id	Integer		
pattern_not_available	Boolean	Yes	"true" if this pattern is not currently available from the source
pattern_source	PatternSource		
pattern_source	PatternSource (list)		
primary_source	Boolean	Yes	"true" if this is the primary source for the pattern

Printing (public)

Attributes

Name	Type	Nullable	Description
created_at	Date		
id	Integer		
pattern_id	Integer		
pattern_source_id	Integer		
primary_source	Boolean	Yes	"true" if this is the primary source for the pattern

Printing (POST)

Attributes

Name	Type	Nullable	Description
id	Integer		
pattern_not_available	Boolean	Yes	"true" if this pattern is not currently available from the source
pattern_source_id	Integer		
primary_source	Boolean	Yes	"true" if this is the primary source for the pattern

ProductAttachment

ProductAttachment

Attributes

Name	Type	Nullable	Description
document	Array, Document		Details about the attached file
id	Integer		Product attachment ID
language_id	Integer		Language ID
product_id	Integer		Product ID

ProductAttachment (full)

Attributes

Name	Type	Nullable	Description
created_at	Date		Time when the record was created
deleted			
document	Array, Document		Details about the attached file
id	Integer		Product attachment ID
language_id	Integer		Language ID
product_id	Integer		Product ID
sort_order	Integer		Sort order
updated_at	Date		Time when the record was last updated

ProductAttachment (receipt)

Attributes

Name	Type	Nullable	Description
document	Array, Document		Details about the attached file
id	Integer		Product attachment ID
product_id	Integer		Product ID
product_title			

ProductAttachment (POST)

Attributes

Name	Type	Nullable	Description
language_id	Integer		Language ID
sort_order	Integer		Sort order

DraftPatternSource

DraftPatternSource (full)

Attributes

Name	Type	Nullable	Description
created_at	DateTime		
draft_pattern_id	Integer		
id	Integer		
isbn	String	Yes	
issue	String	Yes	
name	String	Yes	Draft pattern name
notes			
online	Boolean	Yes	
out_of_print	Boolean	Yes	
pattern_source	PatternSource (list)	Yes	
pattern_source_id	Integer	Yes	
pattern_source_type_id	Integer	Yes	
primary	Boolean	Yes	
print	Boolean	Yes	
published	DateTime	Yes	
publisher_business_id	Integer	Yes	The Pro account that the source belongs to
ravelry_ebook	Boolean	Yes	
ravelry_store	Boolean	Yes	
source_group_name	String	Yes	
updated_at	DateTime		
url	String	Yes	

DraftPatternSource (POST)

Attributes

Name	Type	Nullable	Description
id	Integer		

Name	Type	Nullable	Description
issue	String	Yes	
month_published	DateTime (POST)	Yes	Publication month. Day is ignored. (ex: 2022-05-01)
name	String	Yes	Draft pattern name
pattern_source_id	Integer	Yes	
pattern_source_type_id	Integer	Yes	
publisher_business_id	Integer	Yes	The Pro account that the source belongs to
url	String	Yes	

SavedSearch

SavedSearch (list)

Attributes

Name	Type	Nullable	Description
created_at	Date		
id	Integer		Saved search ID
last_loaded	Date		The last time this search was run by the user
search_parameters			
search_path			
search_type	String		One of: groups, patterns, stash, people, yarns, designers, projects, discussions, patternsources, events, fiberstashes
subscribed	Boolean		true if the user is "subscribed" to this search
subscription_updated_at			
title			
updated_at	Date		

DraftPattern

DraftPattern

Attributes

Name	Type	Nullable	Description
id	Integer		draft pattern ID
name	String		Draft pattern name
permalink	String		

DraftPattern (list)

Attributes

Name	Type	Nullable	Description
created_at			
created_by_user	(small)		
id	Integer		draft pattern ID
name	String		Draft pattern name
permalink	String		
updated_at			

DraftPattern (full)

Attributes

Name	Type	Nullable	Description
craft_id	Integer		
currency	String		3 letter currency code
downloadable	Boolean		"true" if the pattern is available digitally for download (anywhere)
draft_component_yarns	Array, DraftComponentYarn (full)		
draft_errata_links	Array, DraftErrataLink (full)		
draft_needle_sizes	Array, DraftNeedleSize (full)		
draft_pattern_author_name	String		
draft_pattern_sources	Array, DraftPatternSource (full)		
draft_pattern_yarns	Array, DraftPatternYarn (full)		
draft_use_default_pattern_author	Boolean		
draft_yardage_units	String		'M' for meters, 'Y' for yards
free	Boolean		
gauge	String		
gauge_divisor	String		
gauge_pattern	String		
gauge_repeats	String		
id	Integer		draft pattern ID
languages	Array, Language (list)		
name	String		Draft pattern name
notes			
notes_html	String		Notes (rendered as HTML)
only_available_with_yarn_purchase	Boolean		"true" if the pattern is only available with the purchase of a yarn

Name	Type	Nullable	Description
pattern_attributes	Array, PatternAttribute (list)		
pattern_categories	Array, PatternCategory (list)		
permalink	String		
prerelease_pattern_code	String	Yes	Tester code, for linking projects to a draft pattern, if any
price	Decimal		
published	Date		
published_pattern_id	Integer	Yes	ID of the published pattern that was created from this draft, if it has been published
row_gauge	Integer		
sizes_available	String		Sizes available (free form text list of sizes)
url	String		Primary non-Ravelry URL for information about this pattern (if one exists)
yardage_max	Integer		
yardage_min	Integer		
yarn_held_together	Boolean		"true" if component yarns are all held together
yarn_list_type	Integer		1 = all of the listed yarns are used in the pattern, 2 = only some of the listed yarns are used in the pattern (ie. the list contains suggested/alternative yarns)
yarn_weight_id	Integer		

DraftPattern (POST)

Attributes

Name	Type	Nullable	Description
craft_id	Integer		
currency	String		3 letter currency code
downloadable	Boolean		"true" if the pattern is available digitally for download (anywhere)
draft_business_id	Integer		
draft_component_yarns	Array, DraftComponentYarn (POST)		
draft_needle_sizes	Array, DraftNeedleSize (POST)		

Name	Type	Nullable	Description
draft_pattern_author_name	String		
draft_pattern_sources	Array, DraftPatternSource (POST)		
draft_pattern_yarns	Array, DraftPatternYarn (POST)		
draft_store_id	Integer	Yes	Pattern store to associate with this pattern
draft_yardage_units	String		'M' for meters, 'Y' for yards
free	Boolean		
gauge	String		
gauge_divisor	String		
gauge_pattern	String		
gauge_repeats	String		
name	String		Draft pattern name
notes	String		Notes (original/markdown format)
only_available_with_yarn_purchase	Boolean		"true" if the pattern is only available with the purchase of a yarn
pattern_classifications	Array, PatternClassification (POST)		
pattern_languages	Array, PatternLanguage (POST)		
pattern_taggings	Array, PatternTagging (POST)		
price	Decimal (POST)		
published	Date		
row_gauge	Integer		
sizes_available	String		Sizes available (free form text list of sizes)
url	String		Primary non-Ravelry URL for information about this pattern (if one exists)
yardage_max	Integer		
yardage_min	Integer		
yarn_held_together	Boolean		"true" if component yarns are all held together
yarn_list_type	Integer		1 = all of the listed yarns are used in the pattern, 2 = only some of the listed yarns are used in the pattern (ie. the list contains suggested/alternative yarns)
yarn_weight_id	Integer		

Collection

Collection (medium)

Attributes

Name	Type	Nullable	Description
id	Integer		
permalink	String		
tag_names	Array, String		
title	String		

Activity

Activity (list)

Attributes

Name	Type	Nullable	Description
activity_type_id	Integer		Activity type ID. A textual description is provided in activity_type_key
activity_type_key	String		String key for this activity type. ("added_project_photo", "queued_pattern", etc)
created_at	Date		Date/time of activity
descriptive_title	String		Name/title of the target with a qualifier (example: "Smith faved Neo's Hat")
id	Integer		Activity identifier
photo	Photo (small)		The photo associated with the activity
target_id	Integer		The target object associated with the activity (the target of "added_project_photo" is a Project, the target of "queued_pattern" is a QueuedProject, etc)
target_id	Integer		The target object associated with the activity (the target of "added_project_photo" is a Project, the target of "queued_pattern" is a QueuedProject, etc)
target_uri	String		URI for retrieving the target information. (Example: /projects/janesmith/mittens.json)
title	String		Name/title of the target
user	User (small)		The user that performed the activity

NeedleType

NeedleType

Attributes

Name	Type	Nullable	Description
description			
id			
length			
metric_name			
name			
needle_size_id			
type_name			

NeedleType (full)

Attributes

Name	Type	Nullable	Description
description			
id			
length			
metric_name			
name			
needle_size_id			
type_name			

StashStatus

StashStatus

Attributes

Name	Type	Nullable	Description
id			
name			

Message

Message (list)

Attributes

Name	Type	Nullable	Description
id	Integer		
message_type_name	String		

Name	Type	Nullable	Description
parent_message_id	Integer	Yes	ID of the parent message, if this message is a reply
read_message	Boolean		True if the message has been read
recipient	User		Message recipient
replied	Boolean		True the recipient replied to this message
replied_at	Date	Yes	Date a reply was sent
sender	User		Message sender
sent_at	Date		
subject	String		Message subject

Message (full)

Attributes

Name	Type	Nullable	Description
content_html			
folder_name	String		
id	Integer		
message_type_name	String		
parent_message_id	Integer	Yes	ID of the parent message, if this message is a reply
read_message	Boolean		True if the message has been read
recipient	User		Message recipient
replied	Boolean		True the recipient replied to this message
replied_at	Date	Yes	Date a reply was sent
sender	User		Message sender
sent_at	Date		
subject	String		Message subject

Message (export)

Attributes

Name	Type	Nullable	Description
content_html			
folder_name	String		
id	Integer		
message_type_name	String		
parent_message_id	Integer	Yes	ID of the parent message, if this message is a reply
read_message	Boolean		True if the message has been read
recipient	User		Message recipient
replied	Boolean		True the recipient replied to this message
replied_at	Date	Yes	Date a reply was sent
sender	User		Message sender

Name	Type	Nullable	Description
sent_at	Date		
subject	String		Message subject

Message (POST)

Attributes

Name	Type	Nullable	Description
content	String		Message body. Markdown and limited HTML is supported. (TODO: Rich Content documentation)
recipient_user_id	Integer	Yes	User to deliver the message to. One of recipient_user_id or recipient_login is required.
recipient_username	Integer	Yes	User to deliver the message to. One of recipient_user_id or recipient_username is required.
subject	String		Message subject

Friendship

Friendship (list)

Attributes

Name	Type	Nullable	Description
created_at	Date		Creation date
friend_avatar	Hash		Hash containing a large_photo_url (240x240 image), photo_url (100x100 image) and tiny_photo_url (25x25 image)
friend_id			
friend_user_id	Integer		User ID of the friend
friend_username	User		Friend user name
id	Integer		ID of this friendship record
tag_names	Array, String		List of user defined tag names

Friendship (full)

Attributes

Name	Type	Nullable	Description
created_at	Date		Creation date
friend_avatar	Hash		Hash containing a large_photo_url (240x240 image), photo_url (100x100 image) and tiny_photo_url (25x25 image)
friend_user	User		Complete user record for the friend
friend_user_id	Integer		User ID of the friend

Name	Type	Nullable	Description
friend_username	User		Friend user name
id	Integer		ID of this friendship record
tag_names	Array, String		List of user defined tag names

VolumeAttachment

VolumeAttachment

Attributes

Name	Type	Nullable	Description
bytes	Integer		Size of the attached file in bytes
content_type	String		Content type of the attached file. Currently only "application/pdf" is supported.
filename	String		Name of the attached file.
language_code	String	Yes	Language of the document, if available. ISO 639 language code
notes	String	Yes	Notes added by the file's uploader/seller. Generally blank or an explanation of file contents if a product includes more than one file.
product_attachment_id	Integer		Use the product attachment ID with /product_attachment/{id}/generate_download_link.json to get a direct link to this PDF.
ravelry_download_url	String		Ravelry URL that a user can view in a browser in order to download the file. Requires a normal Ravelry session / authentication (ie. username/password)
thumbnail_url	String		URL to a thumbnail of the file. Thumbnails are 150 pixels high. PDF thumbnails are typically 116 x 150.

UserSite

UserSite

Attributes

Name	Type	Nullable	Description
id			
social_site	SocialSite		Details about the external site
url	String		URL to profile page on an external site
username	String		Username on an external site

UserSite (full)

Attributes

Name	Type	Nullable	Description
id			
social_site	SocialSite		Details about the external site
url	String		URL to profile page on an external site
username	String		Username on an external site

FiberAttribute

FiberAttribute

Attributes

Name	Type	Nullable	Description
fiber_attribute_group_id	Integer		
id	Integer		
name	String		Short category name
permalink	String		

FiberAttributeGroup

FiberAttributeGroup

Attributes

Name	Type	Nullable	Description
id	Integer		
name	String		Short category name
parent_id	Integer		
permalink	String		

SocialSite

SocialSite

Attributes

Name	Type	Nullable	Description
active	Boolean		True if the site is currently shown on Ravelry profile pages
favicon_url			
id	Integer		
name	String		Name of the site

Yarn

Yarn

Attributes

Name	Type	Nullable	Description
certified_organic	Boolean		
discontinued	Boolean		
first_photo	Photo		
gauge_divisor	Integer		
grams	Integer		weight of a skein/ball of the yarn in grams
id	Integer		
machine_washable	Boolean		
max_gauge	Integer		
min_gauge	Integer		
name	String		
organic			
permalink	String		
rating_average	Float		
rating_count	Integer		
rating_total	Integer		
texture	String		(obsolete, this has been superseded by yarn attributes)
thread_size			
wpi	Integer		wraps per inch
yardage	Integer		
yarn_company_name	String		
yarn_weight	YarnWeight (list)		

Yarn (list)

Attributes

Name	Type	Nullable	Description
certified_organic	Boolean		
discontinued	Boolean		
first_photo	Photo		
gauge_divisor	Integer		
grams	Integer		weight of a skein/ball of the yarn in grams
id	Integer		
machine_washable	Boolean		
max_gauge	Integer		

Name	Type	Nullable	Description
min_gauge	Integer		
name	String		
organic			
permalink	String		
personal_attributes	Hash		Hash containing information related to this yarn's status in the current user's notebook (favorited, bookmark_id, stash_ids)
rating_average	Float		
rating_count	Integer		
rating_total	Integer		
texture	String		(obsolete, this has been superseded by yarn attributes)
thread_size			
wpi	Integer		wraps per inch
yardage	Integer		
yarn_company_name	String		
yarn_weight	YarnWeight (list)		

Yarn (stash_list)

Attributes

Name	Type	Nullable	Description
certified_organic	Boolean		
discontinued	Boolean		
gauge_divisor	Integer		
grams	Integer		weight of a skein/ball of the yarn in grams
id	Integer		
machine_washable	Boolean		
max_gauge	Integer		
min_gauge	Integer		
name	String		
notes_html_deprecated			
organic			
permalink	String		
photos_deprecated			
rating_average	Float		
rating_count	Integer		
rating_total	Integer		
texture	String		(obsolete, this has been superseded by yarn attributes)
thread_size			
wpi	Integer		wraps per inch
yardage	Integer		

Name	Type	Nullable	Description
yarn_company	YarnCompany (list)		
yarn_company_name	String		
yarn_weight	YarnWeight (list)		

Yarn (full)

Attributes

Name	Type	Nullable	Description
certified_organic	Boolean		
discontinued	Boolean		
gauge_divisor	Integer		
grams	Integer		weight of a skein/ball of the yarn in grams
id	Integer		
machine_washable	Boolean		
max_gauge	Integer		
max_hook_size			
max_needle_size			
min_gauge	Integer		
min_hook_size			
min_needle_size			
name	String		
notes_html	String		
organic			
permalink	String		
personal_attributes	Hash		Hash containing information related to this yarn's status in the current user's notebook (favorited, bookmark_id, stash_ids)
photos	Array, Photo (full)		
rating_average	Float		
rating_count	Integer		
rating_total	Integer		
texture	String		(obsolete, this has been superseded by yarn attributes)
thread_size			
wpi	Integer		wraps per inch
yardage	Integer		
yarn_attributes	Array, YarnAttribute (full)		Yarn attributes. Examples: "Superwash", "Gradient".
yarn_company	YarnCompany (full)		
yarn_fibers	Array, YarnFiber (full)		

Name	Type	Nullable	Description
yarn_provenance	Array, YarnProvenance (full)		Yarn provenance/origin records containing both a location and information about what was done at that location. Examples: "Dyed at (location)", "Milled in (location)".
yarn_weight	YarnWeight (full)		

Yarn (public)

Attributes

Name	Type	Nullable	Description
certified_organic	Boolean		
discontinued	Boolean		
gauge_divisor	Integer		
grams	Integer		weight of a skein/ball of the yarn in grams
id	Integer		
machine_washable	Boolean		
max_gauge	Integer		
max_hook_size			
max_needle_size			
min_gauge	Integer		
min_hook_size			
min_needle_size			
name	String		
notes_html	String		
permalink	String		
texture	String		(obsolete, this has been superseded by yarn attributes)
thread_size			
wpi	Integer		wraps per inch
yardage	Integer		
yarn_attribute_ids			
yarn_attribute_ids			
yarn_attributes	Array, YarnAttribute (public)		Yarn attributes. Examples: "Superwash", "Gradient".
yarn_company_id			
yarn_fibers	Array, YarnFiber (public)		
yarn_weight_id			

Yarn (oembed)

Attributes

Name	Type	Nullable	Description
currency_code			
name	String		
price			
title			
url			

Bookmark

Bookmark (list)

Attributes

Name	Type	Nullable	Description
comment	String		User defined comment
created_at	Date		
favorited	Object		The default output format for the favorited item is nested inside the result
id	Integer		Favorite ID
tag_list	String	Yes	Space delimited list of tags (tags cannot contain commas)
type	String		The type of item that was favorited. One of: project, pattern, yarn, stash, forumpost, designer, yarnbrand, yarnshop

Bookmark (full)

Attributes

Name	Type	Nullable	Description
bundles	Bundle (list)		The bundles that this favorite is a member of
comment	String		User defined comment
created_at	Date		
favorited	Object		The default output format for the favorited item is nested inside the result
id	Integer		Favorite ID
tag_list	String	Yes	Space delimited list of tags (tags cannot contain commas)
type	String		The type of item that was favorited. One of: project, pattern, yarn, stash, forumpost, designer, yarnbrand, yarnshop

Bookmark (export)

Attributes

Name	Type	Nullable	Description
bundles	Bundle (list)		The bundles that this favorite is a member of

Name	Type	Nullable	Description
comment	String		User defined comment
created_at	Date		
favorited	Object		The default output format for the favorited item is nested inside the result
id	Integer		Favorite ID
tag_list	String	Yes	Space delimited list of tags (tags cannot contain commas)
type	String		The type of item that was favorited. One of: project, pattern, yarn, stash, forumpost, designer, yarnbrand, yarnshop

Bookmark (POST)

Attributes

Name	Type	Nullable	Description
comment	String		User defined comment
favorited_id	String		The ID of the item that was favorited. May only be set during creation.
tag_list	String	Yes	List of tags, space delimited
type	String		The type of item that was favorited. One of: project, pattern, yarn, stash, forumpost, designer, yarnbrand, yarnshop. May only be set during creation.

PatternClassification

PatternClassification

Attributes

Name	Type	Nullable	Description
id	Integer		
pattern_category_id	Integer		
pattern_id	Integer		

PatternClassification (list)

Attributes

Name	Type	Nullable	Description
id	Integer		
pattern_category	Array, PatternCategory (list)		Pattern category
pattern_category_id	Integer		
pattern_id	Integer		

PatternClassification (POST)

Attributes

Name	Type	Nullable	Description
id	Integer		
pattern_category_id	Integer		

ShopCustomer

ShopCustomer

Attributes

Name	Type	Nullable	Description
created_at	Date		Date and time that the customer record was created
customer_reference	String	Yes	Usable by API clients - storage for reference information such as your customer ID, etc. Max length is 255 characters.
email_address	String	Yes	Customer email
id			
name	String	Yes	Customer name
shop	Shop (tiny)	Yes	The shop that the customer record is associated with
user	User (small)	Yes	The customer's Ravelry account
user_id	String	Yes	Customer's user ID

ShopCustomer (list)

Attributes

Name	Type	Nullable	Description
created_at	Date		Date and time that the customer record was created
customer_reference	String	Yes	Usable by API clients - storage for reference information such as your customer ID, etc. Max length is 255 characters.
email_address	String	Yes	Customer email
id			
name	String	Yes	Customer name
shop	Shop (tiny)	Yes	The shop that the customer record is associated with
user	User (small)	Yes	The customer's Ravelry account
user_id	String	Yes	Customer's user ID

ShopCustomer (POST)

Attributes

Name	Type	Nullable	Description
email_address	String	Yes	Customer email
name	String	Yes	Customer name
user_id	String	Yes	Customer's user ID

User

User

Attributes

Name	Type	Nullable	Description
id			
large_photo_url			
photo_url			
small_photo_url			
tiny_photo_url			
username			

User (small)

Attributes

Name	Type	Nullable	Description
id			
large_photo_url			
photo_url			
profile_country_code			
small_photo_url			
tiny_photo_url			
username			

User (full)

Attributes

Name	Type	Nullable	Description
about_me_html			
about_me			
fave_colors			
fave_curse			
first_name			
id			

Name	Type	Nullable	Description
large_photo_url			
location			
pattern_author	PatternAuthor (for_user)		The designer that is linked to this user
photo_url			
profile_country_code			
small_photo_url			
tiny_photo_url			
user_sites	UserSite (full)		Information about external social/etc sites that the user has added to their profile
username			

User (export)

Attributes

Name	Type	Nullable	Description
about_me_html			
about_me			
fave_colors			
fave_curse			
first_name			
id			
large_photo_url			
location			
pattern_author	PatternAuthor (for_user)		The designer that is linked to this user
photo_url			
profile_country_code			
small_photo_url			
tiny_photo_url			
user_sites	UserSite (full)		Information about external social/etc sites that the user has added to their profile
username			

User (POST)

Attributes

Name	Type	Nullable	Description
about_me	String	Yes	"About me" text. Can contain markdown and/or HTML
fave_colors			

Name	Type	Nullable	Description
fave_curse			
first_name			

PatternAuthor

PatternAuthor

Attributes

Name	Type	Nullable	Description
crochet_pattern_count	Integer		Number of crochet patterns attributed to the designer
favorites_count	Integer		Number of times the designer has been favorited
id	Integer		
knitting_pattern_count	Integer		Number of knitting patterns attributed to the designer
name	String		Designer's full name or alias
patterns_count	Integer		Number of patterns attributed to the designer
permalink	String		
users	Array, User (small)		User accounts linked to this designer

PatternAuthor (full)

Attributes

Name	Type	Nullable	Description
crochet_pattern_count	Integer		Number of crochet patterns attributed to the designer
favorites_count	Integer		Number of times the designer has been favorited
id	Integer		
knitting_pattern_count	Integer		Number of knitting patterns attributed to the designer
name	String		Designer's full name or alias
notes			
notes_html			
patterns_count	Integer		Number of patterns attributed to the designer
permalink	String		
users	Array, User (full)		User accounts linked to this designer

PatternAuthor (public)

Attributes

Name	Type	Nullable	Description
id	Integer		
name	String		Designer's full name or alias

Name	Type	Nullable	Description
permalink	String		

PatternAuthor (for_user)

Attributes

Name	Type	Nullable	Description
favorites_count	Integer		Number of times the designer has been favorited
id	Integer		
name	String		Designer's full name or alias
patterns_count	Integer		Number of patterns attributed to the designer
permalink	String		

Payment

Payment

Attributes

Name	Type	Nullable	Description
gross	Decimal		Gross amount of the payment
id	Integer		Payment ID
txn_id	Integer		PayPal transaction ID
txn_type	String		PayPal txn_type (will typically be "express_checkout")

Payment (sale)

Attributes

Name	Type	Nullable	Description
gross	Decimal		Gross amount of the payment
id	Integer		Payment ID
txn_id	Integer		PayPal transaction ID
txn_type	String		PayPal txn_type (will typically be "express_checkout")

Colorway

Colorway

Attributes

Name	Type	Nullable	Description
------	------	----------	-------------

Name	Type	Nullable	Description
code	String	Yes	Code, for yarns with numeric/etc colorway codes
id	Integer		
name	String		
yarn_id	Integer		

Colorway (full)

Attributes

Name	Type	Nullable	Description
code	String	Yes	Code, for yarns with numeric/etc colorway codes
id	Integer		
name	String		
photo_url			
projects_count	Integer		Number of projects using this colorway
stashes_count	Integer		Number of stashes using this colorway
usage_count			
yarn_id	Integer		

Craft

Craft (list)

Attributes

Name	Type	Nullable	Description
id	Integer		
name	String		
permalink	String		

Cross-Origin Resource Sharing (CORS)

CORS headers are set when making requests to api.ravelry.com

- If your Authorization header includes a valid OAuth2 token, Access-Control-Allow-Origin is set to your list of redirect URIs
- If you are using a different type of token or you are making a preflight OPTIONS request, Access-Control-Allow-Origin will match the Origin of your request
- If something is wrong, Access-Control-Allow-Origin is set to this page. Make sure that you are requesting a JSON document from api.ravelry.com and that you are using a valid API key.

Use Etags to eliminate redundant result retrieval

- In any API call, you will be sent an HTTP header called "Etag"
- When you next make that API call again, send the etag value back to the API server in an "If-None-Match" HTTP Header. Etags are quoted so be sure to include the quotes in your header value.

If-None-Match: "MyEtagValue"

- If the result has changed, you'll get the new results.

If the result has not changed, you'll get an HTTP 304 Not Modified and you can serve up a cached result instead of retrieving it over the network.

"Polling" for unread messages, etc

If you include the "extras=1" parameter in any API call, an object containing current message counts and other realtime-ish information will be included in the results.

Currently: extras: { unread_messages_count: 1, unread_forum_replies: 0 }

Activity Feeds

Pattern database additions and updates

A simple feed of recently added and updated patterns is available at <https://api.ravelry.com/feeds/v1/patterns>.

Usage tips:

1. If you have an ETag from the last time you requested the URL, supply the value in the 'If-Modified-Since' header. You will receive a 304 Not Modified response if nothing has changed since the last request.
2. If something has changed or if you did not supply an 'If-Modified-Since' header, you'll see the feed. Save the 'ETag' header for next time.
3. If the date of the oldest record in the feed is still newer than the last time that you checked it, use the 'previous_page_url' to get the next page of older results.

Debugging requests

Your app's last 100 requests are visible in the debug log section of your App control panel in your Ravelry Pro account (<http://www.ravelry.com/pro>)

If you would like the JSON responses to be logged as well, include a `debug=1` parameter in your requests. You may not enable response logging without the permission from the user.

automatically generated Last updated 2026-03-30